

**FINAL REPORT NUMBER: SINCAP-TRC-19-002**

**NEW CAR ASSESSMENT PROGRAM (NCAP)  
MOVING DEFORMABLE BARRIER SIDE IMPACT TEST**

**GENERAL MOTORS LLC  
2019 Cadillac XT4 SUV  
NHTSA NUMBER: M20190102**

**PREPARED BY:  
Transportation Research Center Inc.  
10820 State Route 347  
P. O. Box B-67  
East Liberty, OH 43319**



**Report Date: May 13, 2019**

**FINAL REPORT**

**PREPARED FOR:  
U.S. DEPARTMENT OF TRANSPORTATION  
National Highway Traffic Safety Administration  
Office of Crashworthiness Standards  
Mail Code: NRM-110  
1200 New Jersey Ave, SE, Room W43-410  
Washington, D.C. 20590**

This publication is distributed by the U.S. Department of Transportation, National Highway Traffic Safety Administration, in the interest of information exchange. The opinions, findings, and conclusions expressed in this publication are those of the author(s) and not necessarily those of the Department of Transportation or the National Highway Traffic Safety Administration. The United States Government assumes no liability for its contents or use thereof.

If trade or manufacturers' names or products are mentioned, it is only because they are considered essential to the object of the publication and should not be construed as an endorsement.

Report Prepared By: ILO Project Operations Group

Report Approved By: 

John Shultz

Approval Date: May 13, 2019

FINAL REPORT ACCEPTANCE BY OCWS:

---

Division Chief, New Car Assessment Program  
NHTSA, Office of Crashworthiness Standards

Date: \_\_\_\_\_

---

COTR, New Car Assessment Program  
NHTSA, Office of Crashworthiness Standards

Date: \_\_\_\_\_



Technical Report Documentation Page

1. Report No. SINCAP-TRC-19-002	2. Government Accession No.	3. Recipient's Catalog No.																																																									
4. Title and Subtitle Final Report of New Car Assessment Program Side Impact MDB Testing of a 2019 Cadillac XT4 SUV, NHTSA No.: M20190102		5. Report Date May 13, 2019																																																									
		6. Performing Organization Code TRC Inc.																																																									
7. Author(s) John Shultz, Project Manager		8. Performing Organization Report Number 190221																																																									
9. Performing Organization Name and Address Transportation Research Center Inc. 10820 State Route 347 East Liberty, OH 43319		10. Work Unit No.																																																									
		11. Contract or Grant No. DTNH22-14-D-00354																																																									
12. Sponsoring Agency Name and Address U.S. Department of Transportation National Highway Traffic Safety Administration Office of Crashworthiness Standards (NRM-110) 1200 New Jersey Ave, SE, Room W43-410 Washington, DC 20590		13. Type of Report and Period Covered Final Test Report February 21, 2019 – May 13, 2019																																																									
		14. Sponsoring Agency Code NRM-110																																																									
15. Supplemental Notes																																																											
16. Abstract <p>This 55 / 28 km/h 90° Moving Deformable Barrier SINCAP Side Impact Test was conducted on the subject 2019 Cadillac XT4 SUV, in accordance with the specifications of the Office of Crashworthiness Standards Test Procedure for the generation of consumer information on vehicle side crash protection. This test was conducted by Transportation Research Center Inc. in East Liberty, Ohio, on February 21, 2019.</p> <p>The impact velocity of the Moving Deformable Barrier (MDB) was 61.83 km/h, and the ambient temperature at the struck (left) side of the target vehicle at the time of impact was 21.7° C. The target vehicle post-test maximum crush was 225 mm at Level 3. The test vehicle's performance was as follows:</p> <table border="1"> <thead> <tr> <th colspan="4">Driver ATD (ES-2re)</th> </tr> <tr> <th>Measurement Description</th> <th>Units</th> <th>IARV</th> <th>Result</th> </tr> </thead> <tbody> <tr> <td>Head Injury Criteria (HIC<sub>36</sub>)</td> <td>N/A</td> <td>1000</td> <td>114</td> </tr> <tr> <td>Maximum Thoracic Rib Deflection</td> <td>mm</td> <td>44</td> <td>19.1</td> </tr> <tr> <td>Total Abdominal Force</td> <td>N</td> <td>2500</td> <td>824.6</td> </tr> <tr> <td>Pubic Symphysis Force</td> <td>N</td> <td>6000</td> <td>-1458.7</td> </tr> <tr> <td>Lower Spine Acceleration</td> <td>G</td> <td>82*</td> <td>26.1</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th colspan="4">Passenger ATD (SID-IIs)</th> </tr> <tr> <th>Measurement Description</th> <th>Units</th> <th>IARV</th> <th>Result</th> </tr> </thead> <tbody> <tr> <td>Head Injury Criteria (HIC<sub>36</sub>)</td> <td>N/A</td> <td>1000</td> <td>169</td> </tr> <tr> <td>Lower Spine Resultant Acceleration</td> <td>g's</td> <td>82</td> <td>51.3</td> </tr> <tr> <td>Total Pelvic Force (sum of acetabular and iliac forces)</td> <td>N</td> <td>5525</td> <td>2661.9</td> </tr> <tr> <td>Maximum Thoracic Rib Deflection</td> <td>mm</td> <td>38*</td> <td>35.4</td> </tr> <tr> <td>Maximum Abdominal Rib Deflection</td> <td>mm</td> <td>45*</td> <td>47.8</td> </tr> </tbody> </table> <p>* Proposed IARV</p> <p>The doors on the struck side of the vehicle did not separate from the body at the hinges or latches and the opposite doors did not open during the side impact event.</p>				Driver ATD (ES-2re)				Measurement Description	Units	IARV	Result	Head Injury Criteria (HIC <sub>36</sub> )	N/A	1000	114	Maximum Thoracic Rib Deflection	mm	44	19.1	Total Abdominal Force	N	2500	824.6	Pubic Symphysis Force	N	6000	-1458.7	Lower Spine Acceleration	G	82*	26.1	Passenger ATD (SID-IIs)				Measurement Description	Units	IARV	Result	Head Injury Criteria (HIC <sub>36</sub> )	N/A	1000	169	Lower Spine Resultant Acceleration	g's	82	51.3	Total Pelvic Force (sum of acetabular and iliac forces)	N	5525	2661.9	Maximum Thoracic Rib Deflection	mm	38*	35.4	Maximum Abdominal Rib Deflection	mm	45*	47.8
Driver ATD (ES-2re)																																																											
Measurement Description	Units	IARV	Result																																																								
Head Injury Criteria (HIC <sub>36</sub> )	N/A	1000	114																																																								
Maximum Thoracic Rib Deflection	mm	44	19.1																																																								
Total Abdominal Force	N	2500	824.6																																																								
Pubic Symphysis Force	N	6000	-1458.7																																																								
Lower Spine Acceleration	G	82*	26.1																																																								
Passenger ATD (SID-IIs)																																																											
Measurement Description	Units	IARV	Result																																																								
Head Injury Criteria (HIC <sub>36</sub> )	N/A	1000	169																																																								
Lower Spine Resultant Acceleration	g's	82	51.3																																																								
Total Pelvic Force (sum of acetabular and iliac forces)	N	5525	2661.9																																																								
Maximum Thoracic Rib Deflection	mm	38*	35.4																																																								
Maximum Abdominal Rib Deflection	mm	45*	47.8																																																								
17. Key Words New Car Assessment Program (NCAP) Side Impact MDB ES-2re SID-IIs		18. Distribution Statement Copies of this report are available from: National Highway Traffic Safety Administration Technical Information Services Division, NPO-411 1200 New Jersey Ave, SE Washington, DC 20590 e-mail: <a href="mailto:tis@nhtsa.dot.gov">tis@nhtsa.dot.gov</a> FAX: 202-493-2833																																																									
19. Security Classification (of this report) Unclassified	20. Security Classification (of this page) Unclassified	21. Number of Pages 215	22. Price																																																								

## TABLE OF CONTENTS

<u>Section</u>		<u>Page No.</u>
1	Test Purpose and Procedure	1
2	Summary of Test Results	2
3	Occupant and Vehicle Information	4
<u>Appendix</u>		
A	Photographs	A-1
B	Vehicle and Dummy Response Data Plots	B-1
C	Dummy Performance Calibration Test Data	C-1
D	Test Equipment and Instrumentation Calibration Data	D-1
<u>Data Sheet No.</u>		<u>Page No.</u>
1	General Test and Vehicle Parameter Data	5
2	Seat, Seat Belt, Steering Wheel Adjustment and Fuel Systems Data	8
3	Dummy Longitudinal Clearance Dimensions	11
4	Dummy Lateral Clearance Dimensions	12
5	Camera and Instrumentation Data	13
6	Test Vehicle Accelerometer Locations	14
7	MDB Accelerometer Locations	15
8	Post-Test Observations	16
9	MDB Summary of Results	18
10	Test Vehicle Profile Measurements	19
11	Test Vehicle Exterior Crush Measurements	20
12	MDB Exterior Static Crush Measurements	23
13	Vehicle and MDB Damage Distances	24
14	FMVSS No. 301 Static Rollover Results	25
15	Dummy/Vehicle Temperature and Humidity Stabilization	26

**SECTION 1**  
**TEST PURPOSE AND PROCEDURE**

**TEST PURPOSE AND PROCEDURE**

This moving deformable barrier side impact test was conducted as part of the MY 2019 New Car Assessment Program Side Impact Test Program, sponsored by the National Highway Traffic Safety Administration (NHTSA), under Contract No. DTNH22-14-D-00354. The purpose of this test is to generate comparative side impact performance in a 2019 Cadillac XT4 SUV. The side impact test was conducted in accordance with the Office of Crashworthiness Standard's Laboratory Test Procedure dated October 2015.

## SECTION 2

### SUMMARY OF TEST RESULTS

A 2019 Cadillac XT4 SUV was impacted on the left (driver's) side by a Moving Deformable Barrier (MDB) which was moving forward in a 27° crabbed position to the tow road guidance system at a velocity of 61.83 km/h (38.42 mph). The target vehicle was stationary and was positioned at an angle of 63° to the line of forward motion. The side impact test was conducted by the Transportation Research Center Inc. in East Liberty, Ohio, on February 21, 2019. Pre-test and post-test photographs of the test vehicle and the MDB and the dummies (ES-2-re and SID-IIs) are included in this report.

Dummies were placed in the driver and left rear designated seating positions according to instructions specified in the OCWS Side Impact Laboratory Test Procedure, dated October 2015. The side impact event was documented by 11 cameras. Camera locations are included in this report.

The dummies were instrumented in the following manner:

**DRIVER ATD (ES-2re)**

Primary and redundant head CG tri-axial accelerometers

Chest upper rib, middle rib, and lower rib y-axis displacement potentiometers

Abdomen forward, middle, and rear y-axis load cells

Lower spine (T12) tri-axial accelerometers

Pubic symphysis y-axis load cell

**PASSENGER ATD (SID-IIs)**

Primary and redundant head CG triaxial accelerometers

Chest upper rib, middle rib, and lower rib y-axis displacement potentiometers

Abdomen upper rib and lower rib y-axis displacement potentiometers

Lower spine (T12) tri-axial accelerometers

Acetabulum and iliac wing y-axis load cells

APPENDIX B contains the vehicle and dummy response data. Dummy configuration and performance verification data can be found in APPENDIX C of this report. APPENDIX D of this report contains the test equipment and instrumentation calibration data.

Dummy injury readings were recorded as follows:

Measurement Description	Driver ATD (ES-2-re)		
	Units	Threshold	Result
Head Injury Criteria (HIC <sub>36</sub> )	N/A	1000	114
Maximum Thoracic Rib Deflection	mm	44	19.1
Combined Abdominal Force	N	2500	824.6
Pubic Symphysis Force	N	6000	-1458.7
Lower Spine (T12) Resultant Acceleration	G	82*	26.1

\* Proposed IARV

Measurement Description	Passenger ATD (SID-IIs)		
	Units	Threshold	Result
Head Injury Criteria (HIC <sub>36</sub> )	N/A	1000	169
Lower Spine (T12) Resultant Acceleration	G	82	51.3
Total Pelvic Force (sum of acetabular and iliac forces)	N	5525	2661.9
Maximum Thoracic Rib Deflection	mm	38*	35.4
Maximum Abdominal Rib Deflection	mm	45*	47.8

\* Proposed IARV

Supplemental Restraint Information is given below:

Restraint Type	Left Front (Driver) Occupant Location 1		Left Rear (Passenger) Occupant Location 4	
	Mounted	Deployed	Mounted	Deployed
Frontal Airbag	Yes	No		
Side Curtain Airbag	Yes	Yes	Yes	Yes
Side Torso/Pelvis Airbag	Yes	Yes	No	N/A
Side Pelvis Airbag	No	N/A	No	N/A
Knee Airbag	Yes	No	No	N/A
Seat Belt Pretensioner	Yes	Yes	No	N/A
Seat Belt Load Limiter	Yes	Unknown	No	N/A
Other Safety Restraint	No	N/A	No	N/A

### GENERAL COMMENTS

All doors remained closed throughout the test. No fuel spillage occurred during the impact or the static rollover test which followed. Injury values for the driver were within the established performance thresholds. Injury values for the passenger Maximum Abdominal Rib Deflection exceeded the performance threshold.

Left Lower A-Post Acceleration (Y); Questionable data throughout

Left Middle A-Post Acceleration (Y); Channel failed at 32.0 ms

Left Lower B-Post Acceleration (Y); Channel failed at 32.0 ms

**SECTION 3**  
**OCCUPANT AND VEHICLE INFORMATION**

**DATA SHEET NO. 1  
GENERAL TEST AND VEHICLE PARAMETER DATA**

Test Vehicle: 2019 Cadillac XT4 SUV  
Test Program: SINCAP Side Impact

NHTSA No.: M20190102  
Test Date: 2/21/2019

**TEST VEHICLE INFORMATION AND OPTIONS**

NHTSA No.	M20190102
Model Year	2019
Make	Cadillac
Model	XT4
Body Style	MPV
VIN	1GYAZAR45KF122319
Body Color	Radiant Silver Metallic
Odometer Reading (km/mi)	128 mi
Engine Displacement (L)	2.0
Type/No. Cylinders	Gas/4
Engine Placement	Front Transverse
Transmission Type	Automatic
Transmission Speeds	9
Overdrive	Yes
Final Drive	FWD
Roof Rack	No
Sunroof/T-Top	No
Running Boards	No
Tilt Steering Wheel	Yes
Power Seats	Yes
Anti-Lock Brakes (ABS)	Yes

Traction Control System (TCS)	Yes
Auto-Leveling System	No
Automatic Door Locks (ADL)	Yes
Power Window Auto-Reverse	Yes
Other Optional Feature	No
Driver Front Airbag	Yes
Driver Curtain Airbag	Yes
Driver Head/Torso Airbag	No
Driver Torso Airbag	No
Driver Torso/Pelvis Airbag	Yes
Driver Pelvis Airbag	No
Driver Knee Airbag	Yes
Rear Pass. Curtain Airbag	Yes
Rear Pass. Head/Torso Airbag	No
Rear Pass. Torso Airbag	No
Rear Pass. Torso/Pelvis Airbag	No
Rear Passenger Pelvis Airbag	No
Driver Seat Belt Pretensioner	Yes
Rear Pass. Seat Belt Pretensioner	No
Driver Load Limiter	Yes
Rear Passenger Load Limiter	No
Other Safety Restraint	No

Does owner's manual provide instructions to turn off automatic door locks? No

**DATA FROM CERTIFICATION LABEL**

Manufactured By	GENERAL MOTORS LLC
Date of Manufacture	10/18
Vehicle Type	MPV

GVWR (kg)	2250
GAWR Front (kg)	1220
GAWR Rear (kg)	1200

**VEHICLE SEATING AND CAPACITY WEIGHT INFORMATION**

Measured Parameter	Front	Rear	Third	Total
Designated Seating Capacity (DSC)	2	3	N/A	5
Capacity Weight (VCW) (kg)				511.0
DSC x 68.04 (kg)				340.2
Cargo Weight (RCLW) (kg)				170.8


**VEHICLE SEAT TYPE**

Seating Location	Type of Seat Pan				Type of Seat Back		
	Bucket	Bench	Split Bench	Contoured	Fixed	Adjustable	
						w/ Lever	w/ Knob
Front Seat	Yes	N/A	N/A		N/A	N/A	Yes
Rear or Second Row Seat	N/A	N/A	Yes	Yes	Yes	N/A	N/A
Third Row Seat	N/A	N/A	N/A	N/A	N/A	N/A	N/A

**DATA SHEET NO. 1 (CONTINUED)**  
**GENERAL TEST AND VEHICLE PARAMETER DATA**

Test Vehicle: 2019 Cadillac XT4 SUV  
 Test Program: SINCAP Side Impact

NHTSA No.: M20190102  
 Test Date: 2/21/2019



**DATA FROM TIRE PLACARD**

Measured Parameter	Front	Rear
Maximum Tire Pressure (kPa)	350	350
Cold Pressure (kPa)	240	240
Recommended Tire Size	235/60R18 H	235/60R18 H
Tire Size on Vehicle	235/60R18 H	235/60R18 H
Tire Manufacturer	Continental	Continental
Tire Model	Pro Contact TX	Pro Contact TX
Treadwear	500	500
Traction	A	A
Temperature Grades	A	A
Tire Plies Sidewall	2	2
Tire Plies Body	5	5
Load Index/Speed Symbol	103 H	103 H
Tire Material	Polyester/Steel/Polyamide	Polyester/Steel/Polyamide
DOT Safety Code Left	A345 WD77 4118	A345 WD77 4118
DOT Safety Code Right	A345 WD77 4118	A345 WD77 4118



**DATA SHEET NO. 1 (CONTINUED)  
GENERAL TEST AND VEHICLE PARAMETER DATA**

Test Vehicle: 2019 Cadillac XT4 SUV  
Test Program: SINCAP Side Impact

NHTSA No.: M20190102  
Test Date: 2/21/2019

**TIRE PRESSURES**

	Units	LF	RF	LR	RR
As Delivered	kPa	240	240	240	240
Tire Placard	kPa	240	240	240	240
Owner's Manual	kPa	240	240	240	240
As Tested	kPa	240	240	240	240

**MDB TIRE SPECIFICATIONS**

	Units	Requirement	LF	RF	LR	RR
Tire Size		P205/75R15	P205/75R15	P205/75R15	P205/75R15	P205/75R15
Tire Pressure	kPa	200 ± 21 kPa	207	207	207	207

**TEST VEHICLE AXLE WEIGHTS**

	Units	As Delivered (UVW)			As Tested (ATW)			Fully Loaded		
		Front Axle	Rear Axle	Total	Front Axle	Rear Axle	Total	Front Axle	Rear Axle	Total
Left	kg	490.0	349.6		529.8	452.6		543.4	474.8	
Right	kg	492.8	314.2		513.6	404.4		493.0	396.4	
Ratio	%	59.7	40.3		54.9	45.1		54.3	45.7	
Totals	kg	982.8	663.8	1646.6	1043.4	857.0	1900.4	1036.4	871.2	1907.6

**TARGET TEST WEIGHT CALCULATION**

Measured Parameter	Units	Value	
Total As Delivered Weight (UVW)	kg	1646.6	(A)
Actual Weight of 1 P572V ATD (SID-Its) Dummy Used	kg	125.0	(B)
Rated Cargo/Luggage Weight (RCLW) <sup>1</sup>	kg	136.0	(C)
Calculated Vehicle Target Weight (TVTW)	kg	1907.6	(A+B+C)

Does the measured As Tested Vehicle Weight lie within the required weight range (i.e. Calculated Test Vehicle Target Weight – 4.5 kg to 9 kg)?  YES  NO

**TEST VEHICLE ATTITUDES AND CG**

Measurement Description	Units	Fully Loaded	As Tested	Meets Requirement
LF	mm	790	784	Yes
RF	mm	800	797	Yes
RR	mm	808	810	Yes
LR	mm	790	794	Yes
Vehicle CG (Aft of Front Axle)	mm	1267	1251	
Vehicle CG (Left(+)/Right(-) from Longitudinal Centerline)	mm	+54	+27	

\*\*\*The "As Tested" vehicle attitude measurements must be equal to or within ± 10 mm of the "Fully Loaded" vehicle attitude measurements at each wheel well. Indicate "Yes" or "No" for "Meets Requirement".

Test height adjustable suspension setting, if applicable:

N/A

**WEIGHT OF BALLAST AND VEHICLE COMPONENTS REMOVED TO MEET TVTW**

Component Description	Weight (kg)
Ballast: Steel plate mounted in cargo area	95.3
Removed: None	0.0

<sup>1</sup> Rated cargo and luggage weight limited to 136.0 kg or 300.0 lbs.

**DATA SHEET NO. 2**  
**SEAT, SEAT BELT, STEERING WHEEL ADJUSTMENT AND FUEL SYSTEM DATA**

Test Vehicle: 2019 Cadillac XT4 SUV  
 Test Program: SINCAP Side Impact

NHTSA No.: M20190102  
 Test Date: 2/21/2019

**SEAT POSITIONING**

The driver seat, front center seat (if applicable), and right front passenger's seat should be set to the mid-track, lowest, mid-angle position. The struck-side rear passenger's seat, rear center seat, and non-struck side rear passenger's seats should be set to the rear-most, lowest, mid-angle position.

**SCRL ANGLE RANGE**

Seat	SCRL(°)		
	Max.	Min.	Mid
Driver Seat	18.4	9.9	14.2
Front Passenger Seat	16.2	11.7	14.0
Front Center Seat*	N/A	N/A	N/A
Struck Side Rear Seat	Fixed	N/A	11.6
Non-Struck Side Rear Seat	Fixed	N/A	11.6
Rear Center Seat*	Fixed	N/A	11.0

\* If applicable.

**SEAT HEIGHT AND ANGLE**

Seat	As Tested SCRL Angle (Mid) (°)	As Tested SCRP Height (mm)	SCRP Height Position	SCRP Height (mm)		
				Rearmost	Mid-Fore/Aft	Forward-Most
Driver Seat	14.2	182	Max	235	233	231
			Mid	210	208	206
			Min	184	182	180
Front Passenger Seat	14.0	188	Max	N/A	N/A	N/A
			Mid	184	188	188
			Min	N/A	N/A	N/A
Front Center Seat*	N/A	N/A	Max	N/A	N/A	N/A
			Mid	N/A	N/A	N/A
			Min	N/A	N/A	N/A
Struck Side Rear Seat	11.6	Fixed	Max	N/A	N/A	N/A
			Mid	N/A	N/A	N/A
			Min	N/A	N/A	N/A
Non-Struck Side Rear Seat	11.6	Fixed	Max	N/A	N/A	N/A
			Mid	N/A	N/A	N/A
			Min	N/A	N/A	N/A
Rear Center Seat*	11.0	Fixed	Max	N/A	N/A	N/A
			Mid	N/A	N/A	N/A
			Min	N/A	N/A	N/A

\* If applicable.

**DATA SHEET NO. 2 (CONTINUED)**  
**SEAT, SEAT BELT, STEERING WHEEL ADJUSTMENT AND FUEL SYSTEM DATA**

Test Vehicle: 2019 Cadillac XT4 SUV  
 Test Program: SINCAP Side Impact

NHTSA No.: M20190102  
 Test Date: 2/21/2019


**SEAT FORE/AFT POSITION**

Seat	Total Fore/Aft Travel		Test Position from Forwardmost Position	
	mm	Detents	mm	Detent
Driver Seat	240	N/A	120	N/A
Front Passenger Seat	240	N/A	120	N/A
Front Center Seat*	N/A	N/A	N/A	N/A
Struck Side Rear Seat	0	Fixed	N/A	Fixed
Non-Struck Side Rear Seat	0	Fixed	N/A	Fixed
Rear Center Seat*	0	Fixed	N/A	Fixed

\* If applicable

**SEAT BACK ANGLE ADJUSTMENT**

The driver's seat back is positioned to the manufacturer's designated seat back angle. The front center and front passenger's seat backs are positioned in a similar manner as the driver's seat back. The struck side rear seat back is positioned such that the dummy's head is level. The rear center and non-struck side rear outboard seat backs are positioned in a similar manner as the struck-side rear seat back.



Seat	Total Seat Back Angle Range		Test Position from Most Upright	
	Degrees	Detents	Degrees	Detent
Driver Seat w/ Seated Dummy	66.0	N/A	-8.9	N/A
Front Passenger Seat	65.4	N/A	-8.9	N/A
Front Center Seat*	N/A	N/A	N/A	N/A
Struck Side Rear Seat w/ Seated Dummy	0	Fixed	20.1	N/A
Non-Struck Side Rear Seat	0	Fixed	19.5	N/A
Rear Center Seat*	0	Fixed	19.8	N/A

\* If applicable

**SEAT BELT ANCHORAGE ADJUSTMENT**

Seat belt anchorages are adjusted in accordance with the information provided by the manufacturer on Form No. 1.

	Total # of Positions	Placed in Position #
Driver Seat	4	1, Full Up
Rear Seat	Fixed	Fixed

**HEAD RESTRAINT ADJUSTMENT**

The driver's head restraint is adjusted to the highest and most full forward in-use position. The struck-side rear passenger's head restraint is adjusted to the lowest and most full forward in-use position.

	Total # of Positions	Placed in Position #
Driver Seat	9	1, Uppermost
Rear Seat	5	5, Lowermost

**DATA SHEET NO. 2 (CONTINUED)**  
**SEAT, SEAT BELT, STEERING WHEEL ADJUSTMENT AND FUEL SYSTEMS DATA**


Test Vehicle: 2019 Cadillac XT4 SUV  
 Test Program: SINCAP Side Impact

NHTSA No.: M20190102  
 Test Date: 2/21/2019

**STEERING COLUMN ADJUSTMENT**

Steering wheel and column adjustments are made so that the steering wheel hub is at the center of its geometric locus it describes when it moves through its full range of motion.


	Degrees	Fore/Aft Position (mm)
Lowermost, Position No. 1	21.7	0
Geometric Center, Position No. 2	23.8	30
Uppermost, Position No. 3	26.0	60
Telescoping Steering Wheel Travel		60
Test Position	23.8	30



**FUEL PUMP**

Describe the fuel pump type, details about how it operates, and the location of the fuel filler neck.

With the key on (run mode) the pump will keep the lines pressurized.



**FUEL TANK CAPACITY**


	Liters
Usable Capacity of "Standard Tank" (see Form No. 1)	60.2
Usable Capacity of "Optional Tank" (see Form No. 1)	61.7
Usable Capacity of Standard Tank (see Owner's Manual)	60.2
Usable Capacity of Optional Tank (see Owner's Manual)	61.7
93% of Usable Capacity	56.0
Actual Amount of Solvent Used in Test	56.0
1/3 of Usable Capacity	20.1

Is the Actual Amount of Solvent Used in the test equal to 93% ± 1% of the Usable Capacity stated in on Form No. 1?       YES       NO

**DATA SHEET NO. 3  
DUMMY LONGITUDINAL CLEARANCE DIMENSIONS**

Test Vehicle: 2019 Cadillac XT4 SUV  
Test Program: SINCAP Side Impact

NHTSA No.: M20190102  
Test Date: 2/21/2019



**LEFT SIDE VIEW**

NOTE: 2-DOOR VEHICLE SHOWN.  
REAR DUMMY PHX & PHZ  
MEASUREMENTS FOR A 4-DOOR  
VEHICLE WOULD USE THE C-POST  
STRIKER AS A REFERENCE POINT


**DUMMY LONGITUDINAL CLEARANCE DIMENSION INFORMATION**

Driver Code	Pass. Code	Measurement Description	Driver		Passenger	
			Length (mm)	Angle	Length (mm)	Angle
HH		Header to Header	527			
HW		Header to Windshield	805			
HZ	HZ	Head to Roof Liner	232		267	
NR	NB	Nose to Rim/Seat Back	557		528	
CD	CB	Chest to Dash/Seat Back	663		458	
CS		Chest to Steering Wheel	472			
KD(L)/KDA(L) <sup>°</sup>	KB(L)/KBA(L) <sup>°</sup>	Left Knee to Dash/Seat Back	245	25.6	181	26.8
KD(R)/KDA(R) <sup>°</sup>	KB(R)/KBA(R) <sup>°</sup>	Right Knee to Dash/Seat Back	235	24.9	186	26.4
PAX <sup>°</sup>	PAX <sup>°</sup>	Pelvic Tilt Angle X		0.4		0.1
	PAY <sup>°</sup>	Pelvic Tilt Angle Y				21.6
PHX	PHX	Hip Point to Striker (X-Axis)	95		241	
PHZ	PHZ	Hip Point to Striker (Z-Axis)	153		214	

**DATA SHEET NO. 4  
DUMMY LATERAL CLEARANCE DIMENSIONS**

Test Vehicle: 2019 Cadillac XT4 SUV  
 Test Program: SINCAP Side Impact

NHTSA No.: M20190102  
 Test Date: 2/21/2019




**FRONT VIEW OF DUMMY**

Code	Description	Units	Driver	Passenger
HR	Head to Side Header	mm	235	262
HS	Head to Side Window	mm	363	365
AD	Arm to Door	mm	103	144
HD	H-Point to Door	mm	158	132

**DATA SHEET NO. 5  
CAMERA AND INSTRUMENTATION DATA**

Test Vehicle: 2019 Cadillac XT4 SUV  
Test Program: SINCAP Side Impact

NHTSA No.: M20190102  
Test Date: 2/21/2019



**CAMERA LOCATIONS AND DATA**

No.	Camera View	Coordinates (mm)			Lens Length (mm)	Operating Frame Rate (fps)
		X	Y	Z		
1	Overhead Overall	-160	1150	5692	8.5	1000
2	Overhead Close-up	0	770	5692	28	1000
3	Left Impact Point (MDB)	1494	0	847	25	1000
4	Side Overall (MDB)	2420	0	1471	12.5	1000
5	Rear	0	7300	1235	20	1000
6	Left Front	2661	-4432	1206	20	1000
7	Driver Front (OB)				25	1000
8	Driver Side (OB)				12.5	1000
9	Passenger Side (OB)				12.5	1000
10	Real-time Left Rear				Zoom	30
11	Real-time Inrun	Zoom	30			

Reference: Impact Point projected to Ground; +X = To Front of MDB +Y = To Right of MDB; +Z = Down

\*All measurements accurate to ± 6 mm.

If applicable, explain why camera(s) did not operate as intended: N/A


**INSTRUMENTATION**

Driver Dummy Channels	16
Passenger Dummy Channels	16
Vehicle Structure Accelerometers	23
MBD Accelerometers	5
<b>TOTAL</b>	<b>60</b>

**DATA SHEET NO. 6**  
**TEST VEHICLE ACCELEROMETER LOCATIONS**

Test Vehicle: 2019 Cadillac XT4 SUV  
Test Program: SINCAP Side Impact

NHTSA No.: M20190102  
Test Date: 2/21/2019



**TEST VEHICLE ACCELEROMETER LOCATIONS**

Loc. No.	Accelerometer Location	Coordinates (mm)		
		X	Y	Z
1	Vehicle CG	2803	140	-333
2	Right Sill at Front Seat	2660	745	-385
3	Right Sill at Rear Seat	1650	755	-380
4	Left Sill at Front Door	2678	-745	-372
5	Left Sill at Rear Door	1660	-755	-383
6	A-Post Lower	3138	-855	-541
7	A-Post Middle	3155	-865	-939
8	B-Post Lower	2040	-760	-570
9	B-Post Middle	2029	-830	-1005
10	Front Seat Track	2228	-562	-413
11	Rear Seat Structure	1505	-545	-535
12	Right Rear Occ. Compartment	1505	560	-547
13	Engine Block	3905	0	-843
14	Rear Above Axle	810	0	-535


Reference: X - Rear surface of vehicle (+ forward)  
Y - Vehicle Centerline (+ to right)  
Z - Ground Plane (+ down)



**DATA SHEET NO. 7  
MDB ACCELEROMETER LOCATIONS**

Test Vehicle: 2019 Cadillac XT4 SUV  
 Test Program: SINCAP Side Impact

NHTSA No.: M20190102  
 Test Date: 2/21/2019



**MDB ACCELEROMETER LOCATIONS**

Loc. No.	Accelerometer Location	Coordinates (mm)		
		X	Y	Z
1	MDB CG	-2179	0	-505
2	MDB Rear	-3648	-650	-618

Reference : X - Face of MDB (+ forward)  
 Y - MDB Centerline (+ to right)  
 Z - Ground Plane (+ down)

**DATA SHEET NO. 8  
POST-TEST OBSERVATIONS**

Test Vehicle: 2019 Cadillac XT4 SUV  
Test Program: SINCAP Side Impact

NHTSA No.: M20190102  
Test Date: 2/21/2019

**TEST DUMMY INFORMATION AND CONTACT POINTS**

Dummy Body Part	Front Seat Dummy (ES2-re)	Rear Seat Dummy (SID-IIs)
Face	SCAB	SCAB
Top of Head	Headliner, SCAB	SCAB
Left Side of Head	SCAB	SCAB
Back of Head	SCAB	SCAB
Left Shoulder	SAB, B-Pillar, Door panel	Door panel
Upper Torso	Seatback bolster, SAB	Door panel/Armrest
Lower Torso	Seatback bolster	Door panel/Armrest
Left Hip	Door panel	Seat cushion bolster, door panel
Left Knee	Door panel	Door panel

**POST-TEST DOOR PERFORMANCE**

Description	Struck Side		Non-Struck Side		Trunk Lid
	Front	Rear	Front	Rear	
Remained Closed and Operational	No	No	Yes	Yes	Yes
Total Separation from Vehicle at Hinges or Latches	No	No	No	No	No
Latch or Hinge Systems Pulled Out of Their Anchorages	No	No	No	No	No
Disengaged from Latched Position	No	No	No	No	No
Latch Separated from Striker	No	No	No	No	No
Jammed Shut	Yes	Yes	No	No	No
If Door Opened at Striker, Record Width of Opening at Striker (mm)	N/A	N/A	N/A	N/A	N/A

**POST-TEST SEAT PERFORMANCE**

Description	Struck Side		Non-Struck Side	
	Front	Rear	Front	Rear
Seat Movement Along Seat Track	No	N/A	No	N/A
Seat Disengagement from Floor pan	No	No	No	No
Seat Back Movement from Initial Position	No	No	No	No
Seat Back Collapse	No	No	No	No

**POST-TEST STRUCTURAL OBSERVATIONS**

Critical Areas of Performance	Observations and Conclusions
Pillar Performance	Good
Sill Separation	None
Windshield Damage	None
Side Window Damage	None
Other Notable Effects	None

**DATA SHEET NO. 8 (CONTINUED)  
POST TEST OBSERVATIONS**

Test Vehicle: 2019 Cadillac XT4 SUV  
Test Program: SINCAP Side Impact

NHTSA No.: M20190102  
Test Date: 2/21/2019

**SUPPLEMENTAL RESTRAINT SYSTEM INFORMATION**

Restraint Type	Struck Side Driver		Struck Side Rear Passenger	
	Mounted	Deployed	Mounted	Deployed
Frontal Airbag	Yes	No		
Knee Airbag	Yes	No		
Side Curtain Airbag	Yes	Yes	Yes	Yes
Side Torso/Pelvis Airbag	Yes	Yes	No	N/A
Side Pelvis Airbag	No	N/A	No	N/A
Seat Belt Pretensioner	Yes	Yes	No	N/A
Seat Belt Load Limiter	Yes	Unknown	No	N/A
Other	No	N/A	No	N/A

**IMPACT POINT LOCATION DATA**

Measured Parameter	Units	Tolerance	Value
Vehicle Wheel Base	mm		2775
Vertical Impact Reference Line (Aft of Front Axle) (Intended Impact Point)	mm		448
Actual Impact Point (Aft of Front Axle)	mm		448
Horizontal Offset ( + forward / - rearward)	mm	+/- 50 of Intended Impact point	0
Vertical Offset (+ down / - up)	mm	+/- 20 of Intended Impact point	-2

**DATA SHEET NO. 9  
MDB SUMMARY OF RESULTS**

Test Vehicle: 2019 Cadillac XT4 SUV  
Test Program: SINCAP Side Impact

NHTSA No.: M20190102  
Test Date: 2/21/2019

**MDB SPECIFICATIONS**

Measurement Description	Length (mm)
Overall Width of Framework Carriage	1252
Overall Length Including Honeycomb Face	4115
Wheel Base of Framework Carriage	2591
C.G. Location aft of Front Axle	1099

**MDB WEIGHTS**

	Units	Front Axle	Rear Axle	Total
Left	kg	405.2	273.2	678.4
Right	kg	379.6	304.6	684.2
Ratio	%	57.6	42.4	100.0
Totals	kg	784.8	577.8	1362.6


**SPEED AND IMPACT ANGLE DATA**

Measured Parameter	Units	Requirement	Value
Trap No. 1 Velocity (Primary)	km/h	61.1 to 62.7	61.83
Trap No. 2 Velocity (Redundant)	km/h	61.1 to 62.7	61.85
MDB CL to Target Vehicle CL	degrees	88.5 to 91.5	90
MDB Forward Line of Motion to Target Vehicle CL	degrees	62.5 to 63.5	63
MDB Crabbed Angle to MDB Forward Line of Motion	degrees	26 to 28	27

**DATA SHEET NO. 10  
TEST VEHICLE PROFILE MEASUREMENTS**

Test Vehicle: 2019 Cadillac XT4 SUV  
Test Program: SINCAP Side Impact

NHTSA No.: M20190102  
Test Date: 2/21/2019



**LEFT SIDE VIEW**

All MEASUREMENTS IN (mm) WITH TOLERANCE OF  $\pm 3$ mm


**VEHICLE PRE- AND POST-TEST MEASUREMENT INFORMATION**

Code	Measurement Description	Pre-Test	Post-Test	Difference
A	Wheelbase	2775	2770	5
B	Front Axle to Front Surface of Vehicle	950	945	5
C	Rear Axle to Rear Surface of Vehicle	881	881	0
D	Total Length at Centerline	4600	4596	4
E	Front Bumper Thickness	85	85	0
F	Front Bumper Bottom to Ground	475	482	-7
G	Sill Height at Front Wheel Well	295	315	-20
H	Sill Height at Front Door Leading Edge	305	325	-20
I	Sill Height at B-Pillar	315	400	-85
J1	Sill Height at Rear Wheel Well	312	344	-32
J2	Pinch Weld Height at Rear Wheel Well	225	271	-46
K	Sill Height Aft of Rear Wheel Well	450	508	-58
L	Rear Bumper Thickness	55	55	0
M	Rear Bumper Bottom to Ground	505	568	-63
N	Sill Height to Window Bottom Sill	920	825	95
O	Front Door Leading Edge to Impact CL	827	801	26
P	Rear Door Trailing Edge to Impact CL	1371	1325	46
Q	Front Window Opening	400	391	9
R	Right Side Length	4205	4205	0
S	Left Side Length	4200	4190	10
T	Vehicle Width	1875	1879	-4

**DATA SHEET NO. 11  
TEST VEHICLE EXTERIOR CRUSH MEASUREMENTS**

Test Vehicle: 2019 Cadillac XT4 SUV  
Test Program: SINCAP Side Impact

NHTSA No.: M20190102  
Test Date: 2/21/2019



**LEFT SIDE VIEW**

**MAXIMUM EXTERIOR CRUSH MEASUREMENTS**

Level	Measurement Description	Height Above Ground	Maximum Exterior Static Crush	Distance From Impact
1	Sill Top	390	86	1050
2	Driver Hip Point	636	214	1650
3	Mid-Door	755	225	1650
4	Window Sill	1058	88	1800
5	Window Top	1571	1	1350

**NOTE:** The above measurements were taken along the vertical impact reference line. Vehicle measurements forward of the vertical impact reference line are negative.

**DATA SHEET NO. 11 (CONTINUED)**  
**TEST VEHICLE EXTERIOR CRUSH MEASUREMENTS**

Test Vehicle: 2019 Cadillac XT4 SUV  
 Test Program: SINCAP Side Impact

NHTSA No.: M20190102  
 Test Date: 2/21/2019

**EXTERIOR CRUSH MEASUREMENTS AT EACH LEVEL**


	Pre-Test					Post-Test					Difference				
	1	2	3	4	5	1	2	3	4	5	1	2	3	4	5
<b>-450</b>	0	0	0	786	0	0	0	0	798	0	0	0	0	-12	0
<b>-300</b>	0	0	0	802	0	0	0	0	807	0	0	0	0	-5	0
<b>-150</b>	0	0	937	817	0	0	0	933	811	0	0	0	4	6	0
<b>0</b>	922	936	926	827	0	921	925	919	814	0	1	11	7	13	0
<b>150</b>	913	917	920	835	0	891	798	809	838	0	22	119	111	-3	0
<b>300</b>	908	914	919	843	0	860	769	771	846	0	48	145	148	-3	0
<b>450</b>	906	916	920	853	0	846	781	748	849	0	60	135	172	4	0
<b>600</b>	907	918	920	863	0	838	775	738	852	0	69	143	182	11	0
<b>750</b>	906	920	919	872	0	832	761	732	848	0	74	159	187	24	0
<b>900</b>	905	922	919	878	610	825	754	728	847	612	80	168	191	31	-2
<b>1050</b>	904	924	918	883	616	818	753	761	843	617	86	171	157	40	-1
<b>1200</b>	900	927	916	882	617	821	763	739	812	618	79	164	177	70	-1
<b>1350</b>	898	929	915	880	616	823	741	703	806	615	75	188	212	74	1
<b>1500</b>	897	930	915	878	614	824	733	695	797	615	73	197	220	81	-1
<b>1650</b>	900	931	918	875	609	830	717	693	793	609	70	214	225	82	0
<b>1800</b>	908	933	926	872	603	858	725	721	784	603	50	208	205	88	0
<b>1950</b>	0	938	940	859	595	0	943	840	828	596	0	-5	100	31	-1
<b>2100</b>	0	0	0	866	585	0	0	0	902	586	0	0	0	-36	-1
<b>2250</b>	0	0	0	862	0	0	0	0	857	0	0	0	0	5	0

**NOTE:** Pre-test measurements are taken when the vehicle is in the "As Tested" weight condition. Vehicle measurements forward of the vertical impact reference line are negative. The crush profile grid is established prior to the test based on an estimated impact point.

**DATA SHEET NO. 11 (CONTINUED)**  
**TEST VEHICLE EXTERIOR CRUSH MEASUREMENTS**

Test Vehicle: 2019 Cadillac XT4 SUV  
Test Program: SINCAP Side Impact

NHTSA No.: M20190102  
Test Date: 2/21/2019






**DATA SHEET NO. 12  
MDB EXTERIOR STATIC CRUSH MEASUREMENTS**

Test Vehicle: 2019 Cadillac XT4 SUV  
Test Program: SINCAP Side Impact

NHTSA No.: M20190102  
Test Date: 2/21/2019



**MAXIMUM STATIC CRUSH OF HONEYCOMB IMPACT FACE**

Vertical Location			From Centerline		Maximum Crush
Row	Description	Height	Distance	Direction	
A	Center of Bumper	432	800	Right	238
B	Top of Bumper	560	700	Right	121
C	Mid-Level	686	800	Left	117
D	Top of Stack	813	800	Left	151


**DEFORMABLE BARRIER STATIC CRUSH**

Stack Level	Distance Right of Center								C/L	Distance Left of Center							
	800	700	600	500	400	300	200	100		0	100	200	300	400	500	600	700
1	238	236	232	230	228	226	223	220	217	214	211	208	206	203	200	201	207
2	119	121	118	114	112	110	109	107	101	98	96	93	89	87	84	82	91
3	64	45	38	35	37	38	41	51	69	59	34	31	32	41	57	84	117
4	69	56	43	47	50	67	100	95	82	60	55	55	61	71	81	113	151

**DATA SHEET NO. 13  
VEHICLE AND MDB DAMAGE PROFILE DISTANCES**

Test Vehicle: 2019 Cadillac XT4 SUV  
Test Program: SINCAP Side Impact

NHTSA No.: M20190102  
Test Date: 2/21/2019



MEASUREMENT CONVENTIONS:  
Forward of the impact point (towards front of vehicle) is considered negative (-).  
Rearward of the impact point (toward rearend of vehicle) is considered positive (+).

**VEHICLE DAMAGE PROFILE DISTANCES**

DPD	Distance From Impact Point (mm)	Level	Post-Test (mm)	Pre-Test (mm)	Crush (mm)
1	2250	4	857	862	5
2	1650	3	693	918	225
3	1200	3	739	916	177
4	600	3	738	920	182
5	150	2	798	917	119
6 <sup>1</sup>	-450	4	798	786	0

**MDB DAMAGE PROFILE DISTANCES**

DPD	Distance From Center of MDB	Level	Post-Test (mm)	Pre-Test (mm)	Crush (mm)
1	800 mm Left of Center	1	270	477	207
2	500 mm Left of Center	1	283	486	203
3	200 mm Left of Center	1	276	487	211
4	200 mm Right of Center	1	264	487	223
5	500 mm Right of Center	1	257	487	230
6	800 mm Right of Center	1	232	470	238

<sup>1</sup> DPD 6 is defined as zero crush since the crush does not extend to the end of the vehicle.

**DATA SHEET NO. 14  
FMVSS NO. 301 STATIC ROLLOVER RESULTS**


Test Vehicle: 2019 Cadillac XT4 SUV  
Test Program: SINCAP Side Impact

NHTSA No.: M20190102  
Test Date: 2/21/2019

Test Time: 14:44 Temperature: 21.2°C

- A. From impact until vehicle motion ceases: 0 oz.  
(Maximum allowable is 1 ounce)
- B. For the 5 minute period after motion ceases: 0 oz.  
(Maximum allowable is 5 ounces)
- C. For the following 25 minutes: 0 oz.  
(Maximum allowable is 1 ounce/minute)
- D. Spillage Details: None

**FMVSS 301 STATIC ROLLOVER DATA**



**ROLLOVER SOLVENT COLLECTION TIME TABLE IN SECONDS**

Test Phase	Rotation Time	Hold Time	Total Time
0 to 90	90	330	420
90 to 180	90	330	840
180 to 270	90	330	1260
270 to 360	90	330	1680

**FMVSS NO. 301 ROLLOVER SPILLAGE TABLE**

Test Phase	First 5 Minutes	Sixth Minute	Seventh Minute	Eighth Minute
0 to 90	0	0	0	N/A
90 to 180	0	0	0	N/A
180 to 270	0	0	0	N/A
270 to 360	0	0	0	N/A

**ROLLOVER SOLVENT SPILLAGE LOCATION TABLE**


Test Phase	Spillage Location
0 to 90	None
90 to 180	None
180 to 270	None
270 to 360	None

**DATA SHEET NO. 15**  
**DUMMY/VEHICLE TEMPERATURE AND HUMIDITY STABILIZATION DATA**

Test Vehicle: 2019 Cadillac XT4 SUV  
Test Program: SINCAP Side Impact

NHTSA No.: M20190102  
Test Date: 2/21/2019

M20190102 2019 Cadillac XT4 Left MDB Impact 190221: Test Time 13:17



**APPENDIX A  
PHOTOGRAPHS**

## TABLE OF PHOTOGRAPHS

<b>No.</b>	<b>Description</b>	<b>Page</b>
001	As-Delivered Right Front $\frac{3}{4}$ View of Test Vehicle	A-6
002	As-Delivered Left Rear $\frac{3}{4}$ View of Test Vehicle	A-6
003	Pre-Test Frontal View of Test Vehicle	A-7
004	Post-Test Frontal View of Test Vehicle	A-7
005	Pre-Test Left Front $\frac{3}{4}$ View of Test Vehicle	A-8
006	Post-Test Left Front $\frac{3}{4}$ View of Test Vehicle	A-8
007	Pre-Test Left Side View of Test Vehicle	A-9
008	Post-Test Left Side View of Test Vehicle	A-9
009	Pre-Test Left Rear $\frac{3}{4}$ View of Test Vehicle	A-10
010	Post-Test Left Rear $\frac{3}{4}$ View of Test Vehicle	A-10
011	Pre-Test Rear View of Test Vehicle	A-11
012	Post-Test Rear View of Test Vehicle	A-11
013	Pre-Test Right Side View of Test Vehicle	A-12
014	Post-Test Right Side View of Test Vehicle	A-12
015	Pre-Test Overhead View of Test Area	A-13
016	Post-Test Overhead View of Test Area	A-13
017	Pre-Test Left Side View of MDB Positioned Against Side of Test Vehicle	A-14
018	Pre-Test Right Side View of MDB Positioned Against Side of Test Vehicle	A-14
019	Pre-Test Close-Up View of Impact Point Target	A-15
020	Post-Test Close-Up View of Impact Point Target	A-15
021	Pre-Test Left Front Door Latch Close-Up	A-16
022	Post-Test Left Front Door Latch Close-Up	A-16
023	Pre-Test Left Rear Door Latch Close-Up	A-17
024	Post-Test Left Rear Door Latch Close-Up	A-17
025	Pre-Test Front Close-Up View of Driver Dummy	A-18
026	Post-Test Front Close-Up View of Driver Dummy	A-18
027	Pre-Test Left Side View of Driver Dummy Showing Belt and Chalking	A-19
028	Pre-Test Left Side View of Driver Dummy Shoulder and Door Top	A-20
029	Post-Test Left Side View of Driver Dummy Shoulder and Door Top	A-20
030	Pre-Test Frontal View of Driver Seat Back Prior to Dummy Positioning	A-21
031	Pre-Test Frontal View of Driver Dummy Head and Shoulders in Relation to Head Restraint	A-21
032	Pre-Test Frontal View of Driver Seat Pan Prior to Dummy Positioning	A-22
033	Pre-Test Overhead View of Driver Dummy Thighs on Seat Pan	A-22
034	Pre-Test Placement of Driver Dummy's Feet	A-23
035	Pre-Test View of Belt Anchorage for Driver Dummy	A-23
036	Pre-Test Left Side View of Steering Wheel	A-24

## TABLE OF PHOTOGRAPHS (CONTINUED)

<b>No.</b>	<b>Description</b>	<b>Page</b>
<b>037</b>	View of Disengaged Parking Brake	<b>A-24</b>
<b>038</b>	Pre-Test View of Parking Brake	<b>A-25</b>
<b>039</b>	Pre-Test Close-Up Left Side View of Driver Seat Track	<b>A-25</b>
<b>040</b>	Pre-Test Close-Up Left Side View of Driver Seat Back	<b>A-26</b>
<b>041</b>	Pre-Test Close-Up View of Driver Seat Back or Head Restraint	<b>A-26</b>
<b>042</b>	Pre-Test Driver Dummy and Door Clearance View	<b>A-27</b>
<b>043</b>	Post-Test Driver Dummy and Door Clearance View	<b>A-27</b>
<b>044</b>	Pre-Test Right Side View of Driver Dummy and Front Seat of Occupant Compartment	<b>A-28</b>
<b>045</b>	Post-Test Right Side View of Driver Dummy and Front Seat of Occupant Compartment	<b>A-28</b>
<b>046</b>	Pre-Test Driver Inner Door Panel View	<b>A-29</b>
<b>047</b>	Post-Test Driver Inner Door Panel View Showing Driver Dummy Contact Locations	<b>A-29</b>
<b>048</b>	Post-Test Driver Dummy Close-Up Head Contact with Vehicle View	<b>A-30</b>
<b>049</b>	Post-Test Driver Dummy Close-Up Head Contact with Side Airbag View	<b>A-30</b>
<b>050</b>	Post-Test Driver Dummy Close-Up Torso Contact with Vehicle Interior View	<b>A-31</b>
<b>051</b>	Post-Test Driver Dummy Close-Up Torso Contact with Side Airbag View	<b>A-31</b>
<b>052</b>	Post-Test Driver Dummy Close-Up Pelvis Contact View	<b>A-32</b>
<b>053</b>	Post-Test Driver Dummy Close-Up Pelvis Contact with Side Airbag View	<b>A-32</b>
<b>054</b>	Post-Test Driver Dummy Close-Up Knee Contact View	<b>A-33</b>
<b>055</b>	Pre-Test Left Side View of Rear Passenger Dummy Showing Belt and Chalking	<b>A-33</b>
<b>056</b>	Pre-Test Left Side View of Rear Passenger Dummy Shoulder and Door Top View	<b>A-34</b>
<b>057</b>	Post-Test Left Side View of Rear Passenger Dummy Shoulder and Door Top View	<b>A-34</b>
<b>058</b>	Pre-Test Frontal View of Rear Passenger Seat Back Prior to Dummy Positioning	<b>A-35</b>
<b>059</b>	Pre-Test Frontal View of Rear Passenger Dummy Head and Shoulders in Relation to Head Restraint	<b>A-35</b>
<b>060</b>	Pre-Test Overhead View of Rear Passenger Seat Pan Prior to Dummy Positioning	<b>A-36</b>
<b>061</b>	Pre-Test Overhead View of Rear Passenger Dummy Thighs on Seat Pan	<b>A-36</b>
<b>062</b>	Pre-Test View of Rear Passenger Dummy's Neck Showing Position of Adjustable Neck Bracket	<b>A-37</b>
<b>063</b>	Pre-Test View of Rear Passenger Dummy's Head Showing Dummy's Head is Level	<b>A-37</b>

## TABLE OF PHOTOGRAPHS (CONTINUED)

<b>No.</b>	<b>Description</b>	<b>Page</b>
<b>064</b>	Pre-Test Placement of Rear Passenger Dummy's Feet	<b>A-38</b>
<b>065</b>	Pre-Test View of Belt Anchorage for Rear Passenger Dummy	<b>A-38</b>
<b>066</b>	Pre-Test Close-Up Left Side View of Rear Passenger Seat Track	<b>A-39</b>
<b>067</b>	Pre-Test Close-Up Left Side View of Rear Passenger Seat Back	<b>A-39</b>
<b>068</b>	Pre-Test Close-Up View of Rear Passenger Seat Back or Head Restraint	<b>A-40</b>
<b>069</b>	Pre-Test Rear Passenger Dummy and Door Clearance View	<b>A-41</b>
<b>070</b>	Post-Test Rear Passenger Dummy and Door Clearance View	<b>A-41</b>
<b>071</b>	Pre-Test Right Side View of Rear Passenger Dummy and Rear Seat Occupant Compartment	<b>A-42</b>
<b>072</b>	Post-Test Right Side View of Rear Passenger Dummy and Rear Seat Occupant Compartment	<b>A-42</b>
<b>073</b>	Pre-Test Rear Passenger Inner Door Panel View	<b>A-43</b>
<b>074</b>	Post-Test Rear Passenger Inner Door Panel View	<b>A-43</b>
<b>075</b>	Post-Test Rear Passenger Dummy Close-Up Head Contact with Vehicle View	<b>A-44</b>
<b>076</b>	Post-Test Rear Passenger Dummy Close-Up Head Contact with Side Airbag View	<b>A-44</b>
<b>077</b>	Post-Test Rear Passenger Dummy Close-Up Torso Contact with Vehicle Interior View	<b>A-45</b>
<b>078</b>	Post-Test Rear Passenger Dummy Close-Up Torso Contact with Side Airbag View	<b>A-45</b>
<b>079</b>	Post-Test Rear Passenger Dummy Close-Up Pelvis Contact View	<b>A-46</b>
<b>080</b>	Post-Test Rear Passenger Dummy Close-Up Pelvis Contact with Side Airbag View	<b>A-46</b>
<b>081</b>	Post-Test Rear Passenger Dummy Close-Up Knee Contact View	<b>A-47</b>
<b>082</b>	Pre-Test View of Fuel Filler Cap or Fuel Filler Neck	<b>A-48</b>
<b>083</b>	Post-Test View of Fuel Filler Cap or Fuel Filler Neck	<b>A-48</b>
<b>084</b>	Pre-Test Front View of MDB Impactor Face	<b>A-49</b>
<b>085</b>	Post-Test Front View of MDB Impactor Face	<b>A-49</b>
<b>086</b>	Pre-Test Top View of MDB Impactor Face	<b>A-50</b>
<b>087</b>	Post-Test Top View of MDB Impactor Face	<b>A-50</b>
<b>088</b>	Pre-Test Left Side View of MDB Impactor Face	<b>A-51</b>
<b>089</b>	Post-Test Left Side View of MDB Impactor Face	<b>A-51</b>
<b>090</b>	Pre-Test Right Side View of MDB Impactor Face	<b>A-52</b>
<b>091</b>	Post-Test Right Side View of MDB Impactor Face	<b>A-52</b>



## TABLE OF PHOTOGRAPHS (CONTINUED)

<b>No.</b>	<b>Description</b>	<b>Page</b>
<b>092</b>	Close-Up View of Vehicle's Certification Label	<b>A-53</b>
<b>093</b>	Close-Up View of Vehicle's Tire Information Placard or Label	<b>A-53</b>
<b>094</b>	Pre-Test Ballast View	<b>A-54</b>
<b>095</b>	Post-Test Primary and Redundant Speed Trap Read-Out	<b>A-54</b>
<b>096</b>	FMVSS No. 301 Static Rollover 0 Degrees	<b>A-55</b>
<b>097</b>	FMVSS No. 301 Static Rollover 90 Degrees	<b>A-55</b>
<b>098</b>	FMVSS No. 301 Static Rollover 180 Degrees	<b>A-56</b>
<b>099</b>	FMVSS No. 301 Static Rollover 270 Degrees	<b>A-56</b>
<b>100</b>	FMVSS No. 301 Static Rollover 360 Degrees	<b>A-57</b>
<b>101</b>	Impact Event	<b>A-57</b>
<b>102</b>	Monroney Label	<b>A-58</b>
<b>103</b>	Driver Head Restraint Use and Adjustment Information from Vehicle Owner's Manual	<b>A-58</b>
<b>104</b>	Left Rear Passenger Head Restraint Use and Adjustment Information from Vehicle Owner's Manual	<b>A-59</b>



**001** As-Delivered Right Front  $\frac{3}{4}$  View of Test Vehicle



**002** As-Delivered Left Rear  $\frac{3}{4}$  View of Test Vehicle





**003** Pre-Test Frontal View of Test Vehicle



**004** Post-Test Frontal View of Test Vehicle





**005** Pre-Test Left Front  $\frac{3}{4}$  View of Test Vehicle



**006** Post-Test Left Front  $\frac{3}{4}$  View of Test Vehicle





**007** Pre-Test Left Side View of Test Vehicle



**008** Post-Test Left Side View of Test Vehicle





**009** Pre-Test Left Rear  $\frac{3}{4}$  View of Test Vehicle



**010** Post-Test Left Rear  $\frac{3}{4}$  View of Test Vehicle



**011** Pre-Test Rear View of Test Vehicle



**012** Post-Test Rear View of Test Vehicle





**013** Pre-Test Right Side View of Test Vehicle



**014** Post-Test Right Side View of Test Vehicle





015 Pre-Test Overhead View of Test Area



016 Post-Test Overhead View of Test Area





**017** Pre-Test Left Side View of MDB Positioned Against Side of Test Vehicle



**018** Pre-Test Right Side View MDB Positioned Against Side of Test Vehicle



019 Pre-Test Close-Up View of Impact Point Target



020 Post-Test Close-Up View of Impact Point Target





021 Pre-Test Left Front Door Latch Close-Up



022 Post-Test Left Front Door Latch Close-Up



023 Pre-Test Left Rear Door Latch Close-Up



024 Post-Test Left Rear Door Latch Close-Up





**025** Pre-Test Front Close-Up View of Driver Dummy




**026** Post-Test Front Close-Up View of Driver Dummy



**027** Pre-Test Left Side View of Driver Dummy Showing Belt and Chalking

Intentionally Left Blank





**028** Pre-Test Left Side View of Driver Dummy Shoulder and Door Top



**029** Post-Test Left Side View of Driver Dummy Shoulder and Door Top






**030** Pre-Test Frontal View of Driver Seat Back Prior to Dummy Positioning



**031** Pre-Test Frontal View of Driver Dummy Head and Shoulders in Relation to Head Restraint



**032** Pre-Test Frontal View of Driver Seat Pan Prior to Dummy Positioning



**033** Pre-Test Overhead View of Driver Dummy Thighs on Seat Pan



**034** Pre-Test Placement of Driver's Dummy Feet



**035** Pre-Test View of Belt Anchorage for Driver Dummy





036 Pre-Test Left Side View of Steering Wheel



037 View of Disengaged Parking Brake



**038** Pre-Test View of Parking Brake



**039** Pre-Test Close-Up Left Side View of Driver Seat Track





**040** Pre-Test Close-Up Left Side View of Driver Seat Back



**041** Pre-Test Close-Up View of Driver Seat Back or Head Restraint



**042** Pre-Test Driver Dummy and Door Clearance View



**043** Post-Test Driver Dummy and Door Clearance View





**044** Pre-Test Right Side View of Driver Dummy and Front Seat of Occupant Compartment



**045** Post-Test Right Side View of Driver Dummy and Front Seat of Occupant Compartment






**046** Pre-Test Driver Inner Door Panel View



**047** Post-Test Driver Inner Door Panel View Showing Driver Dummy Contact Locations



**048** Post-Test Driver Dummy Close-Up Head Contact with Vehicle View



**049** Post-Test Driver Dummy Close-Up Head Contact with Side Airbag View





**050** Post-Test Driver Dummy Close-Up Torso Contact with Vehicle Interior View



**051** Post-Test Driver Dummy Close-Up Torso Contact with Side Airbag View




**052** Post-Test Driver Dummy Close-Up Pelvis Contact View



**053** Post-Test Driver Dummy Close-Up Pelvis Contact with Side Airbag View





**054** Post-Test Driver Dummy Close-Up Knee Contact View



**055** Pre-Test Left Side View of Passenger Dummy Showing Belt and Chalking



**056** Pre-Test Left Side View of Passenger Dummy Shoulder and Door Top View



**057** Post-Test Left Side View of Passenger Dummy Shoulder and Door Top View





**058** Pre-Test Frontal View of Rear Passenger Seat Back Prior to Dummy Positioning



**059** Pre-Test Frontal View of Rear Passenger Dummy Head and Shoulders in Relation to Head Restraint




**060** Pre-Test Overhead View of Rear Passenger Seat Pan Prior to Dummy Positioning



**061** Pre-Test Overhead View of Rear Passenger Dummy Thighs on Seat Pan





**062** Pre-Test View of Rear Passenger Dummy's Neck Showing Position of Adjustable Neck Bracket



**063** Pre-Test View of Rear Passenger Dummy's Head Showing Dummy Head is Level




**064** Pre-Test Placement of Rear Passenger Dummy's Feet



**065** Pre-Test View of Belt Anchorage for Rear Passenger Dummy



**066** Pre-Test Close-Up Left Side View of Rear Passenger Seat Track



**067** Pre-test Close-Up Left Side View of Rear Passenger Seat Back





**068** Pre-Test Close-Up View of Rear Passenger Seat Back or Head Restraint

Intentionally Left Blank





**069** Pre-Test Rear Passenger Dummy and Door Clearance View



**070** Post-Test Rear Passenger Dummy and Door Clearance View



**071** Pre-Test Right Side View of Rear Passenger Dummy and Rear Seat Occupant Compartment



**072** Post-Test Right Side View of Rear Passenger Dummy and Rear Seat Occupant Compartment






**073** Pre-Test Rear Passenger Inner Door Panel View



**074** Post-Test Rear Passenger Inner Door Panel View



**075** Post-Test Rear Passenger Dummy Close-Up Head Contact with Vehicle View




**076** Post-Test Rear Passenger Dummy Close-Up Head Contact with Side Airbag View






**077** Post-Test Rear Passenger Dummy Close-Up Torso Contact with Vehicle Interior View



**078** Post-Test Rear Passenger Dummy Close-Up Torso Contact with Side Airbag View



**079** Post-Test Rear Passenger Dummy Close-Up Pelvis Contact View



**080** Post-Test Rear Passenger Dummy Close-Up Pelvis Contact with Side Airbag View



**081** Post-Test Rear Passenger Dummy Close-Up Knee Contact View

Intentionally Left Blank





**082** Pre-Test View of Fuel Filler Cap or Fuel Filler Neck



**083** Post-Test View of Fuel Filler Cap or Fuel Filler Neck






**084** Pre-Test Front View of MDB Impactor Face



**085** Post-Test Front View of MDB Impactor Face



**086** Pre-Test Top View of MDB Impactor Face



**087** Post-Test Top View of MDB Impactor Face





**088** Pre-Test Left Side View of MDB Impactor Face



**089** Post-Test Left Side View of MDB Impactor Face






**090** Pre-Test Right Side View of MDB Impactor Face



**091** Post-Test Right Side View of MDB Impactor Face






092 Close-Up View of Vehicle's Certification Label





093 Close-Up View of Vehicle's Tire Information Placard or Label






094 Pre-Test Ballast View



095 No. Post-Test Primary and Redundant Speed Trap Read-Out






**096** FMVSS No. 301 Static Rollover 0 Degrees




**097** FMVSS No. 301 Static Rollover 90 Degrees






098 FMVSS No. 301 Static Rollover 180 Degrees



099 FMVSS No. 301 Static Rollover 270 Degrees





100 FMVSS No. 301 Static Rollover 360 Degrees



101 Impact Event



### 2019 XT4 FWD LUXURY

EXTERIOR: RADIANT SILVER METALLIC ENGINE: 2.0L 4-CYLINDER TURBO  
INTERIOR: LIGHT PLATINUM / JET TRANSMISSION: 9-SPD AUTOMATIC  
BLACK

Visit us at [www.cadillac.com](http://www.cadillac.com)

<p><b>STANDARD EQUIPMENT</b></p> <p>THESE FEATURES AND OPTIONS ARE INCLUDED AT NO EXTRA CHARGE IN THE STANDARD VEHICLE PRICE SHOWN.</p> <p><b>CADILLAC OWNER BENEFITS</b></p> <ul style="list-style-type: none"> <li>• 4 YEAR / 50,000 MILE* BUMPER-TO-BUMPER LTD WARRANTY</li> <li>• 6 YEAR / 70,000 MILE* POWERTRAIN LTD WARRANTY</li> <li>• FIRST MAINTENANCE VISIT OIL CHANGE AND TIRE ROTATION SEE WWW.CADILLAC.COM</li> <li>• 6 YEAR / 70,000 MILE* COURTESY TRANSPORTATION</li> <li>• 6 YEAR / 70,000 MILE* ROADSIDE ASSISTANCE</li> <li>• *WHICHEVER COMES FIRST. SEE DEALER FOR DETAILS.</li> <li>• ONSTAR (®) SERVICES CAPABLE (SUBJECT TO TERMS SEE ONSTAR.COM)</li> <li>• 4G LTE Wi-Fi (®) HOTSPOT CAPABLE (SUBJECT TO TERMS SEE ONSTAR.COM)</li> </ul>	<p><b>PERFORMANCE</b></p> <ul style="list-style-type: none"> <li>• ENGINE, 2.0L 4-CYLINDER TURBO</li> <li>• TRANSMISSION, 9-SPD AUTOMATIC</li> <li>• 18" 10-SPOKE ALLOY WHEELS</li> <li>• 4 WHL INDEP SUSPENSION</li> <li>• SELECTABLE DRIVING MODES</li> <li>• STABILITRAK STABILITY CONTROL INCLUDES TRACTION CONTROL</li> </ul> <p><b>LUXURY &amp; CONVENIENCE</b></p> <ul style="list-style-type: none"> <li>• LED HEADLAMPS &amp; TAILLAMPS</li> <li>• PASSIVE ENTRY &amp; KEYLESS START</li> <li>• POWER SEAT ADJUSTER, DRIVER 8-WAY &amp; PASS 6-WAY</li> <li>• POWER LUMBAR, 2-WAY, DRIVER &amp; FRONT PASSENGER</li> <li>• ADAPTIVE REMOTE START</li> <li>• REAR SEAT, 60/40 SPLIT FOLDING SEATBACK</li> <li>• 8" COLOR TOUCH DISPLAY</li> <li>• ROTARY INFOTAINMENT CONTROLLER</li> <li>• UNIVERSAL HOME REMOTE</li> </ul>	<p><b>SAFETY &amp; SECURITY</b></p> <ul style="list-style-type: none"> <li>• AIRBAGS, FRONTAL, KNEE AND SEAT SIDE IMPACT FOR DRIVER AND FRONT PASSENGER, HEAD CURTAIN FOR ALL OUTBOARD SEATING POSITIONS</li> <li>• HD REAR VISION CAMERA</li> <li>• REAR PARK ASSIST</li> </ul> <p><b>OPTIONS &amp; PRICING</b></p> <p>MANUFACTURER'S SUGGESTED RETAIL PRICE</p> <table border="1"> <tr> <td><b>STANDARD VEHICLE PRICE</b></td> <td><b>\$34,795.00</b></td> </tr> <tr> <td colspan="2"><small>OPTIONS INSTALLED BY THE MANUFACTURER (MAY REPLACE STANDARD EQUIPMENT SHOWN)</small></td> </tr> <tr> <td>TOTAL OPTIONS</td> <td>\$0.00</td> </tr> <tr> <td>TOTAL VEHICLE &amp; OPTIONS</td> <td>\$34,795.00</td> </tr> <tr> <td>DESTINATION CHARGE</td> <td>995.00</td> </tr> <tr> <td><b>TOTAL VEHICLE PRICE*</b></td> <td><b>\$35,790.00</b></td> </tr> </table>	<b>STANDARD VEHICLE PRICE</b>	<b>\$34,795.00</b>	<small>OPTIONS INSTALLED BY THE MANUFACTURER (MAY REPLACE STANDARD EQUIPMENT SHOWN)</small>		TOTAL OPTIONS	\$0.00	TOTAL VEHICLE & OPTIONS	\$34,795.00	DESTINATION CHARGE	995.00	<b>TOTAL VEHICLE PRICE*</b>	<b>\$35,790.00</b>	<p><b>GOVERNMENT 5-STAR SAFETY RATINGS</b></p> <p>This vehicle has not been rated by the government for overall vehicle score, frontal crash, side crash or rollover risk.</p> <p>Source: National Highway Traffic Safety Administration (NHTSA) <a href="http://www.safercar.gov">www.safercar.gov</a> or 1-888-327-4236</p>	<p><b>PARTS CONTENT INFORMATION</b></p> <p>FOR VEHICLES IN THIS CARLINE: <b>U.S./CANADIAN PARTS CONTENT: 49%</b> <b>MAJOR SOURCES OF FOREIGN PARTS CONTENT: MEXICO 28%</b></p> <p>NOTE: PARTS CONTENT DOES NOT INCLUDE FINAL ASSEMBLY, DISTRIBUTION, OR OTHER NON-PARTS COSTS.</p> <p>FOR THIS VEHICLE: <b>FINAL ASSEMBLY POINT: KANSAS CITY, KS U.S.A.</b> <b>COUNTRY OF ORIGIN: ENGINE: UNITED STATES TRANSMISSION: UNITED STATES</b></p> <p><small>This label has been applied pursuant to Federal law. Do not remove prior to delivery to the ultimate purchaser. Products manufactured in accordance with the Delivery Service. Does not include dealer-installed options and accessories not listed above. Local laws of some states.</small></p> <p><small>© 2018 General Motors LLC. GM/BLR_PROD_2018_01/201818</small></p>
<b>STANDARD VEHICLE PRICE</b>	<b>\$34,795.00</b>															
<small>OPTIONS INSTALLED BY THE MANUFACTURER (MAY REPLACE STANDARD EQUIPMENT SHOWN)</small>																
TOTAL OPTIONS	\$0.00															
TOTAL VEHICLE & OPTIONS	\$34,795.00															
DESTINATION CHARGE	995.00															
<b>TOTAL VEHICLE PRICE*</b>	<b>\$35,790.00</b>															
<p><b>EPA DOT Fuel Economy and Environment</b></p> <p><b>Fuel Economy</b></p> <p><b>26</b> MPG combined city/hwy <b>24</b> MPG city <b>30</b> MPG highway</p> <p><b>3.8</b> gallons per 100 miles</p> <p><b>You spend \$1,750 more in fuel costs over 5 years</b> compared to the average new vehicle.</p> <p><b>Annual fuel cost \$1,750</b></p> <p><b>Fuel Economy &amp; Greenhouse Gas Rating</b> (tailpipe only)</p> <p><b>5</b> Best</p> <p><b>Smog Rating</b> (tailpipe only)</p> <p><b>6</b> Best</p> <p><small>This vehicle emits 336 grams CO<sub>2</sub> per mile. The best emits 0 grams per mile (tailpipe only). Producing and distributing fuel also creates emissions. Learn more at <a href="http://fuelconomy.gov">fuelconomy.gov</a>.</small></p> <p><small>Actual results will vary for many reasons, including driving conditions and how you drive and maintain your vehicle. The average new vehicle gets 27 MPG and costs \$2,000 to fuel over 5 years. Cost estimates are based on 15,000 miles per year at \$3.00 per gallon. MPG is miles per gallon equivalent. Vehicle emissions are a significant cause of climate change and smog.</small></p> <p><b>fuelconomy.gov</b> Calculate personalized estimates and compare vehicles</p>		<p><b>GOVERNMENT 5-STAR SAFETY RATINGS</b></p> <p>This vehicle has not been rated by the government for overall vehicle score, frontal crash, side crash or rollover risk.</p> <p>Source: National Highway Traffic Safety Administration (NHTSA) <a href="http://www.safercar.gov">www.safercar.gov</a> or 1-888-327-4236</p>	<p><b>PARTS CONTENT INFORMATION</b></p> <p>FOR VEHICLES IN THIS CARLINE: <b>U.S./CANADIAN PARTS CONTENT: 49%</b> <b>MAJOR SOURCES OF FOREIGN PARTS CONTENT: MEXICO 28%</b></p> <p>NOTE: PARTS CONTENT DOES NOT INCLUDE FINAL ASSEMBLY, DISTRIBUTION, OR OTHER NON-PARTS COSTS.</p> <p>FOR THIS VEHICLE: <b>FINAL ASSEMBLY POINT: KANSAS CITY, KS U.S.A.</b> <b>COUNTRY OF ORIGIN: ENGINE: UNITED STATES TRANSMISSION: UNITED STATES</b></p> <p><small>This label has been applied pursuant to Federal law. Do not remove prior to delivery to the ultimate purchaser. Products manufactured in accordance with the Delivery Service. Does not include dealer-installed options and accessories not listed above. Local laws of some states.</small></p> <p><small>© 2018 General Motors LLC. GM/BLR_PROD_2018_01/201818</small></p>													

## 102 Monroney Label


### Head Restraints

#### Front Seats

**Warning**


With head restraints that are not installed and adjusted properly, there is a greater chance that occupants will suffer a neck/spinal injury in a crash. Do not drive until the head restraints for all occupants are installed and adjusted properly.

The vehicle's front seats have adjustable head restraints in the outboard seating positions.



Adjust the head restraint so that the top of the restraint is at the same height as the top of the occupant's head. This position reduces the chance of a neck injury in a crash. The height of the head restraint can be adjusted.

### SEATS AND RESTRAINTS 61



To raise or lower the head restraint, press the button located on the side of the head restraint, and pull up or push the head restraint down, and release the button. Pull and push on the head restraint after the button is released to make sure that it is locked in place.

The front seat outboard head restraints are not removable.

#### Rear Seats


##### Adjusting the Rear Head Restraint

The vehicle's rear seats have adjustable head restraints in the outboard seating positions.

## 103 Driver Head Restraint Use and Adjustment Information from Vehicle Owner's Manual




The height of the head restraint can be adjusted. Pull the head restraint up to raise it. Try to move the head restraint to make sure that it is locked in place.




To lower the head restraint, press the button, located on the top of the seatback, and push the head restraint down. Try to move the head restraint after the button is released to make sure that it is locked in place.

**Folding the Rear Head Restraint**

The head restraint can be folded rearward to allow for better visibility when the rear seat is unoccupied.



To fold the head restraint, press the button on the side of the head restraint.



The head restraint will fold rearward automatically.

When an occupant or child restraint is in the seat, always return the head restraint to the full upright position. Pull the head restraint up and forward until it locks into place. Push and pull on the head restraint to make sure that it is locked.

Always adjust the head restraint so that the top of the restraint is at the same height as the top of the occupant's head.

If you are installing a child restraint in the rear seat, see "Securing a Child Restraint Designed for the LATCH System" under *Lower Anchors and Tethers for Children (LATCH System)* ⇨ 98.

**104** Left Rear Passenger Head Restraint Use and Adjustment Information from Vehicle Owner's Manual

**APPENDIX B**  
**VEHICLE AND DUMMY RESPONSE DATA PLOTS**

## TABLE OF DATA PLOTS

### Driver & Passenger Dummy Instrumentation Plots

<b>No.</b>	<b>Description</b>	<b>Page</b>
1	Driver Head Acceleration (X) Primary vs. Time	B-5
2	Driver Head Acceleration (Y) Primary vs. Time	B-5
3	Driver Head Acceleration (Z) Primary vs. Time	B-5
4	Driver Head Resultant Acceleration Primary vs. Time	B-5
5	Driver Upper Thorax Rib Deflection (Y) vs. Time	B-6
6	Driver Middle Thorax Rib Deflection (Y) vs. Time	B-6
7	Driver Lower Thorax Rib Deflection (Y) vs. Time	B-6
8	Driver Thorax Rib Deflection Maximum vs. Time	B-6
9	Driver Anterior Abdominal Force (Y) vs. Time	B-7
10	Driver Middle Abdominal Force (Y) vs. Time	B-7
11	Driver Posterior Abdominal Force (Y) vs. Time	B-7
12	Driver Total Abdominal Force (Y) vs. Time	B-7
13	Driver Pubic Symphysis Force (Y) vs. Time	B-8
14	Passenger Head Acceleration (X) Primary vs. Time	B-9
15	Passenger Head Acceleration (Y) Primary vs. Time	B-9
16	Passenger Head Acceleration (Z) Primary vs. Time	B-9
17	Passenger Head Resultant Acceleration Primary vs. Time	B-9
18	Passenger Lower Spine T12 Acceleration (X) vs. Time	B-10
19	Passenger Lower Spine T12 Acceleration (Y) vs. Time	B-10
20	Passenger Lower Spine T12 Acceleration (Z) vs. Time	B-10
21	Passenger Lower Spine T12 Resultant Acceleration vs. Time	B-10
22	Passenger Iliac Force on Impact Side (Y) vs. Time	B-11
23	Passenger Acetabulum Force on Impact Side (Y) vs. Time	B-11
24	Passenger Total Pelvic Force on Impact Side (Y) vs. Time	B-11



The following additional data can be obtained from the Research and Development section of the NHTSA website (<http://www.nhtsa.gov>)

### **Additional Driver & Passenger Dummy Instrumentation Data**

Driver Lower Spine T12 Acceleration (X)  
Driver Lower Spine T12 Acceleration (Y)  
Driver Lower Spine T12 Acceleration (Z)  
Passenger Upper Thorax Rib Deflection (Y)  
Passenger Middle Thorax Rib Deflection (Y)  
Passenger Lower Thorax Rib Deflection (Y)  
Passenger Upper Abdomen Rib Deflection (Y)  
Passenger Lower Abdomen Rib Deflection (Y)  
Driver Head Acceleration Redundant (X)  
Driver Head Acceleration Redundant (Y)  
Driver Head Acceleration Redundant (Z)  
Passenger Head Acceleration Redundant (X)  
Passenger Head Acceleration Redundant (Y)  
Passenger Head Acceleration Redundant (Z)  
Driver Head Angular Velocity (X)  
Driver Head Angular Velocity (Y)  
Driver Head Angular Velocity (Z)  
Passenger Head Angular Velocity (X)  
Passenger Head Angular Velocity (Y)  
Passenger Head Angular Velocity (Z)

## Vehicle Instrumentation Data

Vehicle Center of Gravity Acceleration (X)  
Vehicle Center of Gravity Acceleration (Y)  
Vehicle Center of Gravity Acceleration (Z)  
Right Side Sill at Front Seat Acceleration (X)  
Right Side Sill at Front Seat Acceleration (Y)  
Right Side Sill at Front Seat Acceleration (Z)  
Right Side Sill at Rear Seat Acceleration (X)  
Right Side Sill at Rear Seat Acceleration (Y)  
Right Side Sill at Rear Seat Acceleration (Z)  
Left Side Sill at Front Seat Acceleration (Y)  
Left Side Sill at Rear Seat Acceleration (Y)  
Lower A-Post Acceleration (Y)  
Middle A-Post Acceleration (Y)  
Lower B-Post Acceleration (Y)  
Middle B-Post Acceleration (Y)  
Front Seat Track Acceleration (Y)  
Rear Seat Structure Acceleration (Y)  
Right Rear Occupant Compartment Acceleration (Y)  
Engine Block (X)  
Engine Block (Y)  
Rear Floorpan Above Axle Acceleration (X)  
Rear Floorpan Above Axle Acceleration (Y)  
Rear Floorpan Above Axle Acceleration (Z)

## MDB Instrumentation Data


MDB Center of Gravity Acceleration (X)  
MDB Center of Gravity Acceleration (Y)  
MDB Center of Gravity Acceleration (Z)  
MDB Rear Acceleration (X)  
MDB Rear Acceleration (Y)  
Left MDB Contact Switch  
Right MDB Contact Switch

**NHTSA**

Test Lab: CTF  
Test Number: 190221 (M20190102)

Position #1 ES-2 Dummy with Rib Extension (F030)  
Position #4 SID IIs Dummy (305)

Test Date: 02/21/2019




<Max>

4.09 g at 160.72 ms

<Min>

-16.35 g at 54.48 ms

CFC\_1000




<Max>

30.06 g at 52.16 ms

<Min>

-4.47 g at 283.44 ms

CFC\_1000




<Max>

8.16 g at 37.04 ms

<Min>

-6.72 g at 63.76 ms

CFC\_1000



<Max>

33.76 g at 52.88 ms

<Min>

0.04 g at -19.36 ms

CFC\_1000





# NHTSA


Test Lab: CTF

Test Number: 190221 (M20190102)

Test Date: 02/21/2019

Position #1 ES-2 Dummy with Rib Extension (F030)

Position #4 SID IIs Dummy (305)




<Max>

12.63 mm at 39.52 ms

<Min>

-1.41 mm at 84.32 ms

CFC\_180




<Max>

15.72 mm at 35.28 ms

<Min>

-1.25 mm at 80.32 ms

CFC\_180




<Max>

19.12 mm at 33.60 ms

<Min>

-0.51 mm at 276.40 ms

CFC\_180



<Max>

19.12 mm at 33.60 ms

<Min>

-0.51 mm at 276.40 ms

CFC\_180



# NHTSA


Test Lab: CTF

Test Number: 190221 (M20190102)

Test Date: 02/21/2019

Position #1 ES-2 Dummy with Rib Extension (F030)

Position #4 SID IIs Dummy (305)




<Max>

307.54 N at 46.16 ms

<Min>

-11.36 N at 15.84 ms

CFC\_600




<Max>

280.70 N at 27.12 ms

<Min>

-5.51 N at 9.60 ms

CFC\_600




<Max>

264.68 N at 29.52 ms

<Min>

-12.00 N at 171.12 ms

CFC\_600



<Max>

824.59 N at 47.20 ms

<Min>

-11.74 N at 250.72 ms

CFC\_600



**NHTSA**


Test Lab: CTF

Test Number: 190221 (M20190102)

Test Date: 02/21/2019

Position #1 ES-2 Dummy with Rib Extension (F030)

Position #4 SID IIs Dummy (305)



<Max>

123.56 N at 126.72 ms

<Min>

-1,458.73 N at 47.36 ms

CFC\_600






**NHTSA**

Test Lab: CTF  
Test Number: 190221 (M20190102)

Position #1 ES-2 Dummy with Rib Extension (F030)  
Position #4 SID IIs Dummy (305)

Test Date: 02/21/2019




<Max>

4.72 g at 29.68 ms

<Min>

-18.74 g at 74.24 ms

CFC\_1000




<Max>

35.51 g at 67.20 ms

<Min>

-7.56 g at 154.88 ms

CFC\_1000




<Max>

5.71 g at 47.68 ms

<Min>

-22.62 g at 70.96 ms

CFC\_1000



<Max>

40.90 g at 70.24 ms

<Min>

0.04 g at -19.92 ms


CFC\_1000




**NHTSA**

Test Lab: CTF  
Test Number: 190221 (M20190102)


Test Date: 02/21/2019  
Position #1 ES-2 Dummy with Rib Extension (F030)  
Position #4 SID IIs Dummy (305)




**<Max>**  
5.85 g at 173.28 ms  
**<Min>**  
-12.04 g at 59.04 ms  
CFC\_180



**<Max>**  
49.68 g at 56.32 ms  
**<Min>**  
-6.35 g at 172.96 ms  
CFC\_180



**<Max>**  
12.08 g at 70.08 ms  
**<Min>**  
-13.70 g at 49.28 ms  
CFC\_180



**<Max>**  
51.32 g at 56.32 ms  
**<Min>**  
0.02 g at -7.12 ms  
CFC\_180



# NHTSA


Test Lab: CTF

Test Number: 190221 (M20190102)

Test Date: 02/21/2019

Position #1 ES-2 Dummy with Rib Extension (F030)

Position #4 SID IIs Dummy (305)




**<Max>**

763.04 N at 57.36 ms

**<Min>**

-131.29 N at 46.08 ms

CFC\_600




**<Max>**

2,210.39 N at 49.60 ms

**<Min>**

-40.81 N at 215.12 ms

CFC\_600



**<Max>**

2,661.86 N at 54.32 ms

**<Min>**

-33.83 N at 97.36 ms

CFC\_600





**APPENDIX C**  
**DUMMY PERFORMANCE CALIBRATION TEST DATA**

## TABLE OF CALIBRATION MEASUREMENTS AND PLOTS

### ES-2re (Driver) Dummy

#### Description

**Table 1.** External Measurements

**Table 2.** Head Drop Test

- Head (X) Acceleration (G's) vs. Time (ms)
- Head (Y) Acceleration (G's) vs. Time (ms)
- Head (Z) Acceleration (G's) vs. Time (ms)
- Resultant Head Acceleration (G's) vs. Time (ms)

**Table 3** Neck Pendulum Test

- Pendulum Velocity (m/s) vs. Time (ms)
- Flexion Angle (°) vs. Time (ms)
- Potentiometer A (°) vs. Time (ms)
- Potentiometer B (°) vs. Time (ms)
- Potentiometer C (°) vs. Time (ms)

**Table 4.** Shoulder Impact Test

- Impactor Acceleration (G's) vs. Time (ms)

**Table 5.** Thorax – Upper Rib Drop Test

- Upper Rib Displacement @ 459 mm Drop Height (mm) vs. Time (ms)
- Upper Rib Displacement @ 815 mm Drop Height (mm) vs. Time (ms)

**Table 6.** Thorax – Middle Rib Drop Test

- Middle Rib Displacement @ 459 mm Drop Height (mm) vs. Time (ms)
- Middle Rib Displacement @ 815 mm Drop Height (mm) vs. Time (ms)

**Table 7.** Thorax – Lower Rib Drop Test

- Lower Rib Displacement @ 459 mm Drop Height (mm) vs. Time (ms)
- Lower Rib Displacement @ 815 mm Drop Height (mm) vs. Time (ms)

**Table 8.** Thorax – Full Body Impact Test

- Pendulum Acceleration (G's) vs. Time (ms)
- Impactor Force (kN) vs. Time (ms)
- Upper Rib Displacement (mm) vs. Time (ms)
- Middle Rib Displacement (mm) vs. Time (ms)
- Lower Rib Displacement (mm) vs. Time (ms)

**Table 9.** Abdomen Impact Test

- Impactor Force (kN) vs. Time (ms)
- Front Abdomen Force (kN) vs. Time (ms)
- Middle Abdomen Force (kN) vs. Time (ms)
- Rear Abdomen Force (kN) vs. Time (ms)
- Total Abdomen Force (kN) vs. Time (ms)

**Table 10.** Lumbar Spine Flexion Test

- Pendulum Velocity (m/s) vs. Time (ms)
- Spine Flexion Angle (°) vs. Time (ms)
- Potentiometer A (°) vs. Time (ms)
- Potentiometer B (°) vs. Time (ms)
- Potentiometer C (°) vs. Time (ms)

**Table 11.** Pelvis Impact Test

- Pendulum Acceleration (G's) vs. Time (ms)
- Impactor Force (kN) vs. Time (ms)
- Pubic Symphysis (Y) Force (kN) vs. Time (ms)

## TABLE OF CALIBRATION MEASUREMENTS AND PLOTS

### SID-IIs (Rear Passenger) Dummy

#### Description

**Table 1.** External Measurements

**Table 2.** Head Drop Test

- Head (X) Acceleration (G's) vs. Time (ms)
- Head (Y) Acceleration (G's) vs. Time (ms)
- Head (Z) Acceleration (G's) vs. Time (ms)
- Resultant Head Acceleration (G's) vs. Time (ms)

**Table 3.** Lateral Neck Pendulum Test

- Pendulum Velocity (m/s) vs. Time (ms)
- Flexion Angle (°) vs. Time (ms)
- Moment About Occipital Condyle (Nm) vs. Time (ms)

**Table 4.** Shoulder Impact Test

- Impactor Acceleration (G's) vs. Time (ms)
- Shoulder Displacement (mm) vs. Time (ms)
- Upper Spine Acceleration (G's) vs. Time (ms)

**Table 5.** Thorax (With Arm) Impact Test

- Impactor Acceleration (G's) vs. Time (ms)
- Shoulder Displacement (mm) vs. Time (ms)
- Upper Rib Displacement (mm) vs. Time (ms)
- Middle Rib Displacement (mm) vs. Time (ms)
- Lower Rib Displacement (mm) vs. Time (ms)
- Upper Spine Acceleration (G's) vs. Time (ms)
- Lower Spine Acceleration (G's) vs. Time (ms)

**Table 6.** Thorax (Without Arm) Impact Test

- Impactor Acceleration (G's) vs. Time (ms)
- Upper Rib Displacement (mm) vs. Time (ms)
- Middle Rib Displacement (mm) vs. Time (ms)
- Lower Rib Displacement (mm) vs. Time (ms)
- Upper Spine Acceleration (G's) vs. Time (ms)
- Lower Spine Acceleration (G's) vs. Time (ms)

**Table 7.** Abdomen Impact Test

- Impactor Acceleration (G's) vs. Time (ms)
- Upper Abdominal Rib Displacement (mm) vs. Time (ms)
- Lower Abdominal Rib Displacement (mm) vs. Time (ms)
- Lower Spine Acceleration (G's) vs. Time (ms)

**Table 8.** Pelvis Plug Quasi-Static Test (Optional\*)

**Table 9.** Pelvis Acetabulum Impact Test

- Impactor Acceleration (G's) vs. Time (ms)
- Pelvis (Y) Acceleration (G's) vs. Time (ms)
- Acetabulum Force (N) vs. Time (ms)

**Table 10.** Pelvis Iliac Impact Test

- Impactor Acceleration (G's) vs. Time (ms)
- Pelvis (Y) Acceleration (G's) vs. Time (ms)
- Iliac Force (N) vs. Time (ms)



**Pre-Test Calibration Sheets**  
**Driver S/N F030**

**Transportation Research Center Inc.**  
**572U ES-2re Dummy**  
**External Dimensions**  
**Serial No. F030 Calibration No. 60**

Symbol	Description	Specification	Results	Pass
		mm	mm	
1	Sitting Height	900.0 - 918.0	910	Yes
2	Seat to Shoulder Joint	558.0 - 572.0	560	Yes
3	Seat to Lower Face of Thoracic Spine Box	346.0 - 356.0	347	Yes
4	Seat to Hip Joint (center of bolt)	97.0 - 103.0	97	Yes
5	Sole to Seat, Sitting	433.0 - 451.0	445	Yes
6	Head Width	152.0 - 158.0	155	Yes
7	Shoulder/Arm Width	461.0 - 479.0	475	Yes
8	Thorax Width	322.0 - 332.0	328	Yes
9	Abdomen Width	273.0 - 287.0	280	Yes
10	Pelvis Lap Width	359.0 - 373.0	367	Yes
11	Head Depth	196.0 - 206.0	201	Yes
12	Thorax Depth	262.0 - 272.0	262	Yes
13	Abdomen Depth	194.0 - 204.0	199	Yes
14	Pelvis Depth	235.0 - 245.0	242	Yes
15	Back of Buttocks to Hip Joint (center of bolt)	150.0 - 160.0	156	Yes
16	Back of Buttocks to Front of Knee	597.0 - 615.0	605	Yes

Baseline 10/07/05



## Transportation Research Center Inc.

Left Lateral Head Drop  
ES-2re Serial No. F030 Certification No. 60-1  
Test Date: 1/10/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.7 °C	Yes
Relative Humidity	10 - 70 %	38 %	Yes
Peak Resultant Acceleration	125 - 155 g	142.4 g	Yes
Peak Longitudinal Acceleration	(-15) - 15 g	9.4 g	Yes
Is Resultant Acceleration Curve Unimodal within 15% of Main Pulse?	Yes	Yes	Yes

**Test meets specifications.**

**Condition: Used**

**Comments:**

**Head Skin S/N: DP6812**

## Transportation Research Center Inc.

Left Lateral Neck  
ES-2re Serial No. F030 Certification No. 60-3  
Test Date: 1/10/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.3 °C	Yes
Relative Humidity	10 - 70 %	41 %	Yes
Pendulum Integrated Velocity Change within Corridor	Yes	Yes	Yes
Pendulum Velocity	(-3.3) - (-3.5) m/s	-3.43 m/s	Yes
Maximum Headform Flexion			
Peak	(-49) - (-59) deg	-52.4 deg	Yes
Time of Peak	54 - 66 ms	59.5 ms	Yes
Headform Flexion Decay			
- Peak to Zero	53 - 88 ms	57.0 ms	Yes

**Test meets specifications.**

**Condition:** Used



**Comments:**

**Neck S/N:** DS5463



# Transportation Research Center Inc.

Left Lateral Neck  
ES-2re Serial No. F030 Certification No. 60-3  
Test Date: 1/10/2019




Specification Source: CFR49 Part 572 Subpart U  
with Polarity in accordance with J211

01.10.2019 12:50:40 1474




# Transportation Research Center Inc.


Left Lateral Neck  
ES-2re Serial No. F030 Certification No. 60-3  
Test Date: 1/10/2019




Filter Class: CFC\_180  
Max: 15.5 ° at 161.3 ms  
Min: -34.1 ° at 59.1 ms



Filter Class: CFC\_180  
Max: 17.7 ° at 163.4 ms  
Min: -31.1 ° at 55.8 ms



Filter Class: CFC\_180  
Max: 12.0 ° at 165.8 ms  
Min: -18.5 ° at 54.5 ms



Filter Class: CFC\_180  
Max: 27.5 ° at 161.3 ms  
Min: -52.4 ° at 59.5 ms


Specification Source: CFR49 Part 572 Subpart U  
with Polarity in accordance with J211

01.10.2019 12:50:40 1474




# Transportation Research Center Inc.


Left Lateral Head Drop  
ES-2re Serial No. F030 Certification No. 60-1  
Test Date: 1/10/2019




Filter Class: CFC\_1000  
Max: 9.4 g at 3.4 ms  
Min: -3.1 g at 1.9 ms



Filter Class: CFC\_1000  
Max: 112.2 g at 2.2 ms  
Min: -5.4 g at 5.4 ms



Filter Class: CFC\_1000  
Max: 87.7 g at 2.2 ms  
Min: -1.2 g at 7.9 ms



Filter Class: CFC\_1000  
Max: 142.4 g at 2.2 ms  
Min: 0.0 g at -1.0 ms

## Transportation Research Center Inc.

Left Lateral Shoulder  
ES-2re Serial No. F030 Certification No. 60-1  
Test Date: 1/11/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.2 °C	Yes
Relative Humidity	10 - 70 %	37 %	Yes
Test Probe Velocity	4.2 - 4.4 m/s	4.28 m/s	Yes
Test Probe Acceleration	(-7.5) - (-10.5) g	-10.44 g	Yes

**Test meets specifications.**

**Condition: Used**


**Comments:**

**Arm S/N: 175-3501-07014**



# Transportation Research Center Inc.

Left Lateral Shoulder  
ES-2re Serial No. F030 Certification No. 60-1  
Test Date: 1/11/2019



Filter Class: CFC\_180  
Max: 0.4 g at 51.8 ms  
Min: -10.4 g at 11.4 ms

Specification Source: CFR49 Part 572 Subpart U  
with Polarity in accordance with J211

01.11.2019 09:18:38 577



## Transportation Research Center Inc.

3.0 m/s Upper Upper Full Rib Module  
ES-2re Serial No. F030 Certification No. 60-1  
Test Date: 1/10/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.3 °C	Yes
Relative Humidity	10 - 70 %	36 %	Yes
3.0 m/s Test Rib Displacement (454 mm to 464 mm)	36 - 40 mm	37.2 mm	Yes

**Test meets specifications.**

**Condition: Used**


**Comments:**

**Drop Height: 462mm**

**Rib Module: 175-4008-A**

# Transportation Research Center Inc.

3.0 m/s Upper Upper Full Rib Module  
ES-2re Serial No. F030 Certification No. 60-1  
Test Date: 1/10/2019



Filter Class: CFC\_180  
Max: 37.2 mm at 27.1 ms  
Min: -5.1 mm at 61.3 ms

Specification Source: CFR49 Part 572 Subpart U  
with Polarity in accordance with J211

01.10.2019 08:27 584



## Transportation Research Center Inc.

4.0 m/s Upper Upper Full Rib Module  
ES-2re Serial No. F030 Certification No. 60-1  
Test Date: 1/10/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.6 °C	Yes
Relative Humidity	10 - 70 %	37 %	Yes
4.0 m/s Test Rib Displacement (807 mm to 823 mm)	46 - 51 mm	46.2 mm	Yes

**Test meets specifications.**

**Condition: Used**

**Comments:**


**Drop Height: 816mm**

**Rib Module: 175-4008-A**



# Transportation Research Center Inc.

4.0 m/s Upper Upper Full Rib Module  
ES-2re Serial No. F030 Certification No. 60-1  
Test Date: 1/10/2019



Filter Class: CFC\_180  
Max: 46.2 mm at 24.1 ms  
Min: -5.6 mm at 56.4 ms

Specification Source: CFR49 Part 572 Subpart U  
with Polarity in accordance with J211

01.10.2019 08:20 477



## Transportation Research Center Inc.

3.0 m/s Center Full Rib Module  
ES-2re Serial No. F030 Certification No. 60-1  
Test Date: 1/10/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.6 °C	Yes
Relative Humidity	10 - 70 %	37 %	Yes
3.0 m/s Test Rib Displacement (454 mm to 464 mm)	36 - 40 mm	37.7 mm	Yes

**Test meets specifications.**

**Condition: Used**


**Comments:**

**Drop Height: 462 mm**

**Rib Module: 175-4008-A**

# Transportation Research Center Inc.

3.0 m/s Center Full Rib Module  
ES-2re Serial No. F030 Certification No. 60-1  
Test Date: 1/10/2019



Filter Class: CFC\_180  
Max: 37.7 mm at 26.8 ms  
Min: -3.5 mm at 60.2 ms

Specification Source: CFR49 Part 572 Subpart U  
with Polarity in accordance with J211

01.10.2019 08:40 573



## Transportation Research Center Inc.

4.0 m/s Center Full Rib Module  
ES-2re Serial No. F030 Certification No. 60-1  
Test Date: 1/10/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.2 °C	Yes
Relative Humidity	10 - 70 %	36 %	Yes
4.0 m/s Test Rib Displacement (807 mm to 823 mm)	46 - 51 mm	48.6 mm	Yes

**Test meets specifications.**

**Condition: Used**

**Comments:**


**Drop Height: 816 mm**

**Rib Module: 175-4008-A**



# Transportation Research Center Inc.

4.0 m/s Center Full Rib Module  
ES-2re Serial No. F030 Certification No. 60-1  
Test Date: 1/10/2019



Filter Class: CFC\_180  
Max: 48.6 mm at 25.8 ms  
Min: -4.0 mm at 58.2 ms

Specification Source: CFR49 Part 572 Subpart U  
with Polarity in accordance with J211

01.10.2019 08:32 466



## Transportation Research Center Inc.

3.0 m/s Lower Full Rib Module  
ES-2re Serial No. F030 Certification No. 60-1  
Test Date: 1/10/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.7 °C	Yes
Relative Humidity	10 - 70 %	39 %	Yes
3.0 m/s Test Rib Displacement (454 mm to 464 mm)	36 - 40 mm	38.3 mm	Yes

**Test meets specifications.**

**Condition: Used**


**Comments:**

**Drop Height: 462 mm**

**Rib Module: 175-4008-A-06-017**

# Transportation Research Center Inc.

3.0 m/s Lower Full Rib Module  
ES-2re Serial No. F030 Certification No. 60-1  
Test Date: 1/10/2019



Filter Class: CFC\_180  
Max: 38.3 mm at 29.6 ms  
Min: -4.3 mm at 64.6 ms

Specification Source: CFR49 Part 572 Subpart U  
with Polarity in accordance with J211

01.10.2019 08:50 549



## Transportation Research Center Inc.

4.0 m/s Lower Full Rib Module  
ES-2re Serial No. F030 Certification No. 60-1  
Test Date: 1/10/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.3 °C	Yes
Relative Humidity	10 - 70 %	38 %	Yes
4.0 m/s Test Rib Displacement (807 mm to 823 mm)	46 - 51 mm	49.3 mm	Yes

**Test meets specifications.**

**Condition: Used**

**Comments:**


**Drop Height: 816 mm**

**Rib Module: 175-4008-A-06-017**



# Transportation Research Center Inc.

4.0 m/s Lower Full Rib Module  
ES-2re Serial No. F030 Certification No. 60-1  
Test Date: 1/10/2019



Filter Class: CFC\_180  
Max: 49.3 mm at 27.7 ms  
Min: -4.8 mm at 61.5 ms

Specification Source: CFR49 Part 572 Subpart U  
with Polarity in accordance with J211

01.10.2019 08:44 451



## Transportation Research Center Inc.

Left Lower Thorax  
ES-2re Serial No. F030 Certification No. 60-1  
Test Date: 1/11/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.6 °C	Yes
Relative Humidity	10 - 70 %	37 %	Yes
Impactor Velocity	5.4 - 5.60 m/s	5.493 m/s	Yes
Peak Impactor Force after 6 ms	(-5,100) - (-6,200) N	-5,487.8 N	Yes
Upper Rib Displacement	34 - 41 mm	38.0 mm	Yes
Center Rib Displacement	37 - 45 mm	42.7 mm	Yes
Lower Rib Displacement	37 - 44 mm	41.7 mm	Yes

**Test meets specifications.**

**Condition: Used**

**Comments:**


**Upper Rib Module S/N: 175-4008-A**

**Middle Rib Module S/N: 175-4008-A**

**Lower Rib Module S/N: 175-4008-A-06-017**

# Transportation Research Center Inc.

Left Lower Thorax  
ES-2re Serial No. F030 Certification No. 60-1  
Test Date: 1/11/2019



Filter Class: CFC\_180  
Max: 40.2 N at 74.2 ms  
Min: -9,813.9 N at 3.1 ms




Specification Source: CFR49 Part 572 Subpart U  
with Polarity in accordance with J211

01.11.2019 09:36:03 457



# Transportation Research Center Inc.

Left Lower Thorax  
ES-2re Serial No. F030 Certification No. 60-1  
Test Date: 1/11/2019



Specification Source: CFR49 Part 572 Subpart U  
with Polarity in accordance with J211

01.11.2019 09:36:04 457





## Transportation Research Center Inc.

Left Lateral Lumbar  
ES-2re Serial No. F030 Certification No. 60-5  
Test Date: 1/11/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.1 °C	Yes
Relative Humidity	10 - 70 %	39 %	Yes
Pendulum Integrated Velocity Change within Corridor	Yes	Yes	Yes
Pendulum Velocity	(-5.95) - (-6.15) m/s	-6.117 m/s	Yes
Maximum Headform Flexion			
Peak	(-45) - (-55) deg	-48.1 deg	Yes
Time of Peak	39 - 53 ms	45.0 ms	Yes
Headform Flexion Decay			
- Peak to Zero	37 - 57 ms	37.9 ms	Yes

**Test meets specifications.**



**Condition:** Used

**Comments:**

**Lumbar S/N: DM3011**

# Transportation Research Center Inc.

Left Lateral Lumbar  
ES-2re Serial No. F030 Certification No. 60-5  
Test Date: 1/11/2019




Specification Source: CFR49 Part 572 Subpart U  
with Polarity in accordance with J211

01.11.2019 07:07:22 669




# Transportation Research Center Inc.


Left Lateral Lumbar  
ES-2re Serial No. F030 Certification No. 60-5  
Test Date: 1/11/2019




Filter Class: CFC\_180  
Max: 14.8 ° at 109.9 ms  
Min: -32.0 ° at 45.0 ms



Filter Class: CFC\_180  
Max: 16.9 ° at 108.4 ms  
Min: -28.2 ° at 43.3 ms



Filter Class: CFC\_180  
Max: 9.4 ° at 107.4 ms  
Min: -16.1 ° at 44.3 ms



Filter Class: CFC\_180  
Max: 24.2 ° at 107.5 ms  
Min: -48.1 ° at 45.0 ms

Specification Source: CFR49 Part 572 Subpart U  
with Polarity in accordance with J211

01.11.2019 07:07:23 669



## Transportation Research Center Inc.

Left Lateral Abdomen  
ES-2re Serial No. F030 Certification No. 60-1  
Test Date: 1/11/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.2 °C	Yes
Relative Humidity	10 - 70 %	40 %	Yes
Test Probe Velocity	3.9 - 4.1 m/s	4.07 m/s	Yes
Test Probe Force			
Peak	4,000 - 4,800 N	4,248.1 N	Yes
Time of Peak	10.6 - 13.0 ms	11.60 ms	Yes
Total Abdominal Force			
Peak	2,200 - 2,700 N	2,480.5 N	Yes
Time of Peak	10.0 - 12.3 ms	10.80 ms	Yes

**Test meets specifications.**

**Condition: Used**


**Comments:**

**Abdomen S/N: 1066**




# Transportation Research Center Inc.

Left Lateral Abdomen  
ES-2re Serial No. F030 Certification No. 60-1  
Test Date: 1/11/2019



Filter Class: CFC\_180  
Max: 18.5 g at 11.6 ms  
Min: -0.4 g at -0.6 ms



Filter Class: CFC\_180  
Max: 4,248.1 N at 11.6 ms  
Min: -80.8 N at -0.6 ms


Specification Source: CFR49 Part 572 Subpart U  
with Polarity in accordance with J211

01.11.2019 10:00:13 596




# Transportation Research Center Inc.


Left Lateral Abdomen  
ES-2re Serial No. F030 Certification No. 60-1  
Test Date: 1/11/2019




Filter Class: CFC\_600  
Max: 532.8 N at 11.9 ms  
Min: -24.5 N at 98.2 ms



Filter Class: CFC\_600  
Max: 1,065.2 N at 11.2 ms  
Min: -10.1 N at 98.2 ms



Filter Class: CFC\_600  
Max: 927.6 N at 9.8 ms  
Min: -5.6 N at 69.5 ms



Filter Class: CFC\_600  
Max: 2,480.5 N at 10.8 ms  
Min: -33.9 N at 98.9 ms

Specification Source: CFR49 Part 572 Subpart U  
with Polarity in accordance with J211

01.11.2019 10:00:14 596



## Transportation Research Center Inc.

Left Lateral Pelvis  
ES-2re Serial No. F030 Certification No. 60-1  
Test Date: 1/11/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.3 °C	Yes
Relative Humidity	10 - 70 %	35 %	Yes
Test Probe Velocity	4.2 - 4.4 m/s	4.36 m/s	Yes
Test Probe Force			
Peak	4,700 - 5,400 N	5,236.9 N	Yes
Time of Peak	11.8 - 16.1 ms	12.64 ms	Yes
Pubic Symphysis Force			
Peak	(-1,230) - (-1,590) N	-1,286.5 N	Yes
Time of Peak	12.2 - 17.0 ms	13.52 ms	Yes

**Test meets specifications.**


**Condition:** Used

**Comments:**


**Pelvis Skin S/N:** N/A

# Transportation Research Center Inc.


Left Lateral Pelvis  
ES-2re Serial No. F030 Certification No. 60-1  
Test Date: 1/11/2019



Filter Class: CFC\_180  
Max: 22.9 g at 12.6 ms  
Min: -0.1 g at 71.8 ms



Filter Class: CFC\_180  
Max: 5,236.9 N at 12.6 ms  
Min: -31.5 N at 71.8 ms



Filter Class: CFC\_600  
Max: 171.0 N at 27.5 ms  
Min: -1,286.5 N at 13.5 ms



**Post-Test Calibration Sheets  
Driver S/N F030**

**Transportation Research Center Inc.**  
**572U ES-2re Dummy**  
**External Dimensions**  
**Serial No. F030 Calibration No. 61**

Symbol	Description	Specification	Results	Pass
		mm	mm	
1	Sitting Height	900.0 - 918.0	910	Yes
2	Seat to Shoulder Joint	558.0 - 572.0	560	Yes
3	Seat to Lower Face of Thoracic Spine Box	346.0 - 356.0	347	Yes
4	Seat to Hip Joint (center of bolt)	97.0 - 103.0	97	Yes
5	Sole to Seat, Sitting	433.0 - 451.0	445	Yes
6	Head Width	152.0 - 158.0	155	Yes
7	Shoulder/Arm Width	461.0 - 479.0	475	Yes
8	Thorax Width	322.0 - 332.0	328	Yes
9	Abdomen Width	273.0 - 287.0	280	Yes
10	Pelvis Lap Width	359.0 - 373.0	367	Yes
11	Head Depth	196.0 - 206.0	201	Yes
12	Thorax Depth	262.0 - 272.0	262	Yes
13	Abdomen Depth	194.0 - 204.0	199	Yes
14	Pelvis Depth	235.0 - 245.0	242	Yes
15	Back of Buttocks to Hip Joint (center of bolt)	150.0 - 160.0	156	Yes
16	Back of Buttocks to Front of Knee	597.0 - 615.0	605	Yes

Baseline 10/07/05



## Transportation Research Center Inc.

Left Lateral Head Drop  
ES-2re Serial No. F030 Certification No. 61-1  
Test Date: 2/22/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.4 °C	Yes
Relative Humidity	10 - 70 %	39 %	Yes
Peak Resultant Acceleration	125 - 155 g	135.3 g	Yes
Peak Longitudinal Acceleration	(-15) - 15 g	8.5 g	Yes
Is Resultant Acceleration Curve Unimodal within 15% of Main Pulse?	Yes	Yes	Yes

**Test meets specifications.**

**Condition: Used**

**Comments:**


**Head Skin S/N: DP6812**

# Transportation Research Center Inc.

Left Lateral Head Drop

ES-2re Serial No. F030 Certification No. 61-1


Test Date: 2/22/2019



Filter Class: CFC\_1000

Max: 8.5 g at 3.4 ms


Min: -3.0 g at 1.5 ms



Filter Class: CFC\_1000

Max: 108.9 g at 2.2 ms


Min: -4.6 g at 5.4 ms



Filter Class: CFC\_1000

Max: 80.3 g at 2.2 ms

Min: -1.8 g at 6.6 ms



Filter Class: CFC\_1000

Max: 135.3 g at 2.2 ms

Min: 0.0 g at -1.0 ms

Specification Source: CFR49 Part 572 Subpart U  
with Polarity in accordance with J211

02.22.2019 08:58:43 327





## Transportation Research Center Inc.

Left Lateral Neck  
ES-2re Serial No. F030 Certification No. 61-3  
Test Date: 2/22/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.5 °C	Yes
Relative Humidity	10 - 70 %	36 %	Yes
Pendulum Integrated Velocity Change within Corridor	Yes	Yes	Yes
Pendulum Velocity	(-3.3) - (-3.5) m/s	-3.33 m/s	Yes
Maximum Headform Flexion			
Peak	(-49) - (-59) deg	-50.6 deg	Yes
Time of Peak	54 - 66 ms	54.2 ms	Yes
Headform Flexion Decay			
- Peak to Zero	53 - 88 ms	62.5 ms	Yes

**Test meets specifications.**


**Condition:** Used

**Comments:**


**Neck S/N:** DS5463

# Transportation Research Center Inc.

Left Lateral Neck  
ES-2re Serial No. F030 Certification No. 61-3  
Test Date: 2/22/2019



Filter Class: CFC\_60  
Max: 32.8 g at 10.3 ms  
Min: -8.4 g at 23.0 ms



Filter Class: CFC\_60  
Max: 3.7 m/s at 36.9 ms  
Min: 0.0 m/s at 0.0 ms


Specification Source: CFR49 Part 572 Subpart U  
with Polarity in accordance with J211

02.22.2019 14:44:26 1481




# Transportation Research Center Inc.


Left Lateral Neck  
ES-2re Serial No. F030 Certification No. 61-3  
Test Date: 2/22/2019




Filter Class: CFC\_180  
Max: 15.3 ° at 160.5 ms  
Min: -32.3 ° at 60.8 ms



Filter Class: CFC\_180  
Max: 16.7 ° at 160.7 ms  
Min: -29.1 ° at 59.4 ms



Filter Class: CFC\_180  
Max: 11.3 ° at 157.0 ms  
Min: -18.5 ° at 54.6 ms



Filter Class: CFC\_180  
Max: 26.5 ° at 160.5 ms  
Min: -50.6 ° at 54.2 ms

Specification Source: CFR49 Part 572 Subpart U  
with Polarity in accordance with J211

02.22.2019 14:44:27 1481



## Transportation Research Center Inc.

Left Lateral Shoulder  
ES-2re Serial No. F030 Certification No. 61-1  
Test Date: 2/22/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.8 °C	Yes
Relative Humidity	10 - 70 %	40 %	Yes
Test Probe Velocity	4.2 - 4.4 m/s	4.33 m/s	Yes
Test Probe Acceleration	(-7.5) - (-10.5) g	-10.32 g	Yes

**Test meets specifications.**


**Condition: Used**

**Comments:**

**Arm S/N: 175-3501-07014**

# Transportation Research Center Inc.

Left Lateral Shoulder  
ES-2re Serial No. F030 Certification No. 61-1  
Test Date: 2/22/2019



Filter Class: CFC\_180  
Max: 2.1 g at 65.5 ms  
Min: -10.3 g at 11.6 ms

Specification Source: CFR49 Part 572 Subpart U  
with Polarity in accordance with J211

02.22.2019 15:50:42 523





## Transportation Research Center Inc.

3.0 m/s Upper Upper Full Rib Module  
ES-2re Serial No. F030 Certification No. 61-1  
Test Date: 2/22/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.4 °C	Yes
Relative Humidity	10 - 70 %	39 %	Yes
3.0 m/s Test Rib Displacement (454 mm to 464 mm)	36 - 40 mm	37.3 mm	Yes

**Test meets specifications.**

**Condition: Used**


**Comments:**

**Drop Height: 462mm**

**Rib Module: 175-4008-A**

# Transportation Research Center Inc.

3.0 m/s Upper Upper Full Rib Module  
ES-2re Serial No. F030 Certification No. 61-1  
Test Date: 2/22/2019



Filter Class: CFC\_180  
Max: 37.3 mm at 27.3 ms  
Min: -5.1 mm at 61.4 ms

Specification Source: CFR49 Part 572 Subpart U  
with Polarity in accordance with J211

02.22.2019 09:29:11 498



## Transportation Research Center Inc.

4.0 m/s Upper Upper Full Rib Module  
ES-2re Serial No. F030 Certification No. 61-1  
Test Date: 2/22/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.4 °C	Yes
Relative Humidity	10 - 70 %	39 %	Yes
4.0 m/s Test Rib Displacement (807 mm to 823 mm)	46 - 51 mm	46.8 mm	Yes

**Test meets specifications.**

**Condition: Used**


**Comments:**

**Drop Height: 816mm**

**Rib Module: 175-4008-A**

# Transportation Research Center Inc.

4.0 m/s Upper Upper Full Rib Module  
ES-2re Serial No. F030 Certification No. 61-1  
Test Date: 2/22/2019



Filter Class: CFC\_180  
Max: 46.8 mm at 24.2 ms  
Min: -5.5 mm at 56.2 ms

Specification Source: CFR49 Part 572 Subpart U  
with Polarity in accordance with J211

02.22.2019 09:20:24 408



## Transportation Research Center Inc.

3.0 m/s Center Full Rib Module  
ES-2re Serial No. F030 Certification No. 61-1  
Test Date: 2/22/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.4 °C	Yes
Relative Humidity	10 - 70 %	38 %	Yes
3.0 m/s Test Rib Displacement (454 mm to 464 mm)	36 - 40 mm	37.5 mm	Yes

**Test meets specifications.**

**Condition: Used**

**Comments:**


**Drop Height: 462 mm**

**Rib Module: 175-4008-A**



# Transportation Research Center Inc.

3.0 m/s Center Full Rib Module  
ES-2re Serial No. F030 Certification No. 61-1  
Test Date: 2/22/2019



Filter Class: CFC\_180  
Max: 37.5 mm at 27.1 ms  
Min: -3.3 mm at 60.3 ms

Specification Source: CFR49 Part 572 Subpart U  
with Polarity in accordance with J211

02.22.2019 09:50:26 500



## Transportation Research Center Inc.

4.0 m/s Center Full Rib Module  
ES-2re Serial No. F030 Certification No. 61-1  
Test Date: 2/22/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.4 °C	Yes
Relative Humidity	10 - 70 %	37 %	Yes
4.0 m/s Test Rib Displacement (807 mm to 823 mm)	46 - 51 mm	48.5 mm	Yes

**Test meets specifications.**

**Condition: Used**


**Comments:**

**Drop Height: 816 mm**

**Rib Module: 175-4008-A**

# Transportation Research Center Inc.

4.0 m/s Center Full Rib Module  
ES-2re Serial No. F030 Certification No. 61-1  
Test Date: 2/22/2019



Filter Class: CFC\_180  
Max: 48.5 mm at 25.8 ms  
Min: -3.8 mm at 58.2 ms

Specification Source: CFR49 Part 572 Subpart U  
with Polarity in accordance with J211

02.22.2019 09:38:05 420



## Transportation Research Center Inc.

3.0 m/s Lower Full Rib Module  
ES-2re Serial No. F030 Certification No. 61-1  
Test Date: 2/22/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.4 °C	Yes
Relative Humidity	10 - 70 %	41 %	Yes
3.0 m/s Test Rib Displacement (454 mm to 464 mm)	36 - 40 mm	38.4 mm	Yes

**Test meets specifications.**

**Condition: Used**


**Comments:**

**Drop Height: 462 mm**

**Rib Module: 175-4008-A-06-017**

# Transportation Research Center Inc.

3.0 m/s Lower Full Rib Module  
ES-2re Serial No. F030 Certification No. 61-1  
Test Date: 2/22/2019



Filter Class: CFC\_180  
Max: 38.4 mm at 30.0 ms  
Min: -4.2 mm at 64.7 ms

Specification Source: CFR49 Part 572 Subpart U  
with Polarity in accordance with J211

02.22.2019 10:02:31 456





## Transportation Research Center Inc.

4.0 m/s Lower Full Rib Module  
ES-2re Serial No. F030 Certification No. 61-1  
Test Date: 2/22/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.4 °C	Yes
Relative Humidity	10 - 70 %	40 %	Yes
4.0 m/s Test Rib Displacement (807 mm to 823 mm)	46 - 51 mm	49.5 mm	Yes

**Test meets specifications.**

**Condition: Used**


**Comments:**

**Drop Height: 816 mm**

**Rib Module: 175-4008-A-06-017**

# Transportation Research Center Inc.

4.0 m/s Lower Full Rib Module  
ES-2re Serial No. F030 Certification No. 61-1  
Test Date: 2/22/2019



Filter Class: CFC\_180  
Max: 49.5 mm at 27.4 ms  
Min: -4.2 mm at 61.2 ms

Specification Source: CFR49 Part 572 Subpart U  
with Polarity in accordance with J211

02.22.2019 09:56:30 412



## Transportation Research Center Inc.

Left Lower Thorax  
ES-2re Serial No. F030 Certification No. 61-1  
Test Date: 2/22/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.7 °C	Yes
Relative Humidity	10 - 70 %	41 %	Yes
Impactor Velocity	5.4 - 5.60 m/s	5.547 m/s	Yes
Peak Impactor Force after 6 ms	(-5,100) - (-6,200) N	-5,507.4 N	Yes
Upper Rib Displacement	34 - 41 mm	38.4 mm	Yes
Center Rib Displacement	37 - 45 mm	42.9 mm	Yes
Lower Rib Displacement	37 - 44 mm	42.0 mm	Yes

**Test meets specifications.**

**Condition: Used**

**Comments:**


**Upper Rib Module S/N: 175-4008-A**

**Middle Rib Module S/N: 175-4008-A**

**Lower Rib Module S/N: 175-4008-A-06-017**

# Transportation Research Center Inc.

Left Lower Thorax  
ES-2re Serial No. F030 Certification No. 61-1  
Test Date: 2/22/2019



Filter Class: CFC\_180  
Max: 613.3 N at 49.2 ms  
Min: -10,174.7 N at 2.8 ms




Specification Source: CFR49 Part 572 Subpart U  
with Polarity in accordance with J211

02.22.2019 15:54:33 445



# Transportation Research Center Inc.

Left Lower Thorax  
ES-2re Serial No. F030 Certification No. 61-1  
Test Date: 2/22/2019



Specification Source: CFR49 Part 572 Subpart U  
with Polarity in accordance with J211

02.22.2019 15:54:34 445





## Transportation Research Center Inc.

Left Lateral Lumbar  
ES-2re Serial No. F030 Certification No. 61-3  
Test Date: 2/22/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.4 °C	Yes
Relative Humidity	10 - 70 %	37 %	Yes
Pendulum Integrated Velocity Change within Corridor	Yes	Yes	Yes
Pendulum Velocity	(-5.95) - (-6.15) m/s	-6.097 m/s	Yes
Maximum Headform Flexion			
Peak	(-45) - (-55) deg	-48.1 deg	Yes
Time of Peak	39 - 53 ms	44.1 ms	Yes
Headform Flexion Decay			
- Peak to Zero	37 - 57 ms	37.4 ms	Yes

**Test meets specifications.**



**Condition:** Used

**Comments:**

**Lumbar S/N: DM3011**

# Transportation Research Center Inc.

Left Lateral Lumbar  
ES-2re Serial No. F030 Certification No. 61-3  
Test Date: 2/22/2019




Specification Source: CFR49 Part 572 Subpart U  
with Polarity in accordance with J211

02.22.2019 12:47:50 639




# Transportation Research Center Inc.


Left Lateral Lumbar  
ES-2re Serial No. F030 Certification No. 61-3  
Test Date: 2/22/2019




Filter Class: CFC\_180  
Max: 15.3 ° at 108.2 ms  
Min: -32.4 ° at 44.6 ms



Filter Class: CFC\_180  
Max: 16.5 ° at 107.2 ms  
Min: -28.6 ° at 43.8 ms



Filter Class: CFC\_180  
Max: 9.3 ° at 109.0 ms  
Min: -15.8 ° at 43.3 ms



Filter Class: CFC\_180  
Max: 24.6 ° at 108.3 ms  
Min: -48.1 ° at 44.1 ms

Specification Source: CFR49 Part 572 Subpart U  
with Polarity in accordance with J211

02.22.2019 12:47:51 639



## Transportation Research Center Inc.

Left Lateral Abdomen  
ES-2re Serial No. F030 Certification No. 61-2  
Test Date: 2/25/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.4 °C	Yes
Relative Humidity	10 - 70 %	37 %	Yes
Test Probe Velocity	3.9 - 4.1 m/s	4.10 m/s	Yes
Test Probe Force			
Peak	4,000 - 4,800 N	4,318.8 N	Yes
Time of Peak	10.6 - 13.0 ms	10.88 ms	Yes
Total Abdominal Force			
Peak	2,200 - 2,700 N	2,553.6 N	Yes
Time of Peak	10.0 - 12.3 ms	10.96 ms	Yes

**Test meets specifications.**


**Condition: Used**

**Comments:**


**Abdomen S/N: 1066**

# Transportation Research Center Inc.

Left Lateral Abdomen  
ES-2re Serial No. F030 Certification No. 61-2  
Test Date: 2/25/2019



Filter Class: CFC\_180  
Max: 18.8 g at 10.9 ms  
Min: -0.4 g at -0.6 ms



Filter Class: CFC\_180  
Max: 4,318.8 N at 10.9 ms  
Min: -83.0 N at -0.6 ms

Specification Source: CFR49 Part 572 Subpart U  
with Polarity in accordance with J211


02.25.2019 07:44:40 578






# Transportation Research Center Inc.


Left Lateral Abdomen  
ES-2re Serial No. F030 Certification No. 61-2  
Test Date: 2/25/2019




Filter Class: CFC\_600  
Max: 609.0 N at 11.4 ms  
Min: -23.9 N at 98.3 ms



Filter Class: CFC\_600  
Max: 1,114.7 N at 11.1 ms  
Min: -10.6 N at 98.2 ms



Filter Class: CFC\_600  
Max: 848.8 N at 10.2 ms  
Min: -4.2 N at 73.9 ms



Filter Class: CFC\_600  
Max: 2,553.6 N at 11.0 ms  
Min: -31.0 N at 99.8 ms

Specification Source: CFR49 Part 572 Subpart U  
with Polarity in accordance with J211

02.25.2019 07:44:41 578



## Transportation Research Center Inc.

Left Lateral Pelvis  
ES-2re Serial No. F030 Certification No. 61-2  
Test Date: 2/25/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.4 °C	Yes
Relative Humidity	10 - 70 %	37 %	Yes
Test Probe Velocity	4.2 - 4.4 m/s	4.38 m/s	Yes
Test Probe Force			
Peak	4,700 - 5,400 N	5,305.1 N	Yes
Time of Peak	11.8 - 16.1 ms	12.48 ms	Yes
Pubic Symphysis Force			
Peak	(-1,230) - (-1,590) N	-1,269.1 N	Yes
Time of Peak	12.2 - 17.0 ms	12.88 ms	Yes

**Test meets specifications.**


**Condition: Used**

**Comments:**


**Pelvis Skin S/N: N/A**

# Transportation Research Center Inc.


Left Lateral Pelvis  
ES-2re Serial No. F030 Certification No. 61-2  
Test Date: 2/25/2019



Filter Class: CFC\_180  
Max: 23.1 g at 12.5 ms  
Min: -0.2 g at 70.9 ms



Filter Class: CFC\_180  
Max: 5,305.1 N at 12.5 ms  
Min: -35.2 N at 70.9 ms



Filter Class: CFC\_600  
Max: 128.8 N at 27.4 ms  
Min: -1,269.1 N at 12.9 ms

**Pre-Test Calibration Sheets**  
**Passenger S/N 305**

**Transportation Research Center Inc.**  
**SIDIIs Dummy - Level D**  
**External Dimensions**  
**Serial No. 305 Calibration No. 68**

Symbol	Description	Specification	Results	Pass
		mm	mm	
A	Sitting Height	772.0 - 788.0	782	Yes
B	Shoulder Pivot Height	437.0 - 453.0	448	Yes
C	H-Point Height	79.0 - 89.0	86	Yes
D	H-Point from Seat Back	141.0 - 151.0	146	Yes
E	Shoulder Pivot from Backline	97.0 - 107.0	101	Yes
F	Thigh Clearance	119.0 - 135.0	130	Yes
G	Head Breadth	140.0 - 148.0	143	Yes
H	Head Back from Backline	40.0 - 46.0	44	Yes
I	Head Depth	178.0 - 188.0	185	Yes
J	Head Circumference	541.0 - 551.0	543	Yes
K	Buttock to Knee Length	514.0 - 540.0	534	Yes
L	Popliteal Height	343.0 - 369.0	348	Yes
M	Knee Pivot to Floor Height	393.0 - 409.0	396	Yes
N	Buttock Popliteal Length	416.0 - 442.0	434	Yes
O	Chest Depth without Jacket	195.0 - 211.0	197	Yes
P	Foot Length (right)	216.0 - 232.0	222	Yes
P	Foot Length (left)	216.0 - 232.0	220	Yes
Q	Hip Breadth	313.0 - 323.0	320	Yes
R	Arm Length	249.0 - 259.0	252	Yes
S	Knee Joint to seat Back	478.0 - 493.0	482	Yes
V	Shoulder Width (only one arm installed)	341.0 - 357.0	351	Yes
W	Foot Width (right)	78.0 - 94.0	85	Yes
W	Foot Width (left)	78.0 - 94.0	85	Yes
Y	Chest Circumference with Jacket	851.0 - 881.0	877	Yes
Z	Waist Circumference	761.0 - 791.0	780	Yes

Revised 9/29/2005





## Transportation Research Center Inc.

Left Lateral Head Drop  
SID IIS Serial No. 305 Certification No. 68-1  
Test Date: 1/10/2019

Test Parameter	Specification	Test Results	Pass
Temperature	18.9 - 25.6 °C	21.7 °C	Yes
Relative Humidity	10 - 70 %	37 %	Yes
Peak Head Resultant Acceleration	115 - 137 g	117.8 g	Yes
Peak Head Longitudinal Acceleration	(-15) - 15 g	-2.4 g	Yes
Is Head Resultant Acceleration Curve Unimodal within 15% of Peak?	Yes	Yes	Yes

**Test meets specifications.**

**Condition: Used**

**Comments:**


**Head Skin S/N: 1253**

# Transportation Research Center Inc.

Left Lateral Head Drop

SID IIS Serial No. 305 Certification No. 68-1


Test Date: 1/10/2019



Filter Class: CFC\_1000

Max: 1.9 g at 5.5 ms


Min: -2.4 g at 3.2 ms



Filter Class: CFC\_1000

Max: 92.0 g at 3.0 ms


Min: -0.8 g at 7.7 ms



Filter Class: CFC\_1000

Max: 73.8 g at 3.1 ms

Min: -0.6 g at 9.8 ms



Filter Class: CFC\_1000

Max: 117.8 g at 3.0 ms

Min: 0.0 g at +0.8 ms

Specification Source: CFR49 Part 572 Subpart V  
with Polarity in accordance with J211

01.10.2019 14:04:35 230



## Transportation Research Center Inc.

Left Lateral Neck  
SID IIS Serial No. 305 Certification No. 68-1  
Test Date: 1/11/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.3 °C	Yes
Relative Humidity	10 - 70 %	38 %	Yes
Pendulum Velocity	(-5.51) - (-5.63) m/s	-5.617 m/s	Yes
Pendulum Integrated Velocity			
Change at 10 ms	2.20 - 2.80 m/s	2.683 m/s	Yes
Change at 15 ms	3.30 - 4.10 m/s	3.834 m/s	Yes
Change at 20 ms	4.40 - 5.40 m/s	5.082 m/s	Yes
Change at 25 ms	5.40 - 6.10 m/s	5.988 m/s	Yes
Change at 25 to 100 ms	5.50 - 6.20 m/s	6.024 m/s	Yes
Maximum Headform Flexion occurring between 50ms and 70ms.			
Peak	(-71) - (-81) deg	-71.6 deg	Yes
Time of Peak	50 - 70 ms	67.5 ms	Yes
Total Neck Occipital Condyles Moment	36 - 44 N·m	37.2 N·m	Yes
Total Neck Occipital Condyles Moment Decay Time to 0 N·m	102 - 126 ms	123.6 ms	Yes

**Test meets specifications.**

**Condition: Used**

**Comments:**



**Neck S/N: 180-2001-606**

# Transportation Research Center Inc.

Left Lateral Neck

SID IIs Serial No. 305 Certification No. 68-1

Test Date: 1/11/2019



Specification Source: CFR49 Part 572 Subpart V  
with Polarity in accordance with J211

01.11.2019 07:50:47 748




# Transportation Research Center Inc.


Left Lateral Neck

SID IIs Serial No. 305 Certification No. 68-1


Test Date: 1/11/2019




Filter Class: CFC\_60  
Max: 18.4 ° at 193.9 ms  
Min: -63.0 ° at 81.8 ms



Filter Class: CFC\_60  
Max: 17.9 ° at 186.2 ms  
Min: -49.5 ° at 63.4 ms



Filter Class: CFC\_60  
Max: 14.4 ° at 177.4 ms  
Min: -12.5 ° at 61.1 ms



Filter Class: CFC\_60  
Max: 32.0 ° at 184.2 ms  
Min: -71.6 ° at 67.5 ms

Specification Source: CFR49 Part 572 Subpart V  
with Polarity in accordance with J211

01.11.2019 07:50:48 748






# Transportation Research Center Inc.


Left Lateral Neck

SID IIS Serial No. 305 Certification No. 68-1


Test Date: 1/11/2019




Filter Class: CFC\_1000  
Max: 432.3 N at 47.0 ms  
Min: -116.1 N at 180.3 ms



Filter Class: CFC\_600  
Max: 430.8 N at 46.9 ms  
Min: -115.8 N at 180.4 ms



Filter Class: CFC\_600  
Max: 30.9 Nm at 56.1 ms  
Min: -19.3 Nm at 6.8 ms



Filter Class: Without\_(Consta  
Max: 37.2 N.m at 56.2 ms  
Min: -15.0 N.m at 7.0 ms

Specification Source: CFR49 Part 572 Subpart V  
with Polarity in accordance with J211

01.11.2019 07:50:50 748



## Transportation Research Center Inc.

Left Lateral Shoulder  
SID IIs Serial No. 305 Certification No. 68-1  
Test Date: 1/10/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.2 °C	Yes
Relative Humidity	10 - 70 %	41 %	Yes
Impactor Velocity	4.2 - 4.4 m/s	4.28 m/s	Yes
Impactor Acceleration	(-13) - (-18) g	-16.2 g	Yes
Shoulder Displacement	28 - 37 mm	30.1 mm	Yes
Upper Spine Lateral Acceleration	17 - 22 g	19.9 g	Yes

**Test meets specifications.**

**Condition: Used**

**Comments:**

**Left Arm S/N: 952**


**Shoulder Rib S/N: 180-3355 169**

# Transportation Research Center Inc.


Left Lateral Shoulder

SID IIs Serial No. 305 Certification No. 68-1


Test Date: 1/10/2019



Filter Class: CFC\_180  
Max: 0.1 g at 54.5 ms  
Min: -16.2 g at 13.1 ms



Filter Class: CFC\_600  
Max: 30.1 mm at 17.3 ms  
Min: -0.0 mm at -3.8 ms



Filter Class: CFC\_180  
Max: 19.9 g at 7.6 ms  
Min: -8.3 g at 39.1 ms

## Transportation Research Center Inc.

Left Lateral Thorax with Arm  
SID IIs Serial No. 305 Certification No. 68-1  
Test Date: 1/10/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.6 °C	Yes
Relative Humidity	10 - 70 %	40 %	Yes
Impactor Velocity	6.60 - 6.80 m/s	6.755 m/s	Yes
Impactor Acceleration	(-30) - (-36) g	-32.5 g	Yes
Shoulder Displacement	31 - 40 mm	33.2 mm	Yes
Upper Thorax Rib Displacement	25 - 32 mm	26.3 mm	Yes
Center Thorax Rib Displacement	30 - 36 mm	31.5 mm	Yes
Lower Thorax Rib Displacement	32 - 38 mm	34.6 mm	Yes
Upper Spine Lateral Acceleration	34 - 43 g	39.0 g	Yes
Lower Spine Lateral Acceleration	29 - 37 g	32.2 g	Yes

**Test meets specifications.**

**Condition: Used**

**Comments:**

**Left Arm S/N: 952**


**Upper Thorax Rib S/N: 2135**

**Middle Thorax Rib S/N: 2136**


**Lower Thorax Rib S/N: 2137**

# Transportation Research Center Inc.


Left Lateral Thorax with Arm  
SID IIs Serial No. 305 Certification No. 68-1  
Test Date: 1/10/2019



Filter Class: CFC\_180  
Max: 0.2 g at 82.8 ms  
Min: -32.5 g at 13.2 ms



Filter Class: CFC\_180  
Max: 39.0 g at 10.2 ms  
Min: -8.5 g at 31.6 ms




Filter Class: CFC\_180  
Max: 32.2 g at 9.5 ms  
Min: -9.0 g at 32.5 ms




# Transportation Research Center Inc.


Left Lateral Thorax with Arm  
SID IIs Serial No. 305 Certification No. 68-1  
Test Date: 1/10/2019




Filter Class: CFC\_600  
Max: 33.2 mm at 16.1 ms  
Min: -0.0 mm at -10.0 ms



Filter Class: CFC\_600  
Max: 26.3 mm at 16.2 ms  
Min: -0.0 mm at -1.0 ms



Filter Class: CFC\_600  
Max: 31.5 mm at 16.6 ms  
Min: -0.0 mm at -4.4 ms



Filter Class: CFC\_600  
Max: 34.6 mm at 17.0 ms  
Min: -0.0 mm at -0.6 ms

Specification Source: CFR49 Part 572 Subpart V  
with Polarity in accordance with J211

01.10.2019 12:36:19 639



## Transportation Research Center Inc.

Left Lateral Thorax without Arm  
SID IIS Serial No. 305 Certification No. 68-1  
Test Date: 1/10/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.7 °C	Yes
Relative Humidity	10 - 70 %	36 %	Yes
Impactor Velocity	4.20 - 4.40 m/s	4.344 m/s	Yes
Impactor Acceleration	(-14) - (-18) g	-16.0 g	Yes
Upper Thorax Rib Displacement	32 - 40 mm	36.0 mm	Yes
Center Thorax Rib Displacement	39 - 45 mm	40.7 mm	Yes
Lower Thorax Rib Displacement	35 - 43 mm	37.2 mm	Yes
Upper Spine Lateral Acceleration	13 - 17 g	15.7 g	Yes
Lower Spine Lateral Acceleration	7 - 11 g	9.9 g	Yes

**Test meets specifications.**

**Condition: Used**

**Comments:**




**Upper Thorax Rib S/N: 2135**

**Middle Thorax Rib S/N: 2136**

**Lower Thorax Rib S/N: 2137**

# Transportation Research Center Inc.

Left Lateral Thorax without Arm  
SID IIs Serial No. 305 Certification No. 68-1  
Test Date: 1/10/2019




Specification Source: CFR49 Part 572 Subpart V  
with Polarity in accordance with J211

01.10.2019 11:27 849




# Transportation Research Center Inc.


Left Lateral Thorax without Arm  
SID IIs Serial No. 305 Certification No. 68-1  
Test Date: 1/10/2019



Filter Class: CFC\_600  
Max: 36.0 mm at 20.6 ms  
Min: -0.0 mm at -8.5 ms



Filter Class: CFC\_600  
Max: 40.7 mm at 21.5 ms  
Min: -0.0 mm at 0.6 ms



Filter Class: CFC\_600  
Max: 37.2 mm at 22.4 ms  
Min: -0.0 mm at -2.6 ms

## Transportation Research Center Inc.

Left Lateral Abdomen  
SID IIs Serial No. 305 Certification No. 68-1  
Test Date: 1/10/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.1 °C	Yes
Relative Humidity	10 - 70 %	39 %	Yes
Impactor Velocity	4.2 - 4.4 m/s	4.28 m/s	Yes
Impactor Acceleration	(-12) - (-16) g	-13.0 g	Yes
Upper Abdominal Rib Displacement	36 - 47 mm	46.6 mm	Yes
Lower Abdominal Rib Displacement	33 - 44 mm	39.7 mm	Yes
Lower Spine Lateral Acceleration	9 - 14.0 g	10.21 g	Yes

**Test meets specifications.**

**Condition: Used**

**Comments:**

**Upper Abdominal Rib S/N: 1997**

**Lower Abdominal Rib S/N: DS1234**




# Transportation Research Center Inc.


Left Lateral Abdomen

SID IIs Serial No. 305 Certification No. 68-1


Test Date: 1/10/2019




Filter Class: CFC\_180  
Max: 0.2 g at 71.2 ms  
Min: -13.0 g at 19.4 ms



Filter Class: CFC\_180  
Max: 10.2 g at 14.0 ms  
Min: -2.0 g at 47.8 ms



Filter Class: CFC\_600  
Max: 46.6 mm at 26.6 ms  
Min: -0.0 mm at -1.9 ms



Filter Class: CFC\_600  
Max: 39.7 mm at 25.8 ms  
Min: -0.0 mm at -6.6 ms

Specification Source: CFR49 Part 572 Subpart V  
with Polarity in accordance with J211

01.10.2019 11:13 684



## Transportation Research Center Inc.

Left Lateral Pelvis  
SID IIs Serial No. 305 Certification No. 68-1  
Test Date: 1/10/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.6 °C	Yes
Relative Humidity	10 - 70 %	39 %	Yes
Pendulum Velocity	6.6 - 6.8 m/s	6.63 m/s	Yes
Impactor Acceleration	(-38.0) - (-47.0) g	-42.54 g	Yes
Peak Pelvis Lateral Acceleration after 6ms	34 - 42 g	38.2 g	Yes
Acetabulum Force	3,600 - 4,300 N	4,043.5 N	Yes

**Test meets specifications.**

**Condition: Used**

**Comments:**

**Pelvis Skin S/N: 884**

**Pelvis Plug Info:**


**Manufacturer: SACO**

**S/N: 12143**


**Cal Date: 20180228**

# Transportation Research Center Inc.


Left Lateral Pelvis  
SID IIs Serial No. 305 Certification No. 68-1  
Test Date: 1/10/2019



Filter Class: CFC\_180  
Max: 0.6 g at -0.9 ms  
Min: -42.5 g at 7.9 ms



Filter Class: CFC\_180  
Max: 50.5 g at 1.4 ms  
Min: -13.6 g at 24.6 ms



Filter Class: CFC\_600  
Max: 4,043.5 N at 7.8 ms  
Min: -34.6 N at 0.1 ms

Specification Source: CFR49 Part 572 Subpart V  
with Polarity in accordance with J211

01.10.2019 12:59:14 480



## Transportation Research Center Inc.

Left Lateral Iliac

SID IIs Serial No. 305 Certification No. 68-1

Test Date: 1/10/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.8 °C	Yes
Relative Humidity	10 - 70 %	39 %	Yes
Pendulum Velocity	4.2 - 4.4 m/s	4.28 m/s	Yes
Impactor Acceleration	(-36) - (-45) g	-37.9 g	Yes
Peak Pelvis Lateral Acceleration	28 - 39 g	28.8 g	Yes
Iliac Force	4,100 - 5,100 N	4,374.6 N	Yes

**Test meets specifications.**

**Condition: Used**

**Comments:**


**Pelvis Skin S/N: 884**

# Transportation Research Center Inc.


Left Lateral Iliac

SID IIs Serial No. 305 Certification No. 68-1


Test Date: 1/10/2019



Filter Class: CFC\_180  
Max: 0.2 g at 38.1 ms  
Min: -37.9 g at 9.8 ms



Filter Class: CFC\_180  
Max: 28.8 g at 8.9 ms  
Min: -2.7 g at 47.8 ms



Filter Class: CFC\_600  
Max: 4,374.6 N at 9.9 ms  
Min: -0.7 N at -7.8 ms

Specification Source: CFR49 Part 572 Subpart V  
with Polarity in accordance with J211

01.10.2019 10:46 689





**Post-Test Calibration Sheets  
Passenger S/N 305**

**Transportation Research Center Inc.**  
**SIDI's Dummy - Level D**  
**External Dimensions**  
**Serial No. 305 Calibration No. 69**

Symbol	Description	Specification	Results	Pass
		mm	mm	
A	Sitting Height	772.0 - 788.0	782	Yes
B	Shoulder Pivot Height	437.0 - 453.0	448	Yes
C	H-Point Height	79.0 - 89.0	86	Yes
D	H-Point from Seat Back	141.0 - 151.0	146	Yes
E	Shoulder Pivot from Backline	97.0 - 107.0	101	Yes
F	Thigh Clearance	119.0 - 135.0	130	Yes
G	Head Breadth	140.0 - 148.0	143	Yes
H	Head Back from Backline	40.0 - 46.0	44	Yes
I	Head Depth	178.0 - 188.0	185	Yes
J	Head Circumference	541.0 - 551.0	543	Yes
K	Buttock to Knee Length	514.0 - 540.0	534	Yes
L	Popliteal Height	343.0 - 369.0	348	Yes
M	Knee Pivot to Floor Height	393.0 - 409.0	396	Yes
N	Buttock Popliteal Length	416.0 - 442.0	434	Yes
O	Chest Depth without Jacket	195.0 - 211.0	197	Yes
P	Foot Length (right)	216.0 - 232.0	222	Yes
P	Foot Length (left)	216.0 - 232.0	220	Yes
Q	Hip Breadth	313.0 - 323.0	320	Yes
R	Arm Length	249.0 - 259.0	252	Yes
S	Knee Joint to seat Back	478.0 - 493.0	482	Yes
V	Shoulder Width (only one arm installed)	341.0 - 357.0	351	Yes
W	Foot Width (right)	78.0 - 94.0	85	Yes
W	Foot Width (left)	78.0 - 94.0	85	Yes
Y	Chest Circumference with Jacket	851.0 - 881.0	877	Yes
Z	Waist Circumference	761.0 - 791.0	780	Yes

## Transportation Research Center Inc.

Left Lateral Head Drop

SID IIS Serial No. 305 Certification No. 69-1

Test Date: 2/22/2019

Test Parameter	Specification	Test Results	Pass
Temperature	18.9 - 25.6 °C	21.4 °C	Yes
Relative Humidity	10 - 70 %	37 %	Yes
Peak Head Resultant Acceleration	115 - 137 g	117.8 g	Yes
Peak Head Longitudinal Acceleration	(-15) - 15 g	1.6 g	Yes
Is Head Resultant Acceleration Curve Unimodal within 15% of Peak?	Yes	Yes	Yes

**Test meets specifications.**

**Condition: Used**

**Comments:**


**Head Skin S/N: 1253**

# Transportation Research Center Inc.

Left Lateral Head Drop

SID IIS Serial No. 305 Certification No. 69-1


Test Date: 2/22/2019



Filter Class: CFC\_1000

Max: 1.6 g at 5.4 ms


Min: -1.0 g at 3.0 ms



Filter Class: CFC\_1000

Max: 92.7 g at 2.8 ms


Min: -1.1 g at 7.0 ms



Filter Class: CFC\_1000

Max: 72.8 g at 2.9 ms

Min: -0.9 g at 9.7 ms



Filter Class: CFC\_1000

Max: 117.8 g at 2.9 ms

Min: 0.0 g at -1.0 ms

Specification Source: CFR49 Part 572 Subpart V  
with Polarity in accordance with J211

02.22.2019 08:44:31 197



## Transportation Research Center Inc.

Left Lateral Neck

SID IIs Serial No. 305 Certification No. 69-2

Test Date: 2/22/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.4 °C	Yes
Relative Humidity	10 - 70 %	37 %	Yes
Pendulum Velocity	(-5.51) - (-5.63) m/s	-5.604 m/s	Yes
Pendulum Integrated Velocity			
Change at 10 ms	2.20 - 2.80 m/s	2.758 m/s	Yes
Change at 15 ms	3.30 - 4.10 m/s	3.967 m/s	Yes
Change at 20 ms	4.40 - 5.40 m/s	5.283 m/s	Yes
Change at 25 ms	5.40 - 6.10 m/s	6.007 m/s	Yes
Change at 25 to 100 ms	5.50 - 6.20 m/s	6.021 m/s	Yes
Maximum Headform Flexion occurring between 50ms and 70ms.			
Peak	(-71) - (-81) deg	-71.2 deg	Yes
Time of Peak	50 - 70 ms	65.6 ms	Yes
Total Neck Occipital Condyles Moment	36 - 44 N·m	40.1 N·m	Yes
Total Neck Occipital Condyles Moment			
Decay Time to 0 N·m	102 - 126 ms	120.3 ms	Yes

**Test meets specifications.**

**Condition:** Used

**Comments:**


**Neck S/N: 180-2001-606**

# Transportation Research Center Inc.

Left Lateral Neck

SID IIs Serial No. 305 Certification No. 69-2


Test Date: 2/22/2019



Filter Class: CFC\_180

Max: 36.9 g at 1.8 ms

Min: -7.1 g at 31.3 ms



Filter Class: CFC\_180

Max: 6.9 m/s at 200.0 ms

Min: 0.0 m/s at 0.0 ms

Specification Source: CFR49 Part 572 Subpart V  
with Polarity in accordance with J211

02.22.2019 09:43:13 720






# Transportation Research Center Inc.


Left Lateral Neck

SID IIs Serial No. 305 Certification No. 69-2


Test Date: 2/22/2019




Filter Class: CFC\_60  
Max: 17.0 ° at 191.4 ms  
Min: -61.3 ° at 81.0 ms



Filter Class: CFC\_60  
Max: 18.0 ° at 184.2 ms  
Min: -48.2 ° at 61.3 ms



Filter Class: CFC\_60  
Max: 16.0 ° at 176.5 ms  
Min: -13.5 ° at 59.0 ms



Filter Class: CFC\_60  
Max: 32.3 ° at 187.5 ms  
Min: -71.2 ° at 65.6 ms

Specification Source: CFR49 Part 572 Subpart V  
with Polarity in accordance with J211

02.22.2019 09:43:14 720




# Transportation Research Center Inc.


Left Lateral Neck

SID IIS Serial No. 305 Certification No. 69-2


Test Date: 2/22/2019




Filter Class: CFC\_1000  
Max: 444.2 N at 46.3 ms  
Min: -149.9 N at 175.7 ms



Filter Class: CFC\_600  
Max: 442.2 N at 46.4 ms  
Min: -148.8 N at 175.7 ms



Filter Class: CFC\_600  
Max: 33.4 Nm at 57.4 ms  
Min: -20.2 Nm at 11.0 ms



Filter Class: Without\_(Consta  
Max: 40.1 N.m at 56.1 ms  
Min: -15.2 N.m at 6.7 ms

Specification Source: CFR49 Part 572 Subpart V  
with Polarity in accordance with J211

02.22.2019 09:43:15 720



## Transportation Research Center Inc.

Left Lateral Shoulder  
SID IIs Serial No. 305 Certification No. 69-1  
Test Date: 2/22/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.5 °C	Yes
Relative Humidity	10 - 70 %	41 %	Yes
Impactor Velocity	4.2 - 4.4 m/s	4.28 m/s	Yes
Impactor Acceleration	(-13) - (-18) g	-15.9 g	Yes
Shoulder Displacement	28 - 37 mm	28.8 mm	Yes
Upper Spine Lateral Acceleration	17 - 22 g	19.1 g	Yes

**Test meets specifications.**

**Condition: Used**

**Comments:**

**Left Arm S/N: 952**


**Shoulder Rib S/N: 180-3355 169**

# Transportation Research Center Inc.


Left Lateral Shoulder

SID IIs Serial No. 305 Certification No. 69-1


Test Date: 2/22/2019



Filter Class: CFC\_180  
Max: 0.1 g at 43.0 ms  
Min: -15.9 g at 13.5 ms



Filter Class: CFC\_600  
Max: 28.8 mm at 17.3 ms  
Min: -0.0 mm at 1.2 ms



Filter Class: CFC\_180  
Max: 19.1 g at 7.8 ms  
Min: -8.7 g at 36.2 ms

Specification Source: CFR49 Part 572 Subpart V  
with Polarity in accordance with J211

02.22.2019 10:53:26 843



## Transportation Research Center Inc.

Left Lateral Thorax with Arm  
SID IIs Serial No. 305 Certification No. 69-3  
Test Date: 2/22/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.5 °C	Yes
Relative Humidity	10 - 70 %	37 %	Yes
Impactor Velocity	6.60 - 6.80 m/s	6.747 m/s	Yes
Impactor Acceleration	(-30) - (-36) g	-32.3 g	Yes
Shoulder Displacement	31 - 40 mm	36.9 mm	Yes
Upper Thorax Rib Displacement	25 - 32 mm	27.5 mm	Yes
Center Thorax Rib Displacement	30 - 36 mm	31.0 mm	Yes
Lower Thorax Rib Displacement	32 - 38 mm	32.6 mm	Yes
Upper Spine Lateral Acceleration	34 - 43 g	38.9 g	Yes
Lower Spine Lateral Acceleration	29 - 37 g	33.0 g	Yes

**Test meets specifications.**

**Condition: Used**

**Comments:**

**Left Arm S/N: 952**


**Upper Thorax Rib S/N: 2135**

**Middle Thorax Rib S/N: 2136**


**Lower Thorax Rib S/N: 2137**

# Transportation Research Center Inc.


Left Lateral Thorax with Arm  
SID IIs Serial No. 305 Certification No. 69-3  
Test Date: 2/22/2019



Filter Class: CFC\_180  
Max: 0.2 g at 41.2 ms  
Min: -32.3 g at 12.6 ms



Filter Class: CFC\_180  
Max: 38.9 g at 10.6 ms  
Min: -10.5 g at 32.9 ms



Filter Class: CFC\_180  
Max: 33.0 g at 9.4 ms  
Min: -8.4 g at 34.3 ms



## Transportation Research Center Inc.

Left Lateral Thorax without Arm  
SID IIS Serial No. 305 Certification No. 69-1  
Test Date: 2/22/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.5 °C	Yes
Relative Humidity	10 - 70 %	41 %	Yes
Impactor Velocity	4.20 - 4.40 m/s	4.275 m/s	Yes
Impactor Acceleration	(-14) - (-18) g	-16.0 g	Yes
Upper Thorax Rib Displacement	32 - 40 mm	35.3 mm	Yes
Center Thorax Rib Displacement	39 - 45 mm	40.2 mm	Yes
Lower Thorax Rib Displacement	35 - 43 mm	37.7 mm	Yes
Upper Spine Lateral Acceleration	13 - 17 g	15.0 g	Yes
Lower Spine Lateral Acceleration	7 - 11 g	9.8 g	Yes

**Test meets specifications.**

**Condition: Used**

**Comments:**


**Upper Thorax Rib S/N: 2135**

**Middle Thorax Rib S/N: 2136**


**Lower Thorax Rib S/N: 2137**

# Transportation Research Center Inc.


Left Lateral Thorax without Arm  
SID IIs Serial No. 305 Certification No. 69-1  
Test Date: 2/22/2019



Filter Class: CFC\_180  
Max: 0.1 g at 94.7 ms  
Min: -16.0 g at 18.7 ms




Filter Class: CFC\_180  
Max: 15.0 g at 15.2 ms  
Min: -6.2 g at 49.0 ms




Filter Class: CFC\_180  
Max: 9.8 g at 14.6 ms  
Min: -4.3 g at 45.8 ms

# Transportation Research Center Inc.


Left Lateral Thorax without Arm  
SID IIs Serial No. 305 Certification No. 69-1  
Test Date: 2/22/2019



Filter Class: CFC\_600  
Max: 35.3 mm at 21.2 ms  
Min: -0.0 mm at -4.8 ms







Filter Class: CFC\_600  
Max: 40.2 mm at 21.8 ms  
Min: -0.0 mm at 1.0 ms



Filter Class: CFC\_600  
Max: 37.7 mm at 22.5 ms  
Min: -0.0 mm at 0.7 ms

# Transportation Research Center Inc.

Left Lateral Thorax with Arm  
SID IIs Serial No. 305 Certification No. 69-3  
Test Date: 2/22/2019



Specification Source: CFR49 Part 572 Subpart V  
with Polarity in accordance with J211

02.22.2019 15:09:48 601



## Transportation Research Center Inc.

Left Lateral Abdomen  
SID IIs Serial No. 305 Certification No. 69-1  
Test Date: 2/22/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.5 °C	Yes
Relative Humidity	10 - 70 %	38 %	Yes
Impactor Velocity	4.2 - 4.4 m/s	4.27 m/s	Yes
Impactor Acceleration	(-12) - (-16) g	-13.3 g	Yes
Upper Abdominal Rib Displacement	36 - 47 mm	43.3 mm	Yes
Lower Abdominal Rib Displacement	33 - 44 mm	40.0 mm	Yes
Lower Spine Lateral Acceleration	9 - 14.0 g	10.30 g	Yes

**Test meets specifications.**

**Condition: Used**

**Comments:**

**Upper Abdominal Rib S/N: 1997**


**Lower Abdominal Rib S/N: DS1234**

# Transportation Research Center Inc.


Left Lateral Abdomen

SID IIS Serial No. 305 Certification No. 69-1


Test Date: 2/22/2019




Filter Class: CFC\_180  
Max: 0.1 g at 71.5 ms  
Min: -13.3 g at 17.8 ms



Filter Class: CFC\_180  
Max: 10.3 g at 13.4 ms  
Min: -1.7 g at 65.5 ms



Filter Class: CFC\_600  
Max: 43.3 mm at 25.7 ms  
Min: -0.0 mm at 1.7 ms



Filter Class: CFC\_600  
Max: 40.0 mm at 25.0 ms  
Min: -0.0 mm at 1.3 ms

Specification Source: CFR49 Part 572 Subpart V  
with Polarity in accordance with J211

02.22.2019 15:27:42 666





## Transportation Research Center Inc.

Left Lateral Pelvis  
SID IIs Serial No. 305 Certification No. 69-2  
Test Date: 2/25/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.3 °C	Yes
Relative Humidity	10 - 70 %	40 %	Yes
Pendulum Velocity	6.6 - 6.8 m/s	6.60 m/s	Yes
Impactor Acceleration	(-38.0) - (-47.0) g	-44.16 g	Yes
Peak Pelvis Lateral Acceleration after 6ms	34 - 42 g	38.1 g	Yes
Acetabulum Force	3,600 - 4,300 N	3,993.4 N	Yes

**Test meets specifications.**

**Condition: Used**

**Comments:**

**Pelvis Skin S/N: 884**

**Pelvis Plug Info:**


**Manufacturer: SACO**

**S/N: 11637**


**Cal Date: 20170327**

# Transportation Research Center Inc.


Left Lateral Pelvis  
SID IIs Serial No. 305 Certification No. 69-2  
Test Date: 2/25/2019



Filter Class: CFC\_180  
Max: 0.6 g at -1.0 ms  
Min: -44.2 g at 8.0 ms



Filter Class: CFC\_180  
Max: 48.6 g at 1.4 ms  
Min: -11.8 g at 22.0 ms



Filter Class: CFC\_600  
Max: 3,993.4 N at 7.7 ms  
Min: -63.3 N at 0.1 ms

Specification Source: CFR49 Part 572 Subpart V  
with Polarity in accordance with J211

02.25.2019 06:57:32 414



## Transportation Research Center Inc.

Left Lateral Iliac

SID IIS Serial No. 305 Certification No. 69-1

Test Date: 2/22/2019

Test Parameter	Specification	Test Results	Pass
Temperature	20.6 - 22.2 °C	21.3 °C	Yes
Relative Humidity	10 - 70 %	37 %	Yes
Pendulum Velocity	4.2 - 4.4 m/s	4.28 m/s	Yes
Impactor Acceleration	(-36) - (-45) g	-38.6 g	Yes
Peak Pelvis Lateral Acceleration	28 - 39 g	29.5 g	Yes
Iliac Force	4,100 - 5,100 N	4,425.5 N	Yes

**Test meets specifications.**

**Condition: Used**

**Comments:**


**Pelvis Skin S/N: 884**

# Transportation Research Center Inc.


Left Lateral Iliac

SID IIs Serial No. 305 Certification No. 69-1


Test Date: 2/22/2019



Filter Class: CFC\_180  
Max: 0.2 g at 47.3 ms  
Min: -38.6 g at 9.0 ms



Filter Class: CFC\_180  
Max: 29.5 g at 8.3 ms  
Min: -3.0 g at 14.6 ms



Filter Class: CFC\_600  
Max: 4,425.5 N at 9.2 ms  
Min: -0.9 N at -8.4 ms

Specification Source: CFR49 Part 572 Subpart V  
with Polarity in accordance with J211

02.22.2019 10:21:34 662



**APPENDIX D**  
**TEST EQUIPMENT AND INSTRUMENTATION CALIBRATION DATA**

**TABLE 1 – Dummy Instrumentation (ES-2re)**

		ES-2re S/N F030			
		Serial Number	Manufacturer	Calibration Date	
Head Accelerometers	X	P87680	Endevco	28-Nov-2018	
	Y	T10352	Endevco	28-Nov-2018	
	Z	P91950	Endevco	28-Nov-2018	
Redundant Head Accelerometers	X	P94566	Endevco	28-Nov-2018	
	Y	P83368	Endevco	28-Nov-2018	
	Z	P94483	Endevco	28-Nov-2018	
Thoracic Rib Displacement Potentiometers	Upper	Y	111	Honeywell	11-Apr-2018
	Middle	Y	174	FTSS	11-Apr-2018
	Lower	Y	173	FTSS	11-Apr-2018
Abdomen Load Cells	Front	Y	1441	Denton	11-Apr-2018
	Middle	Y	1436	Denton	11-Apr-2018
	Rear	Y	1437	Denton	11-Apr-2018
Lower Spine Accelerometers (T12)	X	P89126	Endevco	28-Nov-2018	
	Y	P87139	Endevco	28-Nov-2018	
	Z	P64884	Endevco	28-Nov-2018	
Acetabulum Load Cell	Y	N/A	N/A	N/A	
Pubic Symphysis Load Cell	Y	457-FY	Denton	11-Apr-2018	



**TABLE 2 – Dummy Instrumentation (SID-IIs)**

			SID-IIs S/N 305			
			Serial Number	Manufacturer	Calibration Date	
Head Accelerometers			X	T11432	Endevco	30-Nov-2018
			Y	P93774	Endevco	30-Nov-2018
			Z	P91566	Endevco	30-Nov-2018
Redundant Head Accelerometers			X	P91615	Endevco	30-Nov-2018
			Y	P93762	Endevco	30-Nov-2018
			Z	P93761	Endevco	30-Nov-2018
Displacement Potentiometers	Shoulder		N/A	N/A	N/A	N/A
	Thoracic Rib	Upper	Y	007	Servo	17-Apr-2018
		Middle	Y	037	Servo	17-Apr-2018
		Lower	Y	1161	Servo	17-Apr-2018
	Abdominal Rib	Upper	Y	1295	Servo	17-Apr-2018
		Lower	Y	1136	Servo	17-Apr-2018
Lower Spine Accelerometers (T12)			X	P94545	Endevco	30-Nov-2018
			Y	P94647	Endevco	30-Nov-2018
			Z	P94530	Endevco	30-Nov-2018
Acetabulum Load Cell			Y	DK7483S-FY	FTSS	16-Apr-2018
Iliac Wing Load Cell			Y	287-FY	Denton	16-Apr-2018
Pelvis Plug (struck side)				11859	SACO	23-Jan-2018
Pelvis Plug (non-struck side)				36473	FTSS	23-Jul-2010

**TABLE 3 – Vehicle Instrumentation**

Vehicle Instrumentation			Serial Number	Manufacturer	Calibration Date
1	Vehicle Center of Gravity	X	P94561	Endevco	24-Oct-2018
	Vehicle Center of Gravity	Y	P73220	Endevco	24-Oct-2018
	Vehicle Center of Gravity	Z	P88038	Endevco	24-Oct-2018
2	Right Sill at Front Seat	X	T11825	Endevco	8-Jan-2019
	Right Sill at Front Seat	Y	T11837	Endevco	8-Jan-2019
	Right Sill at Front Seat	Z	T11833	Endevco	8-Jan-2019
3	Right Sill at Rear Seat	X	P97718	Endevco	3-Jan-2019
	Right Sill at Rear Seat	Y	P97724	Endevco	3-Jan-2019
	Right Sill at Rear Seat	Z	P97715	Endevco	3-Jan-2019
4	Left Sill at Front Door	Y	T10650	Endevco	21-Dec-2018
5	Left Sill at Rear Door	Y	P94485	Endevco	21-Dec-2018
6	Left A-Post Lower	Y	T11836	Endevco	8-Jan-2019
7	Left A-Post Middle	Y	T11831	Endevco	8-Jan-2019
8	Left B-Post Lower	Y	T11447	Endevco	3-Jan-2019
9	B-Post Middle	Y	T10349	Endevco	3-Jan-2019
10	Front Seat Track	Y	P97716	Endevco	21-Dec-2018
11	Rear Seat Track or Structure	Y	P73587	Endevco	24-Oct-2018
12	Right Rear Occupant Compartment	Y	T11819	Endevco	21-Jan-2019
13	Engine Block	X	T11840	Endevco	8-Jan-2019
	Engine Block	Y	P56615	Endevco	21-Dec-2018
14	Rear Floorpan Above Axle	X	P88460	Endevco	21-Dec-2018
	Rear Floorpan Above Axle	Y	P87822	Endevco	21-Dec-2018
	Rear Floorpan Above Axle	Z	P94524	Endevco	21-Dec-2018

**TABLE 4 – MDB Instrumentation**

MDB Instrumentation		Serial Number	Manufacturer	Calibration Date
MDB Center of Gravity	X	P76454	Endevco	24-Oct-18
MDB Center of Gravity	Y	P58611	Endevco	24-Oct-18
MDB Center of Gravity	Z	P61295	Endevco	24-Oct-18
Left Frame Rail at Rear Axle Centerline	X	P75115	Endevco	24-Oct-18
Left Frame Rail at Rear Axle Centerline	Y	P94567	Endevco	24-Oct-18