

**NEW CAR ASSESSMENT PROGRAM (NCAP)
DYNAMIC ROLLOVER RESISTANCE TEST**

General Motors, LLC
2019 Chevrolet Silverado 4WD

TEST NUMBER: OCAS-DRI-RR-19-07

Final Report
30 July 2019



Prepared by:

Dynamic Research, Inc
355 Van Ness Ave. #200
Torrance, CA 90501

Prepared for:

National Highway Traffic Safety Administration
Office of Crash Avoidance Standards
1200 New Jersey Avenue S.E.
Washington, DC 20590

The United States Government assumes no liability for the contents of this report or use thereof. If trade or manufacturers' names or products are mentioned, it is only because they are considered essential to the object of the publication and should not be construed as an endorsement. The United States Government does not endorse products or manufacturers.

Dynamic Research, Inc. does not endorse or certify products of manufacturers. The manufacturer's name appears solely to identify the test article. Dynamic Research, Inc. assumes no liability for the report or use thereof. It is responsible for the facts and the accuracy of the data presented herein. This report does not constitute a standard, specification, or regulation.

Report Prepared by:

John Lenkeit, Program Manager

Date: 30 July 2019

1. Report No. OCAS-DRI-RR-19-07	2. Government Accession No.	3. Recipient's Catalog No.	
4. Title and Subtitle NCAP Dynamic Rollover Resistance Maneuver (Fishhook) Test of a 2019 Chevrolet Silverado 4WD Truck		5. Report Date 30 July 2019	6. Performing Organization Code DRI
		8. Performing Organization Report No. DRI- TM-18-75	
7. Author(s) John Lenkeit, Program Manager Peter Broen, Project Engineer		10. Work Unit No. (TRAIS)	
9. Performing Organization Name and Address Dynamic Research, Inc. 355 Van Ness Ave. #200 Torrance, CA 90501		11. Contract or Grant No. DTNH22-14-D-00332	
		13. Type of Report and Period Covered Final Report February 2019 to July 2019	
12. Sponsoring Agency Name and Address National Highway Traffic Safety Administration Office of Crash Avoidance Standards 1200 New Jersey Avenue S.E. Washington, DC 20590		14. Sponsoring Agency Code	
		15. Supplemental Notes	
16. Abstract An NCAP Dynamic Rollover Maneuver (Fishhook) Test was conducted on a 2019 Chevrolet Silverado 4WD at Dynamic Research, Inc. on March 5, 2019. The vehicle did not experience two-wheel lift. The vehicle's steering angle at 0.3 g lateral acceleration at 50 mph was 39.7 degrees.			
17. Key Words NCAP Rollover Resistance Ratings Fishhook Test		18. Distribution Statement Copies of this report are available from: National Highway Traffic Safety Admin. Office of Crash Avoidance Standards 1200 New Jersey Ave., S.E. Washington, DC 20590	
19. Security Classif. (of this report) Unclassified	20. Security Classif. (of this page) Unclassified	21. Number of Pages 55	22. Price

TABLE OF CONTENTS

	Page
I. INTRODUCTION.....	1
II. VEHICLE PREPARATION	2
A. Test Vehicle	2
B. Tires	2
C. Vehicle Loading.....	2
D. Steering Controller	5
E. Real-Time Controller and Data Acquisition	5
F. Equipment Weight.....	6
G. Sensors.....	6
H. Other Vehicle Preparation	7
III. TEST PROCEDURES.....	10
A. Test Procedure Overview.....	10
B. Test Conditions	11
IV. RESULTS.....	14
APPENDIX A Photographs	A-1
APPENDIX B Test Run Log.....	B-1
APPENDIX C Slowly Increasing Steer Test Worksheet.....	C-1
APPENDIX D Time History Plots	D-1

LIST OF FIGURES

	Page
1. Nominal Position of Video Cameras for Fishhook Tests	9
2. DRI-Minter Vehicle Dynamics Area	13

LIST OF TABLES

	Page
1. Test Vehicle Data	3
2. Tire Information	4
3. Vehicle Loading	4
4. Weight of In-Cab Test equipment.....	6
5. Sensor Specifications	8
6. Surface Friction	11
7. Handwheel Angles	11
8. Weather Conditions.....	12

Section I
INTRODUCTION

Beginning with the 2006 fiscal year, the National Highway Traffic Safety Administration (NHTSA) has engaged Dynamic Research, Inc. (DRI) of Torrance, CA to conduct dynamic rollover testing and gather data from that testing as part of NHTSA's New Car Assessment Program (NCAP).

The purpose of the testing reported herein was to determine if a typical 2019 Chevrolet Silverado 4WD would experience tip-up, defined as simultaneous two-wheel lift of two inches or more at an entry speed of 50 mph or less in the Fishhook Procedure developed by NHTSA. This procedure may be found at www.regulations.gov, docket item NHTSA-2006-26555-0136.

The testing reported herein was accomplished under contract DTNH22-14-D-00332. The task order is entitled, "New Car Assessment Program (NCAP) Non-Destructive Vehicle Testing and Data Gathering."

Section II VEHICLE PREPARATION

A. TEST VEHICLE

The test vehicle was new or in as-new condition, meaning the vehicle had been driven no more than 500 miles prior to the start of dynamic rollover testing. It was acquired through a commercial rental/leasing company. Details of the test vehicle are given in Table 1.

B. TIRES

All tires used were new, and of the same make, model, size, and DOT specification of those installed on the vehicle when purchased new. Tire inflation pressures were in accordance with the recommendations indicated on each vehicle's identification placard. To further reduce the possibility of tire debanding, the tires were mounted to the rims without the use of tire mounting lubricant. Tire specifications are listed in Table 2.

C. VEHICLE LOADING

The multi-passenger load, described in the Fishhook Procedure, was used for all tests. The load and positioning of the load in the vehicle are listed in Table 3.

In addition to water dummies, the loading included instrumentation, a steering machine, and outriggers. Test vehicle bumper assemblies were removed for outrigger installation. The reduction in vehicle weight due to the removal of the bumpers was offset by the additional weight of the outriggers and their mounting system. The outrigger system typically outweighs the bumper assemblies.

Table 1. Test Vehicle Data

General Data					
Model year, make, model	2019 Chevrolet Silverado 4WD				
VIN	1GCRYEEDXKZ19xxxx				
Body style	Truck				
Number of doors	4				
Trim level	RST DBL				
Seating positions	Front:	2 nd row	3 rd row	4 th row	5 th row
	2	3	0	0	0
Electronic stability control	Yes				
4-Wheel ABS (Yes/No)	Yes				
Power steering (Yes/No)	Yes				
Major optional equipment	All Star Edition, Convenience Package II, Trailer Brake Controller, Z71 Offroad Package, Engine: 5.3L Ecotec3 V8 with Dynamic Fuel Management				
Odometer at start of testing	9 miles				
Drivetrain					
Engine cylinder arrangement	V-8				
Engine displacement	5.3 L				
Transmission type	Automatic				
Drive arrangement	4WD				
Chassis					
Track width	F: 68 in (1727.2 mm) , R: 68.25 in (1733.6 mm)				
Wheelbase	147.5 in (3746.5 mm)				
Curb weight	5067 lb (2298.4 kg)				
Certification Data from Vehicle's Label					
Vehicle manufactured by	General Motors, LLC				
Date of manufacture	11/18				
GVWR	7000 lb (3175 kg)				
GAWR Front	3800 lb (1724 kg)				
GAWR Rear	3800 lb (1724 kg)				

Table 2. Tire Information

Tire Manufacturer	Goodyear
Tire Model	Wrangler Foritude HT
Tire Size	Front: 265/65R18 Rear: 265/65R18
Load rating	Front: 114 Rear: 114
Speed rating	Front: T Rear: T
Treadwear grade	Front: 680 Rear: 680
Traction grade	Front: A Rear: A
Temperature grade	Front: B Rear: B
Location of "Recommended Tire Pressure" label	Driver's door jamb
Recommended cold tire pressure	Front: 35 psi, (240 kPa) Rear: 35 psi, (240 kPa)
First 8 digits of DOT code	Front: M6C8 JK1R Rear: M6C8 JK1R

Table 3. Vehicle Loading

Water dummy and other loading	3 water dummies in second row
Water dummy weight	175 lb (79.4 kg)
Fuel level	Full
Weight as Tested	
Left front	1743 lb (790.6 kg)
Right front	1726 lb (782.9 kg)
Left rear	1310 lb (594.2 kg)
Right rear	1246 lb (565.2 kg)

D. STEERING CONTROLLER

Precise controlled steering is accomplished using a steering machine designed and constructed by DRI. DRI has used its Automated Vehicle Controller (AVC) steering machine for many vehicle tests including FMVSS 126 tests. It can provide up to 65 ft-lb torque and rates over 1300 deg/sec. The integrated angle encoder has an unlimited range with a resolution of 0.045 degrees and an accuracy of ± 0.045 degrees. The steering motor is controlled by a MicroAutoBox II from dSPACE, which also acts as the data acquisition system.

E. REAL-TIME CONTROLLER AND DATA ACQUISITION

Data acquisition is achieved using a MicroAutoBox II from dSPACE, which also serves as the real-time system for the steering controller. Data from the Oxford IMU, including Longitudinal, Lateral, and Vertical Acceleration, Roll, Yaw, and Pitch Rate, Forward and Lateral Velocity, Roll and Pitch Angle, are sent over Ethernet to the Micro AutoBox. The Oxford IMUs are calibrated per the manufacturer's recommended schedule (Table 5). The MicroAutoBox II specifications are:

Model: D-Space Micro-Autobox II 1401/1513
Base Board SN 549068
I/O Board SN 588523

Two video cameras were used to record the Fishhook runs. They were positioned nominally as shown in Figure 1. The recorded videotapes were reviewed after the Fishhook runs to check for any two-wheel lift. If any two-wheel lift was observed, eight infrared distance-measuring sensors for measurement of wheel lift (two sensors at each wheel) were then mounted for use in subsequent confirmation Fishhook tests.

F. EQUIPMENT WEIGHT

Table 4 lists the equipment and associated weights outlined in the NHTSA Laboratory Test Procedure for Dynamic Rollover and the equipment at DRI used for this specific test program. The equipment used at DRI for this test program differs slightly from the equipment that was previously used by NHTSA for rollover testing. Because DRI's equipment is lighter than NHTSA's equipment, DRI uses ballast to maintain a consistent weight and weight distribution in the vehicle.

Table 4. Weight of In-Cab Test Equipment

Equipment	Location	Equipment Weight (lb)	
		NHTSA*	DRI
Data Acquisition System	Front passenger seat	58	
Steering Machine	Handwheel	31	31
Steering Machine Electronics Box	Passenger row foot well behind the front passenger seat. If vehicle does not have a rear passenger row foot well, the Electronics Box should be placed in the front passenger seat foot well.	39	
MABX, and laptop	Front passenger seat		21
Motor control and power supply	Front passenger footwell		26
Ballast	Front passenger footwell		50
Total		128	128

* Table A.1 from US DOT NHTSA - Laboratory Test Procedure for Dynamic Rollover - The Fishhook Maneuver Test Procedure - New Car Assessment Program (NCAP) - March 2013

G. SENSORS

A list of the sensors is given in Table 5.

H. OTHER VEHICLE PREPARATION

In addition to installation and preparation discussed above, the test vehicle was prepared as follows:

- Front and rear bumpers were removed
- Outrigger mounts were installed in the bumper locations and titanium outriggers were fastened to these mounts
- Airbags were removed or otherwise disabled

Photographs of the vehicle tested are given in Appendix A.

Table 5. Sensors

Measured Variable	Sensor	Range	Resolution	Accuracy	Specifics	Serial Number	Calibration
Vehicle Tire Pressure	Tire Pressure Gauge	0-100 psi 0-690 kPa	0.01 psi 6.89 kPa	< 1% error between 20 and 100 psi	Omega DPG8001	17042707002	By: DRI Date: 6/21/2018 Due: 6/21/2019
Vehicle Total, Wheel, and Axle Load	Platform Scales (Minter)	1200 lb/platform 5338 N/platform	1 lb 4.4 N	0.5% of applied load	Intercomp SWI	1110M206352	By: DRI Date: 1/3/2019 Due: 1/3/2020
	Platform Scales (Torrance)	1500 lb/platform 6672 N/platform	1 lb 4.4 N	0.5% of applied load	Intercomp SW I	24032361	By: DRI Date: 12/11/2018 Due: 12/11/2019
Handwheel Angle	Steering Angle Encoder (Automated Steering Controller)	±800 deg	0.045 deg	±0.045 deg	DRI Automatic Vehicle Controller using D-Space Micro- Autobox II	NA	Verified by DRI at installation ¹
Longitudinal, Lateral, and Vertical Acceleration Roll, Yaw, and Pitch Rate, Forward and Lateral Velocity, Roll and Pitch Angle	Multi-Axis Inertial Sensing System	Accels ± 5 g, Angular Rate ±300 deg/s, Angle >45 deg, Velocity >200 km/h	Accels .001 g, Angular Rate 0.01 deg/s, Angle 0.05 deg, Velocity 0.1 km/h	Accels .001g, Angular Rate 0.01 deg/s, Angle 0.05 deg, Velocity 0.1 km/h	Oxford xNav 550	015360	By: Oxford Technical Solutions Date: 6/21/2017 Due: 6/21/2019

1 . The steering encoder is checked prior to beginning tests to verify that there are no faults. The steering controller is installed in the vehicle and the steering wheel is turned through two complete revolutions while recording data. The data are then reviewed for any dropouts or other nonlinearities that would indicate dust intrusion or faulty sectors.




Figure 1. Nominal Position of Video Cameras for Fishhook Tests

Section III TEST PROCEDURES

This section includes a general overview of the test procedures and details of the particular test.

A. TEST PROCEDURE OVERVIEW

This test was conducted in accordance with NHTSA's NCAP Rollover Resistance Test Procedure (Fishhook) as described in the Federal Register (68 FR 59250). Detailed descriptions of the test procedure, pass/fail criteria, and data acquisition specifications may be found at docket NHTSA-2001-9663.

There are two major components of the test procedure, the Slowly Increasing Steer (SIS) pre-test and the Fishhook test.

The Slowly Increasing Steer (SIS) maneuver was used to characterize the steady state lateral dynamics of each vehicle, and is based on the "Constant Speed, Variable Steer" test defined in SAE J266. The maneuver is used to determine the handwheel angle that produces a lateral acceleration of 0.3 g at 50 mph. This handwheel angle is then used to determine the magnitude of steering to be used for the NHTSA Fishhook maneuver.

SIS tests were performed at a constant speed of 50 mph. Handwheel angle was input at a rate of 13.5 deg/sec, from 0 to an angle that provided at least 0.55 g. Three tests were conducted in each direction, and the data for the six runs were averaged to obtain the handwheel angle that produced 0.3 g at 50 mph.

The Fishhook test is a programmed steering maneuver that is implemented via the steering controller. The vehicle was initially steered in one direction and then the steering was reversed. The timing, magnitude, and rate of the steering were prescribed by the Fishhook Procedure.

To begin the maneuver, the vehicle was driven in a straight line at a speed slightly greater than the desired entrance speed. The driver then released the throttle. When the vehicle was at the target speed, the steering controller automatically initiated the steering maneuver. Following completion of the steering reversal the handwheel position was maintained for three seconds, and then returned to zero angle in 1 second.

The tests were conducted in both left-right and right-left directions. The “Default” test series used a handwheel angle equal to 6.5 times the handwheel angle that produced 0.3 g at 50 mph in the SIS tests, and initial vehicle speeds beginning at 35 mph and concluding up to 50 mph (if no two-wheel lift occurs). Supplemental tests were also done, as specified in the Fishhook Procedure.

B. TEST CONDITIONS

1. Test Surface

The tests were conducted on the Vehicle Dynamics Area at DRI’s Minter Field facility, located near Bakersfield, California, on 3/5/2019. The VDA has a smooth, flat (slope less than 0.5% throughout) asphaltic concrete surface. Its dimensions are as shown in Figure 2. It was built in the spring of 2005.

VDA surface friction measurements were accomplished using the DRI Mobile Tire Tester. Three runs were done, one at each of three previously determined locations. Each run provided for a minimum of 3 seconds of tire friction at constant normal load, slip angle, and speed in a free rolling condition. The test was accomplished using an ASTM E1136 tire with an inflation pressure of 35 (± 0.5) psi at a test speed of 40 (± 0.5) mph. The net slip angle of the test tire for each test run was 7.5 deg. The test tire was no older than 6 months from the date of manufacture. The surface friction measurement results are shown in Table 6.

Table 6. Surface Friction

Date of surface friction measurements	3/5/2019
Average normalized lateral force	0.821

2. Fishhook Handwheel Angles

The 0.3 g handwheel angle obtained from the SIS tests and the handwheel angles used in the Fishhook tests are shown in Table 7.

Table 7. Handwheel Angles

0.3 g handwheel angle (from SIS tests at 50 mph)	39.7°
5.5 scalar handwheel angle for Fishhook Test	218°
6.5 scalar handwheel angle for Fishhook Test	258°

3. Weather Conditions

The weather conditions, recorded at the end of testing, are shown in Table 8.

Table 8. Weather Conditions

Ambient temperature	54° F (12.2° C)
Wind Speed	5 mph (2.2 m/s)
Wind Direction	140




Figure 2. DRI-Minter Vehicle Dynamics Area

Section IV RESULTS


The test run log is given in Appendix B. The Slowly Increasing Steer Test Worksheet is given in Appendix C. Appendix D contains time history plots for the 50 mph runs and any runs which resulted in two-wheel lift. For the 2019 Chevrolet Silverado 4WD, there was no two-wheel lift at any test condition.

APPENDIX A

Photographs

LIST OF FIGURES

	Page
A1. Window Sticker.....	A-3
A2. Front View, Test Vehicle as Delivered	A-4
A3. Rear View, Test Vehicle as Delivered	A-5
A4. Front View, Test Vehicle in Test Condition	A-6
A5. Rear View, Test Vehicle in Test Condition	A-7
A6. Certification Label.....	A-8
A7. Tire Placard	A-9
A8. Instrumentation in Test Vehicle	A-10
A9. Steering Controller and Computer	A-11
A10. Ballast Condition.....	A-12


CHEVROLET

2019 SILVERADO 4WD RST DBL

EXTERIOR: SHADOW GRAY METALLIC
INTERIOR: JET BLACK

ENGINE, 5.3L ECOTEC3 V8 WITH TRANSMISSION, 8-SPEED AUTOMATIC

Visit us at www.chevy.com

STANDARD EQUIPMENT

ITEMS FEATURED BELOW ARE INCLUDED AT NO EXTRA CHARGE IN THE STANDARD VEHICLE PRICE SHOWN

- 3 YR/36,000 MILES BUMPER-TO-BUMPER WARRANTY
- 5 YR/60,000 MILES POWERTRAIN LIMITED WARRANTY
- ROADSIDE ASSISTANCE
- COURTESY TRANSPORTATION
- FIRST MAINTENANCE VISIT
- OIL CHANGE AND TIRE ROTATION
- MULTI-POINT VEHICLE INSPECTION
- SEE CHEVY.COM OR DEALER FOR TERMS, DETAILS & LIMITS

MECHANICAL

- CAPLESS FUEL FILL
- SINGLE-SPD. TRANSFER CASE

SAFETY & SECURITY

- REAR VISION CAMERA
- TEEN DRIVER MODE
- STABILITRAK W/ TRAILER SWAY CONTROL & HILL START ASSIST
- ONSTAR (R) SERVICES CAPABLE (SUBJECT TO TERMS)

SEE ONSTAR.COM

EXTERIOR

- TAILGATE WITH LIFT ASSIST, POWER LOCK, AND RELEASE
- 12 FIXED DURABED TIE DOWNS W/ EACH CORNER RATED AT 500LBS
- LED DURABED LIGHTING
- CORNERS 1EP REAR BUMPER
- FRONT BLACK BOWTIE
- BLACK FRONT RECOVERY HOOKS
- POWER ADJUSTABLE HEATED OUTSIDE MIRRORS
- LED REFLECTOR HEAD LAMPS
- LED FRONT FOG LAMPS
- LED DAYTIME RUNNING LAMPS
- ALL SEASON TIRES

INTERIOR

- 40/20/40 SPLIT BENCH FRONT SEATS W/ ARMREST STORAGE
- ADJ. LUMBAR & UNDERSAT STORAGE
- FRONT DRIVER AND PASSENGER 4-WAY SEAT ADJUSTER
- REAR SEAT REMINDER

OPTIONS & PRICING

- REMOTE START
- KEYLESS OPEN AND START
- POWER WINDOWS, EXPRESS UP & DOWN DRIVER, EXPRESS DOWN FRONT PASSENGER & REAR
- REAR WINDOW DEFOGGER
- REAR HVAC VENTS
- SINGLE ZONE CLIMATE CONTROL
- FRONT & REAR 12V AUX POWER OUTLET
- STEERING WHEEL AUDIO CONTROLS
- CHEVROLET INFOTAINMENT 3 8" DIAG COLOR TOUCHSCREEN
- ADDITIONAL FEATURES FOR COMPATIBLE PHONES INCLUDE: BLUETOOTH AUDIO STREAMING VOICE COMMAND PASSTHROUGH TO PHONE, ANDROID AUTO & APPLE CARPLAY CAPABLE
- 4G LTE WI-FI (R) HOTSPOT CAPABLE (SUBJECT TO TERMS SEE ONSTAR.COM)

MANUFACTURER'S SUGGESTED RETAIL PRICE

STANDARD VEHICLE PRICE \$42,100.00	
(OPTIONS INSTALLED BY THE MANUFACTURER (MAY REPLACE STANDARD EQUIPMENT SHOWN))	
ALL STAR EDITION	2,445.00
SEATS, FRONT BUCKET WITH CENTER CONSOLE	
CENTER CONSOLE, FLOOR	
DUAL-ZONE CLIMATE CONTROL	
SEAT ADJUSTER, DRIVER 10-WAY POWER INCLUDING LUMBAR	
SEATING, HEATED DRIVER AND FRONT PASSENGER	
STEERING WHEEL, HEATED	
STEERING WHEEL, LEATHER-WRAPPED	
STEERING COLUMN, MANUAL TILT AND TELESCOPING	
2ND ROW USB PORTS, (2) CHARGE-ONLY	
DIFFERENTIAL, AUTO LOCKING REAR	
TRAILERING PACKAGE	
TRAILER HIT CH	

<ul style="list-style-type: none"> - 7 PIN AND 4 PIN CONNECTORS - HITCH GUIDANCE CONVENIENCE PACKAGE II • UNIVERSAL HOME REMOTE • POWER SLIDING REAR WINDOW WITH REAR DEFOGGER • 120V L.P. POWER OUTLET • 120V DURABED POWER OUTLET • CHEVROLET INFOTAINMENT 3 PLUS 8" DIAG HD COLOR TOUCHSCREEN AND VOICE RECOGNITION • 2 USB PORTS, 1 SD CARD READER • SIRIUSXM ALL ACCESS + SERVICE SUBSCRIPTION SOLD SEPARATELY BY SIRIUSXM AFTER 3 MTHS • HD RADIO • HD REAR VISION CAMERA • BOSE PREMIUM SOUND SYSTEM ENGINE, 5.3L ECOTEC3 V8 WITH DYNAMIC FUEL MANAGEMENT Z71 OFF-ROAD PACKAGE • SUSPENSION, OFF-ROAD (INCLUDES SHOCKS) • HILL DESCENT CONTROL • SKID PLATES 	<p>1,420.00</p> <p>850.00</p>
--	-------------------------------

<ul style="list-style-type: none"> • AIR CLEANER, HIGH-CAPACITY • TRANSFER CASE TWO-SPEED ELECTRONIC • Z71 BADGE • EXHAUST, DUAL WITH POLISHED OUTLETS • 18" BRIGHT SILVER PAINTED ALUMINUM WHEEL • ALL TERRAIN TIRES TRAILER BRAKE CONTROLLER (GVWR, 7,000 LBS. (3,175 KG)) REAR AXLE 3.23 RATIO 18" BRIGHT SILVER PAINTED ALUMINUM WHEELS 	<p>275.00 INC.</p> <p>INC.</p> <p>INC.</p>
--	--

<p>TOTAL OPTIONS \$6,385.00</p> <p>TOTAL VEHICLE & OPTIONS \$48,485.00</p> <p>DESTINATION CHARGE 1,495.00</p> <p>TOTAL BEFORE SAVINGS \$49,980.00</p> <p>ALL-STAR EDITION DISCOUNT -500.00</p>	<p>TOTAL VEHICLE PRICE* \$49,480.00</p>
--	--

EPA DOT Fuel Economy and Environment

Gasoline Vehicle

Fuel Economy

18 MPG combined city/hwy

16 city

22 highway

5.6 gallons per 100 miles

You spend \$3,500 more in fuel costs over 5 years compared to the average new vehicle.

GOVERNMENT 5-STAR SAFETY RATINGS

This vehicle has not been rated by the government for overall vehicle score, frontal crash, side crash or rollover risk.

Source: National Highway Traffic Safety Administration (NHTSA) www.safercar.gov or 1-888-327-4236

Annual fuel cost \$2,100

Fuel Economy & Greenhouse Gas Rating (tailpipe only)

3

Smog Rating (tailpipe only)

5

This vehicle emits 491 grams CO₂ per mile. The best emits 0 grams per mile (tailpipe only). Producing and distributing fuel also create emissions; learn more at fuelconomy.gov.

Actual results will vary for many reasons, including driving conditions and how you drive and maintain your vehicle. The average new vehicle gets 24 mpg and costs \$7,060 to fuel over 5 years. Cost estimates are based on 15,000 miles per year at \$2.95 per gallon. MPG is miles per gasoline gallon equivalent. Vehicle emissions are a significant cause of climate change and smog.

fuelconomy.gov

PARTS CONTENT INFORMATION

FOR VEHICLES IN THIS CARLINE: U.S./CANADIAN PARTS CONTENT: 42% MAJOR SOURCES OF FOREIGN PARTS CONTENT: MEXICO 46%

NOTE: PARTS CONTENT DOES NOT INCLUDE FINAL ASSEMBLY, DISTRIBUTION, OR OTHER NON-PARTS COSTS.

FOR THIS VEHICLE: FINAL ASSEMBLY POINT: ROANOKE, IN U.S.A. COUNTRY OF ORIGIN: ENGINE: UNITED STATES TRANSMISSION: UNITED STATES

© 2019 General Motors LLC (GM,LLC, PRICED, 2019) - 010500019

Equipped with the safety and security of OnStar®

Visit onstar.com for details.

www.onstar.com

WARNING

Cancer and Reproductive Harm

www.P65Warnings.ca.gov/passenger-vehicle

SEE OWNER'S MANUAL

ORDER NO. SALES CODE E

SALES MODEL CODE CK19733

DEALER NO 20198

FINAL ASSEMBLY

ROANOKE, IN U.S.A.

VIN 1GCRYEEDXKZ19

DEALER TO WHICH DELIVERED

LM

1FA3696151

Figure A1. Window Sticker



Figure A2. Front View, Test Vehicle as Delivered



Figure A3. Rear View, Test Vehicle as Delivered



Figure A4. Front View, Test Vehicle in Test Condition



Figure A5. Rear View, Test Vehicle in Test Condition




Figure A6. Certification Label



Figure A7. Tire Placard



Figure A8. Instrumentation in Test Vehicle




Figure A9. Steering Controller and Computer



Figure A10. Ballast Condition

APPENDIX B

Test Run Log

Vehicle: **2019 Chevrolet Silverado
4WD**

Driver: **Jonathan Robel**

Test Date: **3/5/2019**

Run Number	Test Type	Speed (mph)	Handwheel Angle (deg)	Dir. of First Steer	2 Wheel Lift	Notes
1	Tire Warm-Up	35	60	Right		
2	"	"	70	"		
3	"	"	"	"		
4	"	"	"	"		
5	2x SWA last cycle	"	"	"		
6	Static	0	0			
7	Steady State	50	0			
8	Slowly Increasing Steer	50	60	Left		
9	"	"	"	Left		
10	"	"	"	Left		
11	"	"	"	Right		
12	"	"	"	Right		
13	"	"	"	Right		
14	Fishhook 6.5 Scalar	35	258	Left	No	
15	"	40	"	"	"	
16	"	45	"	"	"	
17	"	47.5	"	"	"	
18	"	50	"	"	"	
19	Fishhook 5.5 Scalar	45	218	Left	No	
20	"	47.5	"	"	"	
21	"	50	"	"	"	

Vehicle: **2019 Chevrolet Silverado
4WD**

Driver: **Jonathan Robel**

Test Date: **3/5/2019**

Run Number	Test Type	Speed (mph)	Handwheel Angle (deg)	Dir. of First Steer	2 Wheel Lift	Notes
22	Fishhook 6.5 Scalar	35	258	Right	No	
23	"	40	"	"	"	
24	"	45	"	"	"	
25	"	47.5	"	"	"	
26	"	50	"	"	"	
27	Fishhook 5.5 Scalar	45	218	Right	No	
28	"	47.5	"	"	"	
29	"	50	"	"	"	

APPENDIX C

Slowly Increasing Steer Test Worksheet

Vehicle: **2019 Chevrolet Silverado
4WD**

Driver: **Jonathan Robel**

Test Date: **3/5/2019**

Run Number	Test Type	Speed (mph)	Handwheel Angle (deg)	Dir. of First Steer	2 Wheel Lift	Notes
1	Tire Warm-Up	35	60	Right		
2	"	"	70	"		
3	"	"	"	"		
4	"	"	"	"		
5	2x SWA last cycle	"	"	"		
6	Static	0	0			
7	Steady State	50	0			
8	Slowly Increasing Steer	50	60	Left		
9	"	"	"	Left		
10	"	"	"	Left		
11	"	"	"	Right		
12	"	"	"	Right		
13	"	"	"	Right		
14	Fishhook 6.5 Scalar	35	258	Left	No	
15	"	40	"	"	"	
16	"	45	"	"	"	
17	"	47.5	"	"	"	
18	"	50	"	"	"	
19	Fishhook 5.5 Scalar	45	218	Left	No	
20	"	47.5	"	"	"	
21	"	50	"	"	"	

Vehicle: **2019 Chevrolet Silverado
4WD**

Driver: **Jonathan Robel**

Test Date: **3/5/2019**

Run Number	Test Type	Speed (mph)	Handwheel Angle (deg)	Dir. of First Steer	2 Wheel Lift	Notes
22	Fishhook 6.5 Scalar	35	258	Right	No	
23	"	40	"	"	"	
24	"	45	"	"	"	
25	"	47.5	"	"	"	
26	"	50	"	"	"	
27	Fishhook 5.5 Scalar	45	218	Right	No	
28	"	47.5	"	"	"	
29	"	50	"	"	"	

APPENDIX D

Time History Plots

LIST OF FIGURES

	Page
D1. Vehicle Speed, Handwheel Angle, and Roll Angle Time History Plots for Default Test Series, L-R, 50 mph	D-3
D2. Steering Machine Operation Time History Plots for Default Test Series, L-R, 50 mph.....	D-4
D3. Yaw Rate, Roll Rate, and Lateral Acceleration Time History Plots for Default Test Series, L-R, 50 mph	D-5
D4. Pitch Rate and Longitudinal Acceleration Time History Plots for Default Test Series, L-R, 50 mph	D-6
D5. Vehicle Speed, Handwheel Angle, and Roll Angle Time History Plots for Default Test Series, R-L, 50 mph	D-7
D6. Steering Machine Operation Time History Plots for Default Test Series, R-L, 50 mph	D-8
D7. Yaw Rate, Roll Rate, and Lateral Acceleration Time History Plots for Default Test Series, R-L, 50 mph	D-9
D8. Pitch Rate and Longitudinal Acceleration Time History Plots for Default Test Series, R-L, 50 mph	D-10
D9. Vehicle Speed, Handwheel Angle, and Roll Angle Time History Plots for Supplemental 2 Test Series, L-R, 50 mph.....	D-11
D10. Steering Machine Operation Time History Plots for Supplemental 2 Test Series, L-R, 50 mph.....	D-12
D11. Yaw Rate, Roll Rate, and Lateral Acceleration Time History Plots for Supplemental 2 Test Series, L-R, 50 mph.....	D-13
D12. Pitch Rate and Longitudinal Acceleration Time History Plots for Supplemental 2 Test Series, L-R, 50 mph.....	D-14
D13. Vehicle Speed, Handwheel Angle, and Roll Angle Time History Plots for Supplemental 2 Test Series, R-L, 50 mph.....	D-15
D14. Steering Machine Operation Time History Plots for Supplemental 2 Test Series, R-L, 50 mph.....	D-16
D15. Yaw Rate, Roll Rate, and Lateral Acceleration Time History Plots for Supplemental 2 Test Series, R-L, 50 mph.....	D-17
D16. Pitch Rate and Longitudinal Acceleration Time History Plots for Supplemental 2 Test Series, R-L, 50 mph.....	D-18




Figure D1. Vehicle Speed, Handwheel Angle, and Roll Angle Time History Plots for Default Test Series, L-R, 50 mph




Figure D2. Steering Machine Operation Time History Plots for Default Test Series, L-R, 50 mph




Figure D3. Yaw Rate, Roll Rate, and Lateral Acceleration Time History Plots For Default Test Series, L-R, 50 mph




Figure D4. Pitch Rate and Longitudinal Acceleration Time History Plots for Default Test Series, L-R, 50 mph




Figure D5. Vehicle Speed, Handwheel Angle, and Roll Angle Time History Plots for Default Test Series, R-L, 50 mph




Figure D6. Steering Machine Operation Time History Plots for Default Test Series, R-L, 50 mph




Figure D7. Yaw Rate, Roll Rate, and Lateral Acceleration Time History Plots for Default Test Series, R-L, 50 mph




Figure D8. Pitch Rate and Longitudinal Acceleration Time History Plots or Default Test Series, R-L, 50 mph




Figure D9. Vehicle Speed, Handwheel Angle, and Roll Angle Time History Plots for Supplemental 2 Test Series, L-R, 50 mph




Figure D10. Steering Machine Operation Time History Plots for Supplemental 2 Test Series, L-R, 50 mph




Figure D11. Yaw Rate, Roll Rate, and Lateral Acceleration Time History Plots for Supplemental 2 Test Series, L-R, 50 mph




Figure D12. Pitch Rate and Longitudinal Acceleration Time History Plots for Supplemental 2 Test Series, L-R, 50 mph




Figure D13. Vehicle Speed, Handwheel Angle, and Roll Angle Time History Plots for Supplemental 2 Test Series, R-L, 50 mph




Figure D14. Steering Machine Operation Time History Plots for Supplemental 2 Test Series, R-L, 50 mph




Figure D15. Yaw Rate, Roll Rate, and Lateral Acceleration Time History Plots for Supplemental 2 Test Series, R-L, 50 mph




Figure D16. Pitch Rate and Longitudinal Acceleration Time History Plots for Supplemental 2 Test Series, R-L, 50 mph