

**REPORT NUMBER: NCAP305I-MGA-2018-005**

**NEW CAR ASSESSMENT PROGRAM (NCAP)  
FMVSS No. 305 Indicant Test**

**MITSUBISHI MOTORS CORPORATION  
2018 Mitsubishi Outlander PHEV SEL 5-Door SUV  
NHTSA NUMBER: O20185602**

**MGA RESEARCH CORPORATION  
5000 Warren Road  
Burlington, WI 53105**



**Test Date: December 17, 2018**

**Report Date: February 7, 2019**

**FINAL REPORT**

**U.S. DEPARTMENT OF TRANSPORTATION  
National Highway Traffic Safety Administration  
Office of Crashworthiness Standards  
Mail Code: NRM-110  
1200 New Jersey Ave, SE  
Room W43-410  
Washington, DC 20590**

This publication is distributed by the U.S. Department of Transportation, National Highway Traffic Safety Administration, in the interest of information exchange. The opinions, findings and conclusions expressed in this publication are those of the author(s) and not necessarily those of the Department of Transportation or the National Highway Traffic Safety Administration. The United States Government assumes no liability for its contents or use thereof.

If trade or manufacturers' names or products are mentioned it is only because they are considered essential to the object of the publication and should not be construed as an endorsement.

Prepared by:   
Ben Fischer, Project Engineer

Approved by:   
Joe Fleck, Project Engineer

Approval Date: February 7, 2019

FINAL REPORT ACCEPTANCE BY OVSC:

\_\_\_\_\_  
Division Chief, New Car Assessment Program  
NHTSA, Office of Crashworthiness Standards

Date: \_\_\_\_\_

\_\_\_\_\_  
COTR, New Car Assessment Program  
NHTSA, Office of Crashworthiness Standards

Date: \_\_\_\_\_

### Technical Report Documentation Page

<b>1. Report No.</b> NCAP305I-MGA-2018-005		<b>2. Government Accession No.</b>		<b>3. Recipient's Catalog No.</b>	
<b>4. Title and Subtitle</b> Final Report of FMVSS 305 Compliance Testing of 2018 Mitsubishi Outlander PHEV SEL 5-Door SUV, NHTSA No.: O20185602		<b>5. Report Date</b> February 7, 2019		<b>6. Performing Organization Code</b> MGA	
		<b>8. Performing Organization Report No.</b> NCAP305I-MGA-2018-005			
<b>7. Author(s)</b> Ben Fischer, Project Engineer		<b>10. Work Unit No.</b>			
<b>9. Performing Organization Name and Address</b> MGA Research Corporation 5000 Warren Road Burlington, WI 53105					
<b>12. Sponsoring Agency Name and Address</b> U.S. Department of Transportation National Highway Traffic Safety Administration Office of Crashworthiness Standards (NRM-110) 1200 New Jersey Ave, SE, Room W43-410 Washington, D.C. 20590		<b>11. Contract or Grant No.</b> DTNH22-13-D-00311L			
		<b>13. Type of Report and Period Covered</b> Final Test Report December 17, 2018 to February 7, 2019			
<b>15. Supplementary Notes</b>		<b>14. Sponsoring Agency Code</b> NRM-110			
		<b>16. Abstract</b>  An FMVSS No. 305 Indicant test, in conjunction with an NCAP side moving deformable barrier (MDB) impact test was conducted on the subject 2018 Mitsubishi Outlander PHEV SEL 5-Door SUV in accordance with the specifications of the applicable Office of Crashworthiness Standards Test Procedures for the generation of consumer information for the New Car Assessment Program (NCAP). No test failures were reported.			
<b>17. Key Words</b> New Car Assessment Program (NCAP) FMVSS 305 Indicant		<b>18. Distribution Statement</b> Copies of this report are available from: National Highway Traffic Safety Administration Technical Information Services Division, NPO-411 1200 New Jersey Ave, SE Washington, DC 20590 Email: <a href="mailto:tis@nhtsa.dot.gov">tis@nhtsa.dot.gov</a> FAX: 202-493-2833			
<b>19. Security Classification of Report</b> Unclassified	<b>20. Security Classification of Page</b> Unclassified	<b>21. No. of Pages</b> 42	<b>22. Price</b>		

## TABLE OF CONTENTS

<u>Section</u>		<u>Page No.</u>
1	Purpose of Test	1
2	Summary of Test Results	2
3	Data Sheets	3
<u>Data Sheet</u>		<u>Page No.</u>
1	Test Vehicle Specifications	4
2	Pre-Impact Data	6
3	Pre-Impact Electric Isolation Measurements and Calculations	7
4	Post-Impact Data	9
5	Static Rollover Test Data	11
<u>Appendix</u>		
A	Photographs	A-1

## **SECTION 1 PURPOSE OF TEST**

An FMVSS No. 305 Indicant test, in conjunction with an NCAP side moving deformable barrier (MDB) impact test was conducted on the subject 2018 Mitsubishi Outlander PHEV SEL 5-Door SUV.

The Indicant test was conducted in accordance with the Office of Crashworthiness Standards Laboratory Test Procedure, dated January 31, 2012 to determine compliance to the requirements of Federal Motor Vehicle Safety Standard (FMVSS) No. 305, "Electric-Powered Vehicles: Electrolyte Spillage and Electrical Shock Protection" for the purpose of providing consumer information.

This FMVSS No. 305 Indicant test is part of the MY 2018 New Car Assessment Program Test Program, sponsored by the National Highway Traffic Safety Administration (NHTSA), under contract DTNH22-13-D-00311L.

## **SECTION 2 SUMMARY OF TEST RESULTS**

A NCAP side moving deformable barrier (MDB) impact test was performed by MGA Research Corporation on a 2018 Mitsubishi Outlander PHEV SEL 5-Door SUV on December 17, 2018. Electrical isolation measurements were taken immediately post-impact and observations were made related to electrolyte spillage and battery retention. A static rollover was subsequently performed on the subject vehicle and electrical isolation measurements were taken at each stage of the rollover.

Based on the test results, the 2018 Mitsubishi Outlander PHEV SEL 5-Door SUV appears to meet the requirements for electrolyte spillage, electrical isolation, and battery retention during FMVSS No. 305 Indicant testing.

Data sheets, along with pre-test and post-test photographs of the test vehicle, are included in this report to document the test.

## **TEST NOTES**

None

MGA does not endorse or certify products. The manufacturer's name appears solely for identification purposes.

**SECTION 3**  
**DATA SHEETS**

**DATA SHEET 1**  
**TEST VEHICLE SPECIFICATIONS**

Test Vehicle: 2018 Mitsubishi Outlander PHEV SEL 5-Door SUV    NHTSA No. O20185602

**TEST VEHICLE INFORMATION**

Year/Make/Model/Body Style	2018 Mitsubishi Outlander PHEV 5-Door SUV
NHTSA No.	O20185602
Color	Alloy Silver Metallic
Odometer Reading	195km / 121mi

**DATA FROM CERTIFICATION LABEL**

Manufactured By	MITSUBISHI MOTORS CORPORATION	GVWR (kg)	2370
Date of Manufacture	MAY 18	GAWR Front (kg)	1160
VIN:	JA4J24A56JZ063854	GAWR Rear (kg)	1270

**ELECTRIC VEHICLE PROPULSION SYSTEM**

Type of Electric Vehicle (Electric/Hybrid):	Hybrid
Electric Energy Storage/Device:	Lithium-Ion (Li-Ion) Battery
Nominal Voltage (V):	300 V
Is this vehicle equipped with an Automatic Propulsion Battery Disconnect?	Yes
Physical Location of the Automatic Propulsion Battery Disconnect:	Physically contained within the Energy Storage System.
Auxiliary Battery Type:	Lead Acid Battery



**DATA SHEET 1 (CONTINUED)**  
**TEST VEHICLE SPECIFICATIONS**

Test Vehicle: 2018 Mitsubishi Outlander PHEV SEL 5-Door SUV NHTSA No. O20185602

**ELECTRIC ENERGY STORAGE CONVERSION/DEVICE SYSTEM DATA (COTR SUPPLIED)**

Electrolyte Fluid Type:	Lithium hexafluorophosphate and carbonate ester	
Electrolyte Fluid Specific Gravity:	1.22 (g/mL) at 20°C	
Electrolyte Kinematic Viscosity (centistokes):	2.1 (cP) at 28.5°C	
Electrolyte Fluid Color:	Clear and colorless	
Electric Energy Storage/Conversion System Coolant Type, Color, Specific Gravity (if applicable):	None	
Location of Battery Modules:	<input type="checkbox"/>	Inside Passenger Compartment
	<input checked="" type="checkbox"/>	Outside Passenger Compartment
	The high-voltage battery is mounted below the occupant compartment.	

**ELECTRIC ENERGY STORAGE CONVERSION/DEVICE STATE OF CHARGE**

<i>For all battery types:</i>	
Voltage range corresponding to <b>useable energy</b> of the battery:	
Minimum State of Charge:	N/A
Maximum State of Charge:	328 V
95% of Maximum State of Charge:	311.6 V
Test Voltage - No less than 95% of maximum State of Charge:	327.1 V
<i>For batteries that are rechargeable ONLY by an energy source on the vehicle:</i>	
Voltage range corresponding to <b>useable energy</b> of the battery:	
Minimum State of Charge:	
Maximum State of Charge:	
Test Voltage – Maximum practicable State of Charge within Normal Operating Range:	

**DATA SHEET 2  
PRE-IMPACT DATA**

Test Vehicle: 2018 Mitsubishi Outlander PHEV SEL 5-Door SUV

NHTSA No. O20185602

**VEHICLE CHASSIS GROUND POINT(S) LOCATION(S)**

Details of Vehicle Chassis Ground Point(s) & Location(s)	Vehicle grounding point located on Front Power Drive Unit
--	---

**ELECTRIC ENERGY STORAGE/CONVERSION TEST POINTS**

Details of Electric Energy Storage/Conversion System Test Points:	Connected at Front Power Drive Unit located in engine compartment
---	--

**DATA SHEET 3**  
**PRE-IMPACT ELECTRIC ISOLATION MEASUREMENTS & CALCULATIONS**

Test Vehicle: 2018 Mitsubishi Outlander PHEV SEL 5-Door SUV

NHTSA No. O20185602

**VOLTMETER INFORMATION**

Make:	Fluke
Model:	177
Serial Number:	17210161
Internal Impedance Value (M $\Omega$ ):	> 10 M $\Omega$ < 100 pF
Resolution (V):	0.001 Volts
Last Calibration Date:	5/29/2018

**ELECTRIC ENERGY STORAGE/CONVERSION SYSTEM VOLTAGE**

Measurement shall be made with Energy Storage/Conversion System connected to the vehicle propulsion system, and the vehicle in the "ready-to-drive" (propulsion system energized) position.

If voltage measurement is not at the voltage or within the normal operating voltage range specified by the manufacturer, the battery must be charged.

Vb (V):	327.1
---------	-------

**ELECTRIC ENERGY STORAGE/CONVERSION SYSTEM TO VEHICLE CHASSIS**

Vehicle chassis point(s) determined and supplied to contractor by COTR.

V1 (V):	300.2
V2 (V):	305.0

**ELECTRIC ENERGY STORAGE/CONVERSION SYSTEM TO  
VEHICLE CHASSIS ACROSS RESISTOR**

The known resistance Ro (in ohms) should be approximately 500 times the normal operating voltage of the vehicle (in volts) per SAE J1766.

Ro ( $\Omega$ ):	200,300
------------------	---------

V1' (V) Pre-Impact:	7.3
V2' (V) Pre-Impact:	1.5

**DATA SHEET 3 (CONTINUED)**  
**PRE-IMPACT ELECTRICAL ISOLATION MEASUREMENTS & CALCULATIONS**

Test Vehicle: 2018 Mitsubishi Outlander PHEV SEL 5-Door SUV      NHTSA No. O20185602

**ELECTRICAL ISOLATION MEASUREMENT**

Note: If measured voltage is zero and results in a division by zero, record "Zero Volts". This "zero voltage" condition is considered as being compliant.

V1' (V):	7.3
$R_{i1} = R_o (1 + V_2/V_1) [(V_1 - V_1')/V_1']$	
Ri1 (Ω):	16,201,890
V2' (V):	1.5
$R_{i2} = R_o (1 + V_1/V_2) [(V_2 - V_2')/V_2']$	
Ri2 (Ω):	80,416,926
Ri = The lesser of Ri1 and Ri2	
Ri Pre-Test (Ω):	16,201,890
Ri/Vb (Ω/V):	49,532
Minimum Electrical Isolation Value is 500 Ω/V	

Is the measured Electrical Isolation Value:	Yes, Pass	No, Fail
$\geq 500 \Omega/V$ without electrical isolation monitoring		
$\geq 100 \Omega/V$ with electrical isolation monitoring	X	

# **DATA SHEET 4** **POST-IMPACT DATA**

Test Vehicle: 2018 Mitsubishi Outlander PHEV SEL 5-Door SUV

NHTSA No. O20185602

## **VOLTMETER INFORMATION**

Make:	Fluke
Model:	177
Serial Number:	17210161
Internal Impedance Value (MΩ):	> 10 MΩ < 100 pF
Nominal Propulsion Battery Voltage (Vb) (V):	300

## **ELECTRIC ENERGY STORAGE/CONVERSION SYSTEM VOLTAGE LOCATION OF MEASUREMENT**

Measurement is made from the side of the automatic disconnect connected to the electric powertrain.

Vb (V):	14.4
---------	------

## **ELECTRIC ENERGY STORAGE/CONVERSION SYSTEM VOLTAGE**

V1 =	33.3	V	Impact Time:	0	Minutes	59	s
V2 =	5.0	V	Impact Time:	1	Minutes	11	s
V1' =	0.0	V	Impact Time:	1	Minutes	9	s
V2' =	0.0	V	Impact Time:	1	Minutes	15	s

## **ELECTRICAL ISOLATION MEASUREMENT**

Note: If measured voltage is zero and results in a division by zero, record "Zero Volts". This "zero voltage" condition is considered as being compliant.

$R_{i1} = R_o (1 + V_2/V_1) [(V_1 - V_1')/V_1']$							
Ri1 =	76,484,525	Ω	Impact Time:	1	Minutes	9	s
$R_{i2} = R_o (1 + V_1/V_2) [(V_2 - V_2')/V_2']$							
Ri2 =	Zero Volts	Ω	Impact Time:	1	Minutes	15	s
Ri = The lesser of Ri1 and Ri2							
Ri =	Zero Volts	Ω	Impact Time:	1	Minutes	15	s
Ri/Vb = electrical Isolation Value/Nominal Battery Voltage							
Minimum Electrical Value is 500 Ω/V							
Ri/Vb =	Zero Volts	Ω/V	Impact Time:	0	Minutes	54	s

Is the measured Electrical Isolation Value:	Yes, Pass	No, Fail
≥500 Ω/V without electrical isolation monitoring		
≥100 Ω/V with electrical isolation monitoring	X	

**DATA SHEET 4 (CONTINUED)**  
**POST-IMPACT DATA**

Test Vehicle: 2018 Mitsubishi Outlander PHEV SEL 5-Door SUV

NHTSA No. O20185602

**ELECTRIC ENERGY STORAGE/CONVERSION DEVICE**

	Inside Passenger Compartment	Outside Passenger Compartment
Location of Electric Energy Storage/Conversion Device:		X

	Yes, Pass	No, Fail
All Components of Electrical Energy Storage/Conversion Device remained attached to the vehicle with at least one mounting location.	X	

Describe Electric Energy Storage/Conversion Device movement within the passenger compartment [Supply photographs as appropriate]:
Not Applicable

	Yes, Fail	No, Pass
Has the Electric Energy Storage/Conversion Device moved within the passenger compartment?		X

Describe intrusion of an outside Electric Energy Storage/Conversion Device into the passenger compartment [Supply photographs as appropriate]:
No Intrusion


	Yes, Fail	No, Pass
Has an outside Electric Energy Storage/Conversion Device intruded into the passenger compartment?		X

	Yes, Fail	No, Pass
Is Electric Energy Storage/Conversion Device electrolyte spillage visible in the passenger compartment?		X

## DATA SHEET 5 STATIC ROLLOVER TEST DATA

Test Vehicle: 2018 Mitsubishi Outlander PHEV SEL 5-Door SUV

NHTSA No. O20185602



### DETERMINATION OF ELECTRIC ENERGY STORAGE/CONVERSION DEVICE ELECTROLYTE COLLECTION TIME PERIOD

Rollover Stage	Rotation Time (spec. 1-3 min)				FMVSS 301 Hold Time		Total Time				Next Whole Minute Interval	
0° - 90°	1	minutes	54	seconds	5	minutes	6	minutes	54	seconds	7	minutes
90° - 180°	1	minutes	51	seconds	5	minutes	6	minutes	51	seconds	7	minutes
180° - 270°	1	minutes	48	seconds	5	minutes	6	minutes	48	seconds	7	minutes
270° - 360°	1	minutes	50	seconds	5	minutes	6	minutes	50	seconds	7	minutes

### ACTUAL TEST VEHICLE ELECTRIC ENERGY STORAGE/CONVERSION DEVICE ELECTROLYTE SPILLAGE

Rollover Stage	Electric Energy Storage/Conversion Device Electrolyte Spillage (L)	Spillage Location
0° to 90°	0	Not Applicable
90° to 180°	0	Not Applicable
180° to 270°	0	Not Applicable
270° to 360°	0	Not Applicable

Total Spillage: 0 L

	Yes, Fail	No, Pass
Is the total spillage of Electric Energy Storage/Conversion Device electrolyte greater than 5.0 Liters?		X
Is Electric Energy Storage/Conversion Device electrolyte spillage visible in the passenger compartment?		X

**DATA SHEET 5 (CONTINUED)**  
**STATIC ROLLOVER TEST DATA**

Test Vehicle: 2018 Mitsubishi Outlander PHEV SEL 5-Door SUV

NHTSA No. O20185602

**VOLTMETER INFORMATION**

Make:	Fluke
Model:	177
Serial Number:	17210161
Internal Impedance Value (MΩ):	> 10 MΩ < 100 pF
Nominal Electric Energy Storage/Conversion Device Voltage (Vb) (V):	300
Record V1, V2, V1', V2' voltage measurements at the start of each successive increment of 90°, 180°, 270°, and 360° of the static rollover test.	

**ELECTRICAL ISOLATION MEASUREMENT**

V1 =	0	V	0°	Time:		Minutes		s
V1 =	0	V	90°	Time:	2	Minutes	20	s
V1 =	0	V	180°	Time:	2	Minutes	13	s
V1 =	0	V	270°	Time:	2	Minutes	20	s
V1 =	0	V	360°	Time:	2	Minutes	17	s
V2 =	0	V	0°	Time:		Minutes		s
V2 =	0	V	90°	Time:	2	Minutes	24	s
V2 =	0	V	180°	Time:	2	Minutes	18	s
V2 =	0	V	270°	Time:	2	Minutes	23	s
V2 =	0	V	360°	Time:	2	Minutes	20	s
V1' =	0	V	0°	Time:		Minutes		s
V1' =	0	V	90°	Time:	2	Minutes	30	s
V1' =	0	V	180°	Time:	2	Minutes	28	s
V1' =	0	V	270°	Time:	2	Minutes	23	s
V1' =	0	V	360°	Time:	2	Minutes	20	s
V2' =	0	V	0°	Time:		Minutes		s
V2' =	0	V	90°	Time:	2	Minutes	34	s
V2' =	0	V	180°	Time:	2	Minutes	22	s
V2' =	0	V	270°	Time:	2	Minutes	26	s
V2' =	0	V	360°	Time:	2	Minutes	23	s
Vb =	0	V	0°	Time:		Minutes		s
Vb =	0	V	90°	Time:	2	Minutes	14	s
Vb =	0	V	180°	Time:	2	Minutes	10	s
Vb =	0	V	270°	Time:	2	Minutes	18	s
Vb =	0	V	360°	Time:	2	Minutes	15	s



**DATA SHEET 5 (CONTINUED)**  
**STATIC ROLLOVER TEST DATA**

Test Vehicle: 2018 Mitsubishi Outlander PHEV SEL 5-Door SUV

NHTSA No. O20185602

**ELECTRICAL ISOLATION CALCULATION**

Note: If measured voltage is zero and results in a division by zero, record "Zero Volts". This "zero voltage" condition is considered as being compliant.

$R_{i1} = R_o (1 + V_2/V_1) [(V_1 - V_1')/V_1']$								
R <sub>i1</sub> =	Zero Volts	Ω	0°	Time:		Minutes		s
R <sub>i1</sub> =	Zero Volts	Ω	90°	Time:	2	Minutes	20	s
R <sub>i1</sub> =	Zero Volts	Ω	180°	Time:	2	Minutes	13	s
R <sub>i1</sub> =	Zero Volts	Ω	270°	Time:	2	Minutes	20	s
R <sub>i1</sub> =	Zero Volts	Ω	360°	Time:	2	Minutes	17	s
$R_{i2} = R_o (1 + V_1/V_2) [(V_2 - V_2')/V_2']$								
R <sub>i2</sub> =	Zero Volts	Ω	0°	Time:		Minutes		s
R <sub>i2</sub> =	Zero Volts	Ω	90°	Time:	2	Minutes	24	s
R <sub>i2</sub> =	Zero Volts	Ω	180°	Time:	2	Minutes	18	s
R <sub>i2</sub> =	Zero Volts	Ω	270°	Time:	2	Minutes	23	s
R <sub>i2</sub> =	Zero Volts	Ω	360°	Time:	2	Minutes	20	s
R <sub>i</sub> = The lesser of R <sub>i1</sub> and R <sub>i2</sub>								
R <sub>i</sub> =	Zero Volts	Ω	0°	Time:		Minutes		s
R <sub>i</sub> =	Zero Volts	Ω	90°	Time:	2	Minutes	20	s
R <sub>i</sub> =	Zero Volts	Ω	180°	Time:	2	Minutes	13	s
R <sub>i</sub> =	Zero Volts	Ω	270°	Time:	2	Minutes	20	s
R <sub>i</sub> =	Zero Volts	Ω	360°	Time:	2	Minutes	17	s
R <sub>i</sub> /V <sub>b</sub> = Electrical Isolation Value/Nominal Battery Voltage Minimum Electrical Isolation Value is 500 Ω /V								
R <sub>i</sub> /V <sub>b</sub> =	Zero Volts	Ω/V	0°	Time:		Minutes		s
R <sub>i</sub> /V <sub>b</sub> =	Zero Volts	Ω/V	90°	Time:	2	Minutes	14	s
R <sub>i</sub> /V <sub>b</sub> =	Zero Volts	Ω/V	180°	Time:	2	Minutes	10	s
R <sub>i</sub> /V <sub>b</sub> =	Zero Volts	Ω/V	270°	Time:	2	Minutes	18	s
R <sub>i</sub> /V <sub>b</sub> =	Zero Volts	Ω/V	360°	Time:	2	Minutes	15	s

Is the measured Electrical Isolation Value:	Yes, Pass	No, Fail
≥500 Ω/V without electrical isolation monitoring		
≥100 Ω/V with electrical isolation monitoring	X	

**APPENDIX A  
PHOTOGRAPHS**

## TABLE OF PHOTOGRAPHS

		<u>Page No.</u>
Photo No. 001	Auxiliary Power Module Warning Label	A-1
Photo No. 002	Power Inverter Warning Label	A-1
Photo No. 003	First Responder Warning Label	A-2
Photo No. 004	First Responder Warning Location	A-2
Photo No. 005	Other Vehicle Label(s) Related to Electrical Propulsion System	A-3
Photo No. 006	Manual High Voltage Service Disconnect in Place	A-3
Photo No. 007	Manual High Voltage Service Disconnect Removed	A-4
Photo No. 007a	Manual High Voltage Service Disconnect Removed	A-4
Photo No. 008	Pre-Impact View of Propulsion Battery	A-5
Photo No. 009	Post-Impact Front View of Propulsion Battery	A-5
Photo No. 010	Post-Impact Rear View of Propulsion Battery	A-6
Photo No. 011	Pre-Impact View of Battery Box(s) or Container(s) Which Holds Individual Battery Modules	A-6
Photo No. 012	Post-Impact View of Battery Box(s) or Container(s) Which Holds Individual Battery Modules	A-7
Photo No. 013	Pre-Impact View of Propulsion Battery Module(s)	A-7
Photo No. 014	Post-Impact View of Propulsion Battery Module(s)	A-8
Photo No. 015	Pre-Impact View of Electric Propulsion Drive	A-8
Photo No. 015a	Pre-Impact View of Electric Propulsion Drive	A-9
Photo No. 016	Post-Impact View of Electric Propulsion Drive	A-9
Photo No. 016a	Post-Impact View of Electric Propulsion Drive	A-10
Photo No. 017	Pre-Impact View of High Voltage Interconnect(s)	A-10
Photo No. 018	Pre-Impact View Propulsion Battery Venting System(s)	A-11
Photo No. 019	Pre-Impact View of Other Visible Electric Propulsion Components	A-11
Photo No. 020	Pre-Impact View of Ground Lead Attached	A-12
Photo No. 021	Pre-Impact View of High Voltage Leads Attached	A-12
Photo No. 022	Pre-Impact Close-Up View of High Voltage Leads Attached	A-13
Photo No. 023	Pre-Impact View of Installed Impact Interface Port	A-13
Photo No. 024	Post-Impact View of Installed Impact Interface Port	A-14
Photo No. 025	Pre-Impact View of Other Test Devices	A-14
Photo No. 026	Post-Impact View of Other Test Devices	A-15
Photo No. 027	FMVSS No. 305 Static Rollover at 90°	A-15
Photo No. 028	FMVSS No. 305 Static Rollover at 180°	A-16
Photo No. 029	FMVSS No. 305 Static Rollover at 270°	A-16

		<u>Page No.</u>
Photo No. 030	FMVSS No. 305 Static Rollover at 360°	A-17
Photo No. 031	Pre-Impact View of the Vehicle Passenger Compartment Adjacent to Propulsion Battery	A-17
Photo No. 032	Post-Impact View of the Vehicle Passenger Compartment Adjacent to Propulsion Battery	A-18
Photo No. 033	Post-Impact Propulsion Battery System Mounting and/or Intrusion Failure(s)	A-18
Photo No. 034	Post-Impact View of Battery Component Intrusion	A-19
Photo No. 035	Post-Impact View of Battery Module Movement or Retention Loss	A-19
Photo No. 036	Post-Impact View of Propulsion Battery Electrolyte Spillage Location	A-20
Photo No. 037	Post-Test View of Propulsion Battery Electrolyte Spillage Location	A-20
Photo No. 038	As Delivered Right Front $\frac{3}{4}$ View of Impact Vehicle	A-21
Photo No. 039	As Delivered Left Rear $\frac{3}{4}$ View of Impact Vehicle	A-21
Photo No. 040	Vehicle's Certification Label	A-22
Photo No. 041	Vehicle's Tire Information Placard or Label	A-22



Photo No. 001 - Auxiliary Power Module Warning Label



Photo No. 002 - Power Inverter Warning Label

**PHOTOGRAPH NOT APPLICABLE**

Photo No. 003 - First Responder Warning Label

**PHOTOGRAPH NOT APPLICABLE**

Photo No. 004 - First Responder Warning Location





Photo No. 005 - Other Vehicle Label(s) Related to Electrical Propulsion System




Photo No. 006 - Manual High Voltage Service Disconnect in Place






Photo No. 007 - Manual High Voltage Service Disconnect Removed



Photo No. 007a - Manual High Voltage Service Disconnect Removed





Photo No. 008 - Pre-Impact View of Propulsion Battery




Photo No. 009 - Post-Impact Front View of Propulsion Battery




Photo No. 010 - Post-Impact Rear View of Propulsion Battery

**PHOTOGRAPH NOT AVAILABLE**

Photo No. 011 - Pre-Impact View of Battery Box(s) or Container(s) Which Holds Individual Battery Modules

**PHOTOGRAPH NOT AVAILABLE**

Photo No. 012 - Post-Impact View of Battery Box(s) or Container(s) Which Holds Individual Battery Modules

**PHOTOGRAPH NOT AVAILABLE**

Photo No. 013 - Pre-Impact View of Propulsion Battery Module(s)



**PHOTOGRAPH NOT AVAILABLE**

Photo No. 014 - Post-Impact View of Propulsion Battery Module(s)



Photo No. 015 - Pre-Impact View of Electric Propulsion Drive



Photo No. 015a - Pre-Impact View of Electric Propulsion Drive

**PHOTOGRAPH NOT AVAILABLE**

Photo No. 016 - Post-Impact View of Electric Propulsion Drive






Photo No. 016a - Post-Impact View of Electric Propulsion Drive

**PHOTOGRAPH NOT AVAILABLE**

Photo No. 017 - Pre-Impact View of High Voltage Interconnect(s)

# PHOTOGRAPH NOT APPLICABLE

Photo No. 018 - Pre-Impact View Propulsion Battery Venting System(s)



Photo No. 019 - Pre-Impact View of Other Visible Electric Propulsion Components





Photo No. 020 - Pre-Impact View of Ground Lead Attached



Photo No. 021 - Pre-Impact View of High Voltage Leads Attached






Photo No. 022 - Pre-Impact Close-Up View of High Voltage Leads Attached

**PHOTOGRAPH NOT AVAILABLE**

Photo No. 023 - Pre-Impact View of Installed Impact Interface Port

**PHOTOGRAPH NOT AVAILABLE**

Photo No. 024 - Post-Impact View of Installed Impact Interface Port

**PHOTOGRAPH NOT APPLICABLE**

Photo No. 025 - Pre-Impact View of Other Test Devices

# PHOTOGRAPH NOT APPLICABLE

Photo No. 026 - Post-Impact View of Other Test Devices




Photo No. 027 - FMVSS No. 305 Static Rollover at 90°





Photo No. 028 - FMVSS No. 305 Static Rollover at 180°



Photo No. 029 - FMVSS No. 305 Static Rollover at 270°





Photo No. 030 - FMVSS No. 305 Static Rollover at 360°



Photo No. 031 - Pre-Impact View of the Vehicle Passenger Compartment Adjacent to Propulsion Battery





Photo No. 032 - Post-Impact View of the Vehicle Passenger Compartment Adjacent to Propulsion Battery

**PHOTOGRAPH NOT APPLICABLE**

Photo No. 033 - Post-Impact Propulsion Battery System Mounting and-or Intrusion Failure(s)

**PHOTOGRAPH NOT APPLICABLE**

Photo No. 034 - Post-Impact View of Battery Component Intrusion



Photo No. 035 - Post-Impact View of Battery Module Movement or Retention Loss

**PHOTOGRAPH NOT APPLICABLE**

Photo No. 036 - Post-Impact View of Propulsion Battery Electrolyte Spillage Location

**PHOTOGRAPH NOT APPLICABLE**

Photo No. 037 - Post-Test View of Propulsion Battery Electrolyte Spillage Location





Photo No. 038 - As Delivered Right Front Three-Quarter View of Impact Vehicle



Photo No. 039 - As Delivered Left Rear Three-Quarter View of Impact Vehicle





Photo No. 040 - Vehicle's Certification Label



Photo No. 041 - Vehicle's Tire Information Placard or Label