

REPORT NUMBER: NCAP-CAL-20-006

**NEW CAR ASSESSMENT PROGRAM (NCAP)
FRONTAL BARRIER IMPACT TEST**

**Ford Motor Co.
2020 Ford Escape
Four Door SUV**

NHTSA No: M20200200

**PREPARED BY:
CALSPAN CORPORATION
P.O. BOX 400
BUFFALO, NEW YORK 104625**



April 14, 2020

FINAL REPORT

**PREPARED FOR:
U. S. DEPARTMENT OF TRANSPORTATION
NATIONAL HIGHWAY TRAFFIC SAFETY ADMINISTRATION
OFFICE OF CRASHWORTHINESS STANDARDS
1200 NEW JERSEY AVE SE, ROOM W43-410
WASHINGTON, D.C. 20590**

This final test report was prepared for the U.S. Department of Transportation, National Highway Traffic Administration, in response to Contract Number 693JJ919D000005.

This publication is distributed by the U.S. Department of Transportation, National Highway Traffic Safety Administration, in the interest of information exchange. The opinions, findings and conclusions expressed in this publication are those of the author(s) and not necessarily those of the Department of Transportation or the National Highway Traffic Safety Administration. The United States Government assumes no liability for its contents or use thereof.

If trade or manufacturers' names or products are mentioned it is only because they are considered essential to the object of the publication and should not be construed as an endorsement. The United States Government does not endorse products or manufacturers.

Prepared by: Vanessa Hansen
Vanessa Hansen, Operations Manager

Date: April 14, 2020

Approved by: Edward Dutton
Edward Dutton, Director

Date: April 14, 2020

FINAL REPORT ACCEPTANCE BY OCWS:

Division Chief, New Car Assessment Program
NHTSA, Office of Crashworthiness Standards

Date: _____

COTR, New Car Assessment Program
NHTSA, Office of Crashworthiness Standards

Date: _____

TECHNICAL REPORT DOCUMENTATION PAGE

1. Report No. NCAP-CAL-20-006		2. Government Accession No.		3. Recipient's Catalog No.																																																					
4. Title and Subtitle Final Report of New Car Assessment Program Frontal Impact Testing of a 2020 Ford Escape four door SUV NHTSA No.: M20200200				5. Report Date April 14, 2020																																																					
				6. Performing Organization Code CAL																																																					
7. Author(s) Vanessa Hansen, Operations Manager Edward Dutton, Director				8. Performing Organization Report No. CAL-DOT-2020-006																																																					
9. Performing Organization Name and Address Calspan Corporation Transportation Test Operations P.O. Box 400 Buffalo, New York 104625				10. Work Unit No.																																																					
				11. Contract or Grant No. 693JJ919D000005																																																					
12. Sponsoring Agency Name and Address U.S. Department of Transportation National Highway Traffic Safety Administration Office of Crashworthiness Standards 1200 New Jersey Ave., SE, Room W43-410 Washington, D.C. 20590				13. Type of Report and Period Covered: Final Test Report January 8, 2020 - April 14, 2020																																																					
				14. Sponsoring Agency Code NRM-110																																																					
15. Supplementary Notes																																																									
16. Abstract <p>A 56.30 km/h (35 mph), NCAP frontal rigid barrier impact test was conducted on a 2020 Ford Escape four door SUV in accordance with the specifications of the Office of Crashworthiness Standards Laboratory Procedure for NCAP Full Frontal Rigid Barrier Impact Testing. This test was conducted to obtain data related to FMVSS Nos. 208, 212, 219 (partial), and 301 performance. The test was conducted at Calspan Corporation's Transportation Test Operations facility in Buffalo, New York on January 8, 2020.</p> <p>The impact velocity of the vehicle was 56.26 km/h, and the ambient temperature at the barrier face at the time of impact was 21°C. The target vehicle post-test maximum crush was 353 mm at C3 to the left side of the front bumper. The test vehicle's occupant performance data is as follows:</p> <table border="1"> <thead> <tr> <th rowspan="2">Measurement Description</th> <th rowspan="2">Units</th> <th colspan="2">Driver ATD (Serial No. 142)</th> <th colspan="2">Passenger ATD (Serial No. 140)</th> </tr> <tr> <th>Threshold</th> <th>Result</th> <th>Threshold</th> <th>Result</th> </tr> </thead> <tbody> <tr> <td>Head Injury Criteria (HIC₁₅)</td> <td></td> <td>700</td> <td>142.626</td> <td>700</td> <td>102.179</td> </tr> <tr> <td>Maximum Chest Compression</td> <td>mm</td> <td>63</td> <td>-21.114</td> <td>52</td> <td>-11.621</td> </tr> <tr> <td>Nij</td> <td></td> <td>1</td> <td>0.225</td> <td>1</td> <td>0.363</td> </tr> <tr> <td>Neck Tension</td> <td>N</td> <td>4,170</td> <td>824.514</td> <td>2,620</td> <td>804.237</td> </tr> <tr> <td>Neck Compression</td> <td>N</td> <td>4,000</td> <td>-102.680</td> <td>2,520</td> <td>-259.329</td> </tr> <tr> <td>Left Femur Force</td> <td>N</td> <td>10,008</td> <td>-835.824</td> <td>6,805</td> <td>-977.463</td> </tr> <tr> <td>Right Femur Force</td> <td>N</td> <td>10,008</td> <td>-1398.969</td> <td>6,805</td> <td>-750.534</td> </tr> </tbody> </table>						Measurement Description	Units	Driver ATD (Serial No. 142)		Passenger ATD (Serial No. 140)		Threshold	Result	Threshold	Result	Head Injury Criteria (HIC ₁₅)		700	142.626	700	102.179	Maximum Chest Compression	mm	63	-21.114	52	-11.621	Nij		1	0.225	1	0.363	Neck Tension	N	4,170	824.514	2,620	804.237	Neck Compression	N	4,000	-102.680	2,520	-259.329	Left Femur Force	N	10,008	-835.824	6,805	-977.463	Right Femur Force	N	10,008	-1398.969	6,805	-750.534
Measurement Description	Units	Driver ATD (Serial No. 142)		Passenger ATD (Serial No. 140)																																																					
		Threshold	Result	Threshold	Result																																																				
Head Injury Criteria (HIC ₁₅)		700	142.626	700	102.179																																																				
Maximum Chest Compression	mm	63	-21.114	52	-11.621																																																				
Nij		1	0.225	1	0.363																																																				
Neck Tension	N	4,170	824.514	2,620	804.237																																																				
Neck Compression	N	4,000	-102.680	2,520	-259.329																																																				
Left Femur Force	N	10,008	-835.824	6,805	-977.463																																																				
Right Femur Force	N	10,008	-1398.969	6,805	-750.534																																																				
17. Key Words 56.3 km/h (35 mph) Full Frontal Rigid Barrier Impact Test New Car Assessment Program (NCAP)				18. Distribution Statement Copies of this report are available from: National Highway Traffic Safety Administration Technical Information Services Division 1200 New Jersey Ave, SE Washington, DC 20590																																																					
19. Security Class. (of this report) UNCLASSIFIED		20. Security Class. (of this page) UNCLASSIFIED		21. No. of Pages 167	22. Price																																																				

Form DOT F1700.7 (8-69)

TABLE OF CONTENTS

<u>Section</u>		<u>Page</u>
1	Purpose and Summary of the Test	1-1
2	Occupant and Vehicle Information / Data Sheets	2-1
<u>Data Sheet</u>		<u>Page</u>
1	General Test and Vehicle Parameter Data	2-2
2	Seat Adjustment, Fuel System, and Steering Wheel Data	2-6
3	Dummy Longitudinal Clearance Dimensions	2-8
4	Dummy Lateral Clearance Dimensions	2-9
5	Seat Belt Positioning Data	2-10
6	High-Speed Camera Locations and Data	2-11
7	Vehicle Accelerometer Locations	2-13
8	Photographic Reference Target Locations	2-14
9	Load Cell Locations on Fixed Barrier	2-15
10	Test Vehicle Summary of Results	2-16
11	Post-Test Observations	2-17
12	Vehicle Profile Measurements	2-18
13	Accident Investigation Division Data	2-20
14	Vehicle Intrusion Measurements	2-21
15	Summary of Indicant FMVSS No.212 and FMVSS No.219 (Partial) Data	2-23
16	FMVSS 301 Barrier Impact & Static Rollover Results	2-25
17	Dummy/Vehicle Temperature Stabilization Chart	2-26
<u>Appendix</u>		<u>Page</u>
A	Photographs	A-1
B	Dummy Response Data Traces	B-1
C	Dummy Calibration and Performance Verification Data	C-1
D	Test Equipment and Instrumentation Calibration	D-1

SECTION 1

PURPOSE AND SUMMARY OF TEST

PURPOSE

This 56.3 km/h frontal barrier impact test is part of the Vehicle Barrier Impact Testing Program sponsored by the National Highway Traffic Safety Administration (NHTSA) under Contract No. 693JJ919D000005. The purpose of this test was to obtain vehicle crashworthiness and occupant restraint system performance data for consumer information purposes.

The 56.3 km/h frontal barrier impact test was conducted in accordance with the Office of Crashworthiness Standards Laboratory Procedure for NCAP Full Frontal Rigid Barrier Impact Testing.

SUMMARY

A load cell barrier consisting of 128 load cells was impacted by a 2020 Ford Escape four door SUV at a velocity of 56.26 km/h. The test was performed at Calspan Corporation's Transportation Test Operations facility in Buffalo, New York on January 8, 2020. Pre- and post-test photographs of the vehicle and dummies to document the test can be found in Appendix A. One real-time camera and 16 high-speed cameras were used to document the frontal barrier impact event. Camera locations and other pertinent camera information can be found in Data Sheet 6 of this report.

One Part 572E, 50th percentile male anthropomorphic test device (ATD), was placed in the driver seating position and one Part 572O 5th percentile female ATD was placed in the right-front passenger seating position according to dummy placement instructions specified in the Laboratory Procedure for NCAP Full Frontal Rigid Barrier Impact Testing. Both ATDs were fully instrumented with head, chest and pelvis tri-axial accelerometers, chest displacement potentiometers, upper neck transducers, femur load cells, and lower leg instrumentation. The driver (position 1) ATD (Serial No. 142) and the right-front passenger (position 2) ATD (Serial No. 140) were qualified prior to this test. Certification details, along with instrumentation calibration data, can be found in Appendix C of this report.

The 486 channels of data were recorded on an on-board data acquisition system. Appendix B contains the vehicle, load cell barrier and dummy response data traces.

There was 100 percent windshield retention and no intrusion into the protected zone of the windshield during the event. There was a total of 0.0 grams of stoddard solvent leakage after the event or during any phase of the static rollover. The maximum static crush of the vehicle was 353 mm and both driver and passenger side doors remained closed during the impact event and were operable after the impact.

The driver's visible contact points were as follows: The driver's head contacted the frontal airbag and then the head restraint. The upper torso contacted the frontal airbag. Both knees contacted the knee air bag.

The passenger's visible contact points were as follows: The passenger's head contacted the frontal airbag and then the head restraint. The upper torso contacted the frontal airbag. Both knees contacted the glove box.

The occupant data is summarized below.

ATD Position	HIC ₁₅	Nij	Neck Tension (N)	Neck Comp. (N)	3ms Chest Clip (Gs)	Chest Disp. (mm)	Left Femur (N)	Right Femur (N)
Driver (50 th)	142.626	0.225	824.514	-102.680	34.385	-21.114	-835.824	-1398.969
Passenger (5 th)	102.179	0.363	804.237	-259.329	33.297	-11.621	-977.463	-750.534

GENERAL COMMENTS:

1. P1 (Driver) serial number - 142
2. P2 (Passenger) serial number – 140
3. Driver shoulder and lap belt load cells were not installed
4. Passenger shoulder and lap belt load cells were not installed

Data Anomalies:

- None

SECTION 2

OCCUPANT AND VEHICLE INFORMATION / DATA SHEETS

This section contains information reporting for the following Data Sheets:

Data Sheet No. 1 – General Test and Vehicle Parameter Data

Data Sheet No. 2 – Seat Adjustment, Fuel System, and Steering Wheel Data

Data Sheet No. 3 – Dummy Longitudinal Clearance Dimensions

Data Sheet No. 4 – Dummy Lateral Clearance Dimensions

Data Sheet No. 5 – Seat Belt Positioning Data

Data Sheet No. 6 – High-Speed Camera Locations and Data

Data Sheet No. 7 – Vehicle Accelerometer Locations

Data Sheet No. 8 – Photographic Reference Target Locations

Data Sheet No. 9 – Load Cell Locations on Fixed Barrier

Data Sheet No. 10 – Test Vehicle Summary of Results

Data Sheet No. 11 – Post-Test Observations

Data Sheet No. 12 – Vehicle Profile Measurements

Data Sheet No. 13 – Accident Investigation Division Data

Data Sheet No. 14 – Vehicle Intrusion Measurements

Data Sheet No. 15 – Summary of Indicant FMVSS No. 212 and FMVSS No. 219 (Partial)

Data Sheet No. 16 – FMVSS 301 Barrier Impact and Static Rollover Results

Data Sheet No. 17 – Dummy/Vehicle Temperature Stabilization Chart

DATA SHEET NO. 1
GENERAL TEST AND VEHICLE PARAMETER DATA

Test Vehicle: 2020 Ford Escape four door SUV
Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20200200
Test Date: 1/8/2020

TEST VEHICLE INFORMATION AND OPTIONS

NHTSA No.	M20200200	Traction Control System (TCS)	Yes
Model Year	2020	Power Steering	Yes
Make	Ford	Power Window Auto-Reverse	No
Model	Escape	Driver Frontal Airbag	Yes
Body Style	SUV	Driver Curtain Airbag	Yes
VIN	1FMCU9G66LUA20567	Driver Head/Torso Airbag	No
Body Color	Silver	Driver Torso Airbag	No
Odometer Reading (km /mi)	15 Miles	Driver Torso/Pelvis Airbag	Yes
Engine Displacement (L)	1.5	Driver Pelvis Airbag	No
Type / No. Cylinders	I3 Ecoboost w/ Start-Stop	Driver Knee Airbag	Yes
Engine Placement	Transverse	Front Pass. Frontal Airbag	Yes
Transmission Type	Automatic	Front Pass. Curtain Airbag	Yes
Transmission Speeds	8-Speed	Front Pass. Head/Torso Airbag	No
Overdrive	Yes	Front Pass. Torso Airbag	No
Final Drive	All Wheel Drive	Front Pass. Torso/Pelvis Airbag	Yes
Roof Rack	No	Front Pass. Pelvis Airbag	No
Sunroof / T-Top	No	Front Pass. Knee Airbag	No
Running Boards	No	Driver Pretensioner	Yes
Tilt Steering Wheel	Yes	Driver Load Limiter	Yes
Power Seats	Yes	Front Pass. Pretensioner	Yes
Anti-Lock Brakes (ABS)	Yes	Front Pass. Load Limiter	Yes
Automatic Door Locks (ADLs)	Yes	Other –	-

Does owner's manual provide instructions to turn off automatic door locks?

No

DATA FROM CERTIFICATION LABEL

Manufactured By	Ford Motor Co.	GVWR (kg)	2041
Date of Manufacture	10/19	GAWR Front (kg)	1089
		GAWR Rear (kg)	1007

VEHICLE SEATING AND WEIGHT CAPACITY DATA


Measured Parameter	Front	Rear	Third	Total
Type of Seats	Bucket	Bench	N/A	
Number of Occupants	2	3	N/A	5
Capacity Wt. (VCW) (kg)				441
Cargo Wt. (RCLW) (kg)				100.8

DATA SHEET NO. 1 ... (CONTINUED)
GENERAL TEST AND VEHICLE PARAMETER DATA

Test Vehicle: 2020 Ford Escape four door SUV
 Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20200200
 Test Date: 1/8/2020

Collect items circled in red, tire manufacturer, and tire name.



VEHICLE TIRE INFORMATION

Measured Parameter	Front	Rear
Maximum Tire Pressure (kPa)	350	350
Cold Pressure (kPa)	230	230
Recommended Tire Size	225/65R17	225/65R17
Tire Size on Vehicle	225/65R17	225/65R17
Tire Manufacturer	Continental	Continental
Tire Model	ProContact	ProContact
Treadwear	500	500
Traction	A	A
Temperature Grades	A	A
Tire Plies Sidewall	1 Polyester	1 Polyester
Tire Plies Body	1 Polyester, 2 Steel, 1 Polyamide	1 Polyester, 2 Steel, 1 Polyamide
Load Index / Speed Symbol	102H	102H
Tire Material	Rubber	Rubber
DOT Safety Code Left	P52YWC4H3819	P52YWC4H3819
DOT Safety Code Right	P52YWC4H3819	P52YWC4H3819

DATA SHEET NO. 1 ... (CONTINUED)
GENERAL TEST AND VEHICLE PARAMETER DATA

Test Vehicle: 2020 Ford Escape four door SUV
 Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20200200
 Test Date: 1/8/2020

TEST VEHICLE WEIGHTS

	Units	As Delivered Weights (UVW)			As Tested Weights (ATW)		
		Front Axle	Rear Axle	Total	Front Axle	Rear Axle	Total
Left	kg	471	334		502.5	427.5	
Right	kg	444	325		484	395	
Ratio	%	58.1	41.9		54.5	45.5	
Totals	kg	915	659	1574	986.5	822.5	1809

TARGET TEST WEIGHT CALCULATION

Measured Parameter	Units	Value	
Total Delivered Weight (UVW)	kg	1574	(A)
Weight of 1 P572E ATD & 1 P572O ATD	kg	142	(B)
Rated Cargo / Luggage Weight (RCLW)	kg	100.8	(C)
Calculated Vehicle Target Weight (TVTW)	kg	1816.8	(A+B+C)

TEST VEHICLE ATTITUDES AND CG

Condition	Units	LF	RF	LR	RR	CG (aft of front axle)
As Delivered	mm	859	865	871	879	1134
As Tested	mm	840	847	837	841	1232
Post-Test	mm	933	853	862	810	

GENERAL TEST VEHICLE DATA

Measurement Description	Units	Value
Total Vehicle Wheel Base	mm	2709
Total Vehicle Length at Left Side	mm	4461
Total Vehicle Length at Centerline	mm	4590
Total Vehicle Length at Right Side	mm	4461
Weight of Ballast in Cargo Area	kg	54
Weight of Vehicle Components Removed	kg	29
Amount of Stoddard Solvent in Fuel Tank	L	55.2

LIST OF COMPONENTS REMOVED TO MEET TEST WEIGHT:

Trunk carpeting, spare tire, jack, tail light, underbody shields

DATA SHEET NO.1 ... (CONTINUED)
GENERAL TEST AND VEHICLE PARAMETER DATA

Test Vehicle: 2020 Ford Escape four door SUV
 Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20200200
 Test Date: 1/8/2020

TARGET VEHICLE STRUCTURAL MEASUREMENT

No.	Description	Pre-Test
1	Total Length	4590
2	Total Width	1809
3*	Bumper Top Height	594
4*	Bumper Bottom Height	439
5*	Longitudinal Member Top Height	654
6	Distance Between Longitudinal Members	1072
7	Longitudinal Member Width	88
8*	Engine Top Height	882
9*	Engine Bottom Height	353
10	Engine and Gearbox Width	470
11	Front Bumper-Engine Distance	671
12*	Front Shock Absorber Fixing Height	940
13*	Bonnet Leading Edge Height	934
14	Front Shock Absorber Fixing Width	1099
15	Front Bumper – Front Axle Distance	970
16	Front Axle – A Pillar Distance	554
17	A-Pillar – B-Pillar Distance	1043
18	B-Pillar – Rear Axle Distance	1112
19	B-Pillar – C-Pillar Distance	1306
20*	Roof Sill Bottom Height	1539
21*	Roof Sill Top Height	1584
22*	Floor Sill Bottom Height	387
23*	Floor Sill Top Height	455

*Height Measurements are taken from the ground
 Note: All measurements are in millimeters


DATA SHEET NO. 2 SEAT ADJUSTMENT, FUEL SYSTEM, AND STEERING WHEEL DATA

Test Vehicle: 2020 Ford Escape four door SUV
Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20200200
Test Date: 1/8/2020

NOMINAL DESIGN RIDING POSITION

The driver's seat back was set to the manufacturer's designated angle. The passenger's seat back was positioned in a similar manner as the driver's seat back. Seat back angles are measured at the headrest post bezel using a digital inclinometer.



Seating Position	Degrees
Driver Seat Back Angle	3.1
Passenger Seat Back Angle	0.5

SEAT FORE / AFT POSITIONS


The driver's seat was positioned at the mid-point of fore/aft travel at its lowest position. The passenger's seat was positioned at the most forward position of fore/aft travel. Zero is defined as the forward most position.

Seating Position	Total Fore / Aft Travel	Placed in Position #
Driver Seat	300	150
Passenger Seat	38 (0-37)	0

SEAT BELT UPPER ANCHORAGE

The driver's seat belt anchorage was positioned according to the manufacturer's designated positioning for a 50th percentile adult male ATD. The passenger's seat belt anchorage was positioned according to the manufacturer's designated positioning for a 5th percentile adult female ATD. For this test zero is defined as the uppermost position.

Seating Position	Total # of Positions	Placed in Position #
Driver Seat	4	0
Passenger Seat	4	0



DATA SHEET NO. 2 ... (CONTINUED)
SEAT ADJUSTMENT, FUEL SYSTEM, AND STEERING WHEEL DATA

Test Vehicle: 2020 Ford Escape four door SUV
 Test Program: NCAP Frontal Barrier Impact Test


NHTSA No.: M20200200
 Test Date: 1/8/2020

FUEL TANK CAPACITY

Description	Liters
Usable Capacity of "Standard Tank"	59.4
Usable Capacity of "Optional Tank"	N/A
92%-94% of Usable Capacity	54.6 – 55.8
Actual Amount of Solvent Used	55.2
1/3 of Usable Capacity	19.5


FUEL PUMP

The vehicle is equipped with an electric fuel pump. The fuel filler neck is on the left side of the vehicle. The pump creates positive pressure in the fuel lines, pushing the gasoline to the engine. See form 1 for more information.



STEERING COLUMN ADJUSTMENT

Steering wheel and column adjustments are made so that the steering wheel hub is at the geometric center of the locus it describes when moved through its full range of motion. For angular measurements, a digital inclinometer was used to measure a plate which was placed across the steering wheel rim. A tape measure was used to measure the telescoping steering wheel travel.



STEERING COLUMN ASSEMBLY


STEERING COLUMN POSITIONS

Description	Degrees	Fore / Aft Position (mm)
Lowermost position No. 1	22.1	
Geometric center position No. 2	24.4	
Uppermost position No. 3	26.7	
Telescoping Steering Wheel Travel		55
Test Position	24.4	27.5

DATA SHEET NO. 3 DUMMY LONGITUDINAL CLEARANCE DIMENSIONS

Test Vehicle: 2020 Ford Escape four door SUV
Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20200200
Test Date: 1/8/2020




Left Side View

Code	Measurement Description	Driver (SN: 142)		Passenger (SN: 140)	
		Length (mm)	Angle (°)	Length (mm)	Angle (°)
WA°	Windshield Angle		28.7		
SWA°	Steering Wheel Angle		24.6		
SCA°	Steering Column Angle		65.4		
SA°	Seat Back Angle (on headrest post)		3.1		0.5
HZ	Head to Roof (Z)	230	90	234	90
HH	Head to Header	358	29.9	294	57.8
HW	Head to Windshield	697	0	635	0
NR	Nose to Rim / Dash	402	11.7	416	26.9
CD	Chest to Dash	526		361	
CS	Chest to Steering Hub	315	1.9		
RA	Rim to Abdomen	185	0		
KDL	Left Knee to Dash	200	20.1	88	28.8
KDR	Right Knee to Dash	206	8.2	94	27.4
PA°	Pelvic Angle		24.1		20.1
TA°	Tibia Angle		40.6		62.3
SK	Striker to Knee	567	4.8	701	5.0
ST	Striker to Head	534	80.4	524	60.1
SH	Striker to H-Point	257	37.3	386	19.2

DATA SHEET NO. 4
DUMMY LATERAL CLEARANCE DIMENSIONS

Test Vehicle: 2020 Ford Escape four door SUV
 Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20200200
 Test Date: 1/8/2020




Front View

Code	Description	Driver (mm)	Passenger (mm)
AD	Arm to Door	117	75
HD	H-Point to Door	143	174
HR	Head to Side Header	254	281
HS	Head to Side Window	370	402
KK	Knee to Knee	345	210
SHY	Striker to H-Point (Y Direction)	230	245
AA	Ankle to Ankle	338	163

DATA SHEET NO. 5 SEAT BELT POSITIONING DATA

Test Vehicle: 2020 Ford Escape four door SUV
 Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20200200
 Test Date: 1/8/2020



SEAT BELT POSITIONING MEASUREMENTS

Measurement Description	Units	Driver	Passenger
PBU — Top surface of reference to belt upper edge	mm	365	275
PBL — Top surface of reference to belt lower edge	mm	290	200

BELT LENGTH DATA


Measurement Description	Units	Driver	Passenger
Shoulder belt length as measured on ATD	mm	815	910
Lap Belt Length as measured on ATD	mm	675	800
Remainder of belt on reel	mm	910	690
Total belt length for continuous webbing systems	mm	2400	2400

DATA SHEET NO. 6
HIGH-SPEED CAMERA LOCATIONS AND DATA

Test Vehicle: 2020 Ford Escape four door SUV
Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20200200
Test Date: 1/8/2020

CAMERA POSITIONS FOR FRONTAL IMPACTS



DATA SHEET NO. 6 ... (CONTINUED)
HIGH-SPEED CAMERA LOCATIONS AND DATA

Test Vehicle: 2020 Ford Escape four door SUV
 Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20200200
 Test Date: 1/8/2020

CAMERA LOCATIONS


No.	Camera View	Location (mm)			Lens (mm)	Speed (fps)
		X	Y	Z		
1	Real-Time Left Overall	-	-	-		60
2	Left Overall	-1904	-6549	-1308	24	1000
3	Driver Close-Up	-1338	-7135	-1404	50	1000
4	Left Front Half	-837	-6225	-1262	28	1000
5	Left Angle	-4832	-3599	-1828	50	1000
6	Steering Column	-1338	-7360	-1976	50	1000
7	Right Overall	-1823	6798	-1324	24	1000
8	Passenger Close-Up	-1291	6591	-1405	50	1000
9	Right Front Half	-824	6469	-1163	28	1000
10	Right Angle	-4832	3590	-1813	50	1000
11	Windshield	1184	0	-3514	12.5	1000
12	Driver Windshield	780	-463	-2327	25	1000
13	Passenger Windshield	780	463	-2327	25	1000
14	Pit Front	-665	0	2627	12.5	1000
15	Pit Rear	-2203	0	2557	12.5	1000
16	Onboard Driver Airbag (Optional)				8	1000
17	Onboard Passenger Airbag (Optional)				8	1000

* COORDINATES: +X = forward of impact plane
 +Y = right of monorail center
 +Z = into ground

DATA SHEET NO. 7 **VEHICLE ACCELEROMETER LOCATIONS**

Test Vehicle: 2020 Ford Escape four door SUV
 Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20200200
 Test Date: 1/8/2020



VEHICLE ACCELEROMETER PRE-TEST LOCATIONS

No.	Accelerometer Location	Measurements (mm)		
		X	Y	Z
1	Left Rear Accelerometer – X Direction	1742	-373	198
2	Right Rear Accelerometer – X Direction	1748	405	204
3	Engine Top X	3677	111	-289
4	Engine Bottom X	3656	411	130
5	Left Rear Accelerometer – Z Direction	1742	-373	198
6	Right Rear Accelerometer – Z Direction	1748	405	204
7	Left Rear Accelerometer – X Direction Redundant	1742	-373	199
8	Right Rear Accelerometer – X Direction Redundant	1748	403	210

Reference Points: *X – Rear Surface of Vehicle (+ forward)*
 Y – Vehicle Centerline (+ to right)
 Z – Ground Plane (+ down)


DATA SHEET NO. 8 **PHOTOGRAPHIC REFERENCE TARGET LOCATIONS**

Test Vehicle: 2020 Ford Escape four door SUV
 Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20200200
 Test Date: 1/8/2020

Item	Value
A	367
B	904
C	2567
D	610
E	1413
F	185
G	1800
H	662
I	1447
J	883
K	890
L	1370
M	661
N	1372
O	889
P	884
Q	1444

All units in millimeters



DATA SHEET NO. 9 **LOAD CELL LOCATIONS ON FIXED BARRIER**

Test Vehicle: 2020 Ford Escape four door SUV
 Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20200200
 Test Date: 1/8/2020




Figure 1 - Load Cell Locations on a 128-Load Cell Barrier with Plywood Height Extension*
 Please note above diagram is not actual representation of load cell barrier used.

DATA SHEET NO. 10
TEST VEHICLE SUMMARY OF RESULTS

Test Vehicle: 2020 Ford Escape four door SUV
Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20200200
Test Date: 1/8/2020

INSTRUMENTATION

Instrumentation	Number of Channels Collected
Driver Dummy Accelerometers	47
Passenger Dummy Accelerometers	47
Vehicle Structure Accelerometers	8
Load Cell Barrier	384
Total	486

CAMERA COVERAGE

Type of Camera	Number Used in this Test
High-Speed Vehicle Onboard	2
High-Speed Offboard	14
Real-Time Panning	1
Total	17

**DATA SHEET NO. 11
POST-TEST OBSERVATIONS**

Test Vehicle: 2020 Ford Escape four door SUV
Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20200200
Test Date: 1/8/2020

TEST DUMMY INFORMATION AND CONTACT LOCATIONS

Description	Driver	Passenger
Dummy Type / Serial No.	P572E 50 th Male / 142	P5720 5 th Female / 140
Head Contact	Front Airbag, Headrest	Front Airbag, Headrest
Upper Torso Contact	Front Airbag	Front Airbag
Lower Torso Contact	None	None
Left Knee Contact	Knee Airbag	Glove Box
Right Knee Contact	Knee Airbag	Glove Box

DOOR OPENING AND SEAT TRACK INFORMATION

Description	Driver	Passenger	Other
Locked / Unlocked Doors	Unlocked	Unlocked	
Front Door Opening	Closed & Operational	Closed & Operational	
Rear Door Opening	Closed & Operational	Closed & Operational	
Trunk/Hatch/Tailgate Opening			Operational
Seat Track Shift (mm)	0	0	
Seat Back Movement from Initial Position	No	No	

**NOTE: Indicate "No", "N/A, or "Yes" described

POST-TEST STRUCTURAL OBSERVATIONS

Critical Areas of Performance	Observations and Conclusions
Windshield Damage	None
Window Damage	None
Other	None

VEHICLE REBOUND FROM BARRIER

Measured Parameter	Units	Value
Left Side	mm	823
Center	mm	859
Right Side	mm	1002
Average	mm	895


SUPPLEMENTAL RESTRAINT SYSTEM INFORMATION

Restraint Type	Driver		Passenger	
	Installed	Deployed	Installed	Deployed
Front Airbag	Yes	Yes	Yes	Yes
Side Airbag 1 - Curtain	Yes	No	Yes	No
Side Airbag 2 - Torso/Pelvis Airbag	Yes	No	Yes	No
Knee Airbag	Yes	Yes	No	N/A
Seat Belt Pretensioner	Yes	Yes	Yes	Yes
Seat Belt Load Limiter	Yes	Yes	Yes	Yes
Other				

DATA SHEET NO. 12 **VEHICLE PROFILE MEASUREMENTS**

Test Vehicle: 2020 Ford Escape four door SUV
 Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20200200
 Test Date: 1/8/2020



DATA SHEET NO. 12 ... (CONTINUED)
VEHICLE PROFILE MEASUREMENTS

Test Vehicle: 2020 Ford Escape four door SUV
 Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20200200
 Test Date: 1/8/2020

No.	Measurement Description	Pre-Test	Post-Test	Difference
1	Total Length of Vehicle at Centerline	4590	4345	-245
2	Rear Surface of Vehicle (RSOV) to Front of Engine	3919	3726	-193
3	RSOV to Firewall	3393	3353	-40
4	RSOV to Upper Leading Edge of Right Door	3158	3157	-1
5	RSOV to Upper Leading Edge of Left Door	3154	3155	1
6	RSOV to Lower Leading Edge of Right Door	3060	3060	0
7	RSOV to Lower Leading Edge of Left Door	3046	3045	-1
8	RSOV to Upper Trailing Edge of Right Door	2032	2034	2
9	RSOV to Upper Trailing Edge of Left Door	2030	2032	2
10	RSOV to Lower Trailing Edge of Right Door	2067	2068	1
11	RSOV to Lower Trailing Edge of Left Door	2063	2065	2
12	RSOV to Bottom of "A" Post of Right Side	3111	3109	-2
13	RSOV to Bottom of "A" Post of Left Side	3111	3108	-3
14	RSOV to Firewall, Right Side	3369	3354	-15
15	RSOV to Firewall, Left Side	3378	3349	-29
16	RSOV to Steering Column	2639	2690	51
17	Center of Steering Column to "A" Post	302	306	4
18	Center of Steering Column to Headliner	434	461	27
19	RSOV to Right Side of Front Bumper	4505	4172	-333
20	RSOV to Left Side of Front Bumper	4506	4364	-142
21	Length of Engine Block	269	269	0
RD	RSOV to Right Side of Dash Panel	2850	2850	0
CD	RSOV to Center of Dash Panel	2780	2786	6
LD	RSOV to Left Side of Dash Panel	2837	2839	2

*UR= Unrecoverable data point
 All Dimensions in mm

DATA SHEET NO. 13
ACCIDENT INVESTIGATION DIVISION DATA

Test Vehicle: 2020 Ford Escape four door SUV
Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20200200
Test Date: 1/8/2020


VEHICLE INFORMATION

VIN: 1FMCU9G66LUA20567
Vehicle Size Category: MPV

Wheelbase (mm): 2709
Test Weight (kg): 1809

ACCELEROMETER DATA

Accelerometer Locations: Please See Data Sheet No. 7
Cal. Procedure / Interval: Calspan Procedure / 6 month
Integration Algorithm: Trapezoidal
Linearity: > 99%
Impact Velocity (km/h): 56.26
Velocity Change (km/h): 63.65
Time of Separation (ms): 142



CRUSH PROFILE

Collision Deformation Classification: 12FDEW2
Midpoint of Damage: C3
Damage Region Length (mm): 1353
Impact Mode: Frontal

No.	Measurement Description	Units	Pre-Test	Post-Test	Difference
C1	Crush Zone 1 at Left Side	mm	4399	4214	185
C2	Crush Zone 2 at Left Side	mm	4531	4186	345
C3	Crush Zone 3 at Left Side	mm	4574	4221	353
C4	Crush Zone 4 at Right Side	mm	4572	4228	344
C5	Crush Zone 5 at Right Side	mm	4528	4195	333
C6	Crush Zone 6 at Right Side	mm	4387	4201	186
L	C1 to C6	mm	1353	1345	8

DATA SHEET NO. 14
VEHICLE INTRUSION MEASUREMENTS

Test Vehicle: 2020 Ford Escape four door SUV
Test Program: NCAP Frontal Barrier Impact Test


NHTSA No.: M20200200
Test Date: 1/8/2020

DOOR OPENING WIDTH

Item	Description	Units	Pre-Test	Post-Test	Difference
A	Left Side Upper	mm	956	956	0
B	Left Side Lower	mm	833	832	-1
D	Right Side Upper	mm	957	956	-1
E	Right Side Lower	mm	846	846	0

WHEELBASE MEASUREMENTS

Item	Description	Units	Pre-Test	Post-Test	Difference
C	Left Side Wheelbase	mm	2709	2623	-86
F	Right Side Wheelbase	mm	2709	2564	-145



Left & Right Side Views

DATA SHEET NO.14 ... (CONTINUED)
VEHICLE INTRUSION MEASUREMENTS


Test Vehicle: 2020 Ford Escape four door SUV
 Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20200200
 Test Date: 1/8/2020

DRIVER COMPARTMENT INTRUSION

Item	Description	Units	Pre-Test	Post-Test	Difference
AB	Door Opening (Inside Window Jam)	mm	749	748	-1
CX	Left Knee Bolster to X	mm	373	379	6
DX	Right Knee Bolster to X	mm	374	380	6
EX	Brake Pedal to X	mm	555	535	-20
FX	Foot Rest to X	mm	581	579	-2
GX	Center of Steering Column Wheel Hub to X	mm	77	130	53

X = Front of Seat Track (Stationary)



DATA SHEET NO. 15
SUMMARY OF FMVSS 212, 219 (PARTIAL), AND 301 DATA

Test Vehicle: 2020 Ford Escape four door SUV
 Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20200200
 Test Date: 1/8/2020


Windshield Mounting Details: A 0.8 mm trim surrounds the top and side of windshield while a plastic shroud is on the bottom.

The standard requires that the post-test retention measurement be a minimum of 75% of the pre-test total periphery measurement for vehicles not equipped with occupant passive restraints and 50% for each side of the windshield for vehicles which are equipped with occupant passive restraints.

Temperature of windshield molding during test: 21 ° C

WINDSHIELD PERIPHERY MEASUREMENTS

Measurement	Pre-Test (mm)	Post-Test (mm)	% Retention
Left Side	2349.5	2349.5	100
Right Side	2349.5	2349.5	100
Total	4699	4699	100



Item	Units	Value
A	mm	1354
B	mm	482
C	mm	1557
D	mm	894
E	mm	533
F	mm	591

AREAS OF PROTECTED ZONE FAILURES

A. *Provide coordinates of the area that the protected zone was penetrated more than .25 inches by a vehicle component other than one that is normally in contact with the windshield.*

- No Penetration

X	Y

B. *Provide coordinates of the area beneath the protected zone that the inner surface of the windshield was penetrated by a vehicle component.*

- No Penetration

X	Y

DATA SHEET NO. 15 ... (CONTINUED)
SUMMARY OF FMVSS 212, 219 (PARTIAL), AND 301 DATA

Test Vehicle: 2020 Ford Escape four door SUV
Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20200200
Test Date: 1/8/2020

FMVSS 301 FUEL SYSTEM INTEGRITY POST IMPACT DATA

Temperature at Time of Impact: 21 ° C

Test Time: 10:47 AM


STODDARD SOLVENT SPILLAGE MEASUREMENTS

- A. From impact until vehicle motion ceases: 0 oz.
(Maximum allowable is 1 oz.)
- B. For the 5-minute period after motion ceases: 0 oz.
(Maximum allowable is 5 oz.)
- C. For the following 25 minutes: 0 oz.
(Maximum allowable is 1 oz./minute)
- D. Spillage: No Spillage Occurred

DATA SHEET NO. 16
FMVSS 301 STATIC ROLLOVER RESULTS

Test Vehicle: 2020 Ford Escape four door SUV
 Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20200200
 Test Date: 1/8/2020



1. The specified fixture rollover rate for each 90° of rotation is 60 to 180 seconds.
2. The position hold time at each position is 300 seconds (minimum).
3. Details of Stoddard Solvent Spillage: No Spillage Occurred

SOLVENT COLLECTION TIME TABLE IN SECONDS

Test Phase	Rotation Time	Hold Time	Total Time
0° to 90°	68	300	368
90° to 180°	66	300	366
180° to 270°	67	300	367
270° to 360°	68	300	368

FMVSS 301 SPILLAGE TABLE

Test Phase	First 5 Minutes	Sixth Minute	Seventh Minute	Eighth Minute
0° to 90°	0	0	0	
90° to 180°	0	0	0	
180° to 270°	0	0	0	
270° to 360°	0	0	0	


SOLVENT SPILLAGE LOCATION TABLE

Test Phase	Spillage Location
0° to 90°	None
90° to 180°	None
180° to 270°	None
270° to 360°	None

DATA SHEET NO. 17
DUMMY / VEHICLE TEMPERATURE STABILIZATION CHART

Test Vehicle: 2020 Ford Escape four door SUV
 Test Program: NCAP Frontal Barrier Impact Test

NHTSA No.: M20200200
 Test Date: 1/8/2020



Temperature and Humidity Stabilization Chart/Data for Dummies and Test Vehicle

APPENDIX A
PHOTOGRAPHS

TABLE OF PHOTOGRAPHS

Fig.	Description	Page
1	Load Cell Location	A-5
2	Pre-Test Load Cell Wall	A-5
3	Post-Test Load Cell Wall	A-6
4	Manufacturer's Label	A-6
5	Tire Placard	A-7
6	2020 Ford Escape Frontal As Delivered	A-7
7	Left Rear 3-4 View, as Received	A-8
8	Pre-Test Front View of Test Vehicle	A-8
9	Post-Test Front View of Test Vehicle	A-9
10	Pre-Test Left View of Test Vehicle	A-9
11	Post-Test Left View of Test Vehicle	A-10
12	Pre-Test Right View of Test Vehicle	A-10
13	Post-Test Right View of Test Vehicle	A-11
14	Pre-Test Right Front 3-4 View	A-11
15	Post-Test Right Front 3-4 View	A-12
16	Pre-Test Left Rear 3-4 View	A-12
17	Post-Test Left Rear 3-4 View	A-13
18	Pre-Test Windshield View	A-13
19	Post-Test Windshield View	A-14
20	Pre-Test Engine Compartment View	A-14
21	Post-Test Engine Compartment View	A-15
22	Pre-Test Fuel Filler Cap View	A-15
23	Post-Test Fuel Filler Cap View	A-16
24	Pre-Test Front Underbody View ¹	A-16
25	Post-Test Front Underbody View ¹	A-17
26	Pre-Test Rear Underbody View ¹	A-17
27	Post-Test Rear Underbody View ¹	A-18
28	Pre-Test Dummy Cable Routing	A-18
29	Post-Test Dummy Cable Routing	A-19
30	Pre-Test Driver Dummy Front View	A-19
31	Post-Test Driver Dummy Front View	A-20
32	Pre-Test Driver Dummy Window View	A-20
33	Post-Test Driver Dummy Window View	A-21
34	Pre-Test Driver Dummy and Vehicle Interior View	A-21
35	Post-Test Driver Dummy and Vehicle Interior View	A-22

Fig.	Description	Page
36	Pre-Test Driver's Seat Fore-Aft Markings	A-22
37	Post-Test Driver's Seat Fore-Aft Markings	A-23
38	Pre-Test View of Belt Anchorage for Driver Dummy	A-23
39	Post-Test View of Belt Anchorage for Driver Dummy	A-24
40	Pre-Test View of Belt Buckle and Latch Plate for Driver Dummy	A-24
41	Post-Test View of Belt Buckle and Latch Plate for Driver Dummy	A-25
42	Pre-Test Driver Dummy Feet	A-25
43	Post-Test Driver Dummy Feet	A-26
44	Pre-Test Driver's Side Knee Bolster	A-26
45	Post-Test Driver's Side Knee Bolster	A-27
46	Pre-Test Driver's Side Floorpan	A-27
47	Post-Test Driver's Side Floorpan	A-28
48	Post-Test Driver Dummy Face	A-28
49	Post-Test Driver Dummy Contact With Airbag	A-29
50	Post-Test Driver Dummy Contact With Headrest	A-29
51	Pre-Test View of the Steering Wheel	A-30
52	Post-Test View of the Steering Wheel	A-30
53	Pre-Test Passenger Dummy Front View	A-31
54	Post-Test Passenger Dummy Front View	A-31
55	Pre-Test Passenger Dummy Window View	A-32
56	Post-Test Passenger Dummy Window View	A-32
57	Pre-Test Passenger Dummy and Vehicle Interior View	A-33
58	Post-Test Passenger Dummy and Vehicle Interior View	A-33
59	Pre-Test Passenger's Seat Fore-Aft Markings	A-34
60	Post-Test Passenger's Seat Fore-Aft Markings	A-34
61	Pre-Test View of Belt Anchorage for Passenger Dummy	A-35
62	Post-Test View of Belt Anchorage for Passenger Dummy	A-35
63	Pre-Test View of Belt Buckle and Latch Plate for Passenger Dummy	A-36
64	Post-Test View of Belt Buckle and Latch Plate for Passenger Dummy	A-36
65	Pre-Test Passenger Dummy Feet	A-37
66	Post-Test Passenger Dummy Feet	A-37
67	Pre-Test Passenger's Side Knee Bolster	A-38
68	Post-Test Passenger's Side Knee Bolster	A-38
69	Pre-Test Passenger's Side Floorpan	A-39
70	Post-Test Passenger's Side Floorpan	A-39
71	Post-Test Passenger Dummy Face	A-40

Fig.	Description	Page
72	Post-Test Passenger Dummy Contact With Airbag	A-40
73	Post-Test Passenger Dummy Contact With Headrest	A-41
74	Photograph of Ballast Installed in Vehicle	A-41
75	Post-Test Stoddard Solvent Spillage Location View, if Required	A-42
76	Post-Test Speed Trap Read-Out	A-42
77	Vehicle at 0° on Static Rollover Device	A-43
78	Vehicle at 90° on Static Rollover Device	A-43
79	Vehicle at 180° on Static Rollover Device	A-44
80	Vehicle at 270° on Static Rollover Device	A-44
81	Vehicle at 360° on Static Rollover Device	A-45
82	2020 Ford Escape Frontal Impact Event	A-45
83	Monroney Label Photograph	A-46

¹**NOTE:** *The underbody views should include the following vehicle components: fuel pump, fuel lines, sender unit, fuel tank filler pipe and any other visible system components.*



Figure A-1: Load Cell Location



Figure A-2: Pre-Test Load Cell Wall



Figure A-3: Post-Test Load Cell Wall



Figure A-4: Manufacturer's Label




Figure A-5: Tire Placard



Figure A-6: 2020 Ford Escape Frontal As Delivered



M20200200

Figure A-7: Left Rear 3-4 View, As Received



Figure A-8: Pre-Test Front View of Test Vehicle



Figure A-9: Post-Test Front View of Test Vehicle



Figure A-10: Pre-Test Left View of Test Vehicle



Figure A-11: Post-Test Left View of Test Vehicle



Figure A-12: Pre-Test Right View of Test Vehicle




Figure A-13: Post-Test Right View of Test Vehicle



Figure A-14: Pre-Test Right Front 3-4 View



Figure A-15: Post-Test Right Front 3-4 View



Figure A-16: Pre-Test Left Rear 3-4 View



Figure A-17: Post-Test Left Rear 3-4 View



Figure A-18: Pre-Test Windshield View



Figure A-19: Post-Test Windshield View



Figure A-20: Pre-Test Engine Compartment View




Figure A-21: Post-Test Engine Compartment View



Figure A-22: Pre-Test Fuel Filler Cap View



Figure A-23: Post-Test Fuel Filler Cap View



Figure A-24: Pre-Test Front Underbody View



Figure A-25: Post-Test Front Underbody View




Figure A-26: Pre-Test Rear Underbody View




Figure A-27: Post-Test Rear Underbody View



Figure A-28: Pre-Test Dummy Cable Routing



Figure A-29: Post-Test Dummy Cable Routing



Figure A-30: Pre-Test Driver Dummy Front View



Figure A-31: Post-Test Driver Dummy Front View



Figure A-32: Pre-Test Driver Dummy Window View



Figure A-33: Post-Test Driver Dummy Window View



Figure A-34: Pre-Test Driver Dummy and Vehicle Interior View



Figure A-35: Post-Test Driver Dummy and Vehicle Interior View



Figure A-36: Pre-Test Driver's Seat Fore-Aft Markings



Figure A-37: Post-Test Driver's Seat Fore-Aft Markings




Figure A-38: Pre-Test View of Belt Anchorage for Driver Dummy




Figure A-39: Post-Test View of Belt Anchorage for Driver Dummy



Figure A-40: Pre-Test View of Belt Buckle and Latch Plate for Driver Dummy



Figure A-41: Post-Test View of Belt Buckle and Latch Plate for Driver Dummy



Figure A-42: Pre-Test Driver Dummy Feet



Figure A-43: Post-Test Driver Dummy Feet




Figure A-44: Pre-Test Driver's Side Knee Bolster



Figure A-45: Post-Test Driver's Side Knee Bolster



Figure A-46: Pre-Test Driver's Side Floorpan



Figure A-47: Post-Test Driver's Side Floorpan



Figure A-48: Post-Test Driver Dummy Face




Figure A-49: Post-Test Driver Dummy Contact With Airbag



Figure A-50: Post-Test Driver Dummy Contact With Headrest



Figure A-51: Pre-Test View of the Steering Wheel



Figure A-52: Post-Test View of the Steering Wheel



Figure A-53: Pre-Test Passenger Dummy Front View



Figure A-54: Post-Test Passenger Dummy Front View



Figure A-55: Pre-Test Passenger Dummy Window View



Figure A-56: Post-Test Passenger Dummy Window View



Figure A-57: Pre-Test Passenger Dummy and Vehicle Interior View



Figure A-58: Post-Test Passenger Dummy and Vehicle Interior View



Figure A-59: Pre-Test Passenger's Seat Fore-Aft Markings



Figure A-60: Post-Test Passenger's Seat Fore-Aft Markings




Figure A-61: Pre-Test View of Belt Anchorage for Passenger Dummy




Figure A-62: Post-Test View of Belt Anchorage for Passenger Dummy



Figure A-63: Pre-Test View of Belt Buckle and Latch Plate for Passenger Dummy



Figure A-64: Post-Test View of Belt Buckle and Latch Plate for Passenger Dummy



Figure A-65: Pre-Test Passenger Dummy Feet



Figure A-66: Post-Test Passenger Dummy Feet



Figure A-67: Pre-Test Passenger's Side Knee Bolster



Figure A-68: Post-Test Passenger's Side Knee Bolster



Figure A-69: Pre-Test Passenger's Side Floorpan



Figure A-70: Post-Test Passenger's Side Floorpan



Figure A-71: Post-Test Passenger Dummy Face



Figure A-72: Post-Test Passenger Dummy Contact With Airbag



Figure A-73: Post-Test Passenger Dummy Contact With Headrest




Figure A-74: Photograph of Ballast Installed in Vehicle

Photo Not Applicable

Figure A-75: Post-Test Stoddard Solvent Spillage Location View, If Required



Figure A-76: Post-Test Speed Trap Read-Out




Figure A-77: Vehicle at 0° on Static Rollover Device



Figure A-78: Vehicle at 90° on Static Rollover Device



Figure A-79: Vehicle at 180° on Static Rollover Device



Figure A-80: Vehicle at 270° on Static Rollover Device




Figure A-81: Vehicle at 360° on Static Rollover Device



Figure A-82: 2020 Ford Escape Frontal Impact Event



 VEHICLE DESCRIPTION ESCAPE AWD 2020 ESCAPE SE AWD 106.7" WHEELBASE 1.5L ECOBOOST W/START-STOP 8-SPD AUTO TRANSMISSION ford.com		LU A20567 EXTERIOR INGOET SILVER METALLIC INTERIOR DARK EARTH GRAY CLOTH SEATS		EPA DOT Fuel Economy and Environment Gasoline Vehicle
STANDARD EQUIPMENT INCLUDED AT NO EXTRA CHARGE				Fuel Economy 28 MPG combined city/hwy 26 city 31 highway 3.6 gallons per 100 miles Small SUVs range from 18 to 120 MPG. The best vehicle rates 138 MPG.
EXTERIOR • ACTIVE GRILLE SHUTTERS • DOOR HANDLES - BODY COLOR • DUAL EXHAUST CHROME TIPS • EASY FUELS CAPLESS FILLER • HEADLAMP COURTESY DELAY • HEADLAMPS - AUTO HALOGEN • LED SIGNATURE LIGHTING • MIRRORS - HTD/POWER GLASS, MANUAL FOLD • PRIVACY GLASS - REAR DOORS • REAR INT WIPER/WASH/DPST • REAR SPOILER • TAILLAMPS-LED				You Save \$250 in fuel costs over 5 years compared to the average new vehicle.
INTERIOR • 1-TOUCH DOWN DRIVER WINDOW • CARPETED FLOOR MATS • DUAL ILLUM VIS VANITY MIRR • ELECTRONIC AUTO TEMP CTRL • HTD FRT SEATS - 10-WAY PWR • 4-WAY MANUAL PASS • ILLUMINATED ENTRY SYSTEM • POWERPOINTS • ROTARY GEAR SHIFT DIAL • SMART CHARGING USB PORT(2) • SPLIT FOLD/SLIDE REAR SEAT • STEERING TL/TELESCOPE, CRUISE & AUDIO CONTROLS				Annual fuel cost \$1,450 Fuel Economy & Greenhouse Gas Rating (passenger only) 6 Smog Rating (passenger only) 7 (This vehicle emits 210 grams CO ₂ per mile. The best emits 0 grams per mile (tailpipe only). Producing and distributing fuel also create emissions. Learn more at fueleconomy.gov)
FUNCTIONAL • AM/FM/MP3 & SPEAKERS • AUTO START STOP TECH • ELECTRIC PARKING BRAKE • FORD CO-PILOT360™ • FORDPASS™ CONNECT 4G-WIFI • HOTSPOT TELEMATICS MODEM • INTELLIGENT ACCESS W/UNLCK • LATCH CHILD SAFETY SYSTEM • REAR VIEW CAMERA • SECURICODE KEYLESS KEYPAD • SIRSUXMB - SVC IVA AKAH • SYNC3 8" SCRN W/APPLINKS				SAFETY/SECURITY • ADVANCETRAC® WITH RSC® • AIRBAG - DRIVER KNEE • AIRBAGS - DUAL STAGE FRONT • AIRBAGS - FRONT SEAT MOUNTED SIDE IMPACT • AIRBAGS - SAFETY CANOPY® • LATCH CHILD SAFETY SYSTEM • PERSONAL SAFETY SYSTEM™ • SOS POST-CRASH ALERT SYS™ • TIRE PRESSURE MONIT SYS WARRANTY • 3YR/36,000 BUMPER / BUMPER • 5YR/60,000 POWERTRAIN • 5YR/60,000 ROADSIDE ASSIST
INCLUDED ON THIS VEHICLE EQUIPMENT GROUP 300A 17" SHOW SILVER-PINTD ALUM WHEEL 225/55R17 102H A/S BSWG TIRES EASY ACCESS CARDO SHADE FORD CO-PILOT360 ASSIST VOICE-ACTV TOUCH SCR NAV SYS ADAPTIVE CRUISE W/STOP AND GO FRONT LICENSE PLATE BRACKET NO CHARGE		PRICE INFORMATION BASE PRICE \$28,595.00 TOTAL OPTIONS/OTHER 830.00 TOTAL VEHICLE & OPTIONS/OTHER 29,425.00 DESTINATION & DELIVERY 1,195.00 TOTAL MSRP \$30,620.00		
SOLD TO Pamela's Ford 2472 Corning Road Elmira NY 14903		SHIP TO (IF OTHER THAN SOLD TO) SHIP THROUGH		
13V 529 CS18		FINAL ASSEMBLY PLANT LOUISVILLE METHOD OF TRAMP CONVOY ITEM # 13-2901 O/T 2		
Whether you decide to lease or finance your vehicle, you'll find the choices that are right for you. See your dealer for details or visit www.ford.com/finance.		1FMCU9G66LUA20567  WARNING: Operating, servicing and maintaining a passenger vehicle, pickup truck, van, or off-road vehicle can expose you to chemicals including engine exhaust, carbon monoxide, phthalates, and lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. To minimize exposure, avoid breathing exhaust, do not idle the engine except as necessary, service your vehicle in a well-ventilated area and wear gloves or wash your hands frequently when servicing your vehicle. For more information go to www.P65Warnings.ca.gov/passenger-vehicle .		
SHIP THROUGH This label is affixed pursuant to the Federal Automobile Information Disclosure Act. Gasoline, License, and Title Fees, State and Local taxes are not included. Dealer installed options or accessories are not included unless listed above.		SHIP TO (IF OTHER THAN SOLD TO) SHIP THROUGH		

Figure A-83: Monroney Label Photograph

APPENDIX B
VEHICLE & DUMMY RESPONSE DATA TRACES

Table of Data Plots





No.	Description	Page
Plot 1	Driver Head X Acceleration vs. Time Primary	B-5
Plot 2	Driver Head Y Acceleration vs. Time Primary	B-5
Plot 3	Driver Head Z Acceleration vs. Time Primary	B-5
Plot 4	Driver Head Resultant Acceleration vs. Time Primary	B-5
Plot 5	Driver Chest X Deflection vs. Time	B-6
Plot 6	Driver Chest X Acceleration vs. Time Primary	B-6
Plot 7	Driver Chest Y Acceleration vs. Time Primary	B-6
Plot 8	Driver Chest Z Acceleration vs. Time Primary	B-6
Plot 9	Driver Chest Resultant Acceleration vs. Time Primary	B-7
Plot 10	Driver Upper Neck Force X vs. Time Primary	B-7
Plot 11	Driver Upper Neck Force Z vs. Time Primary	B-7
Plot 12	Driver Upper Neck Moment Y vs. Time Primary	B-7
Plot 13	Driver Nij vs. Time Primary	B-8
Plot 14	Driver Left Femur Force vs. Time	B-8
Plot 15	Driver Right Femur Force vs. Time	B-8
Plot 16	Passenger Head X Acceleration vs. Time Primary	B-8
Plot 17	Passenger Head Y Acceleration vs. Time Primary	B-9
Plot 18	Passenger Head Z Acceleration vs. Time Primary	B-9
Plot 19	Passenger Head Resultant Acceleration vs. Time Primary	B-9
Plot 20	Passenger Chest X Deflection vs. Time	B-9
Plot 21	Passenger Chest X Acceleration vs. Time Primary	B-10
Plot 22	Passenger Chest Y Acceleration vs. Time Primary	B-10
Plot 23	Passenger Chest Z Acceleration vs. Time Primary	B-10
Plot 24	Passenger Chest Resultant Acceleration vs. Time Primary	B-10
Plot 25	Passenger Upper Neck Force X vs. Time Primary	B-11
Plot 26	Passenger Upper Neck Force Z vs. Time Primary	B-11
Plot 27	Passenger Upper Neck Moment Y vs. Time Primary	B-11
Plot 28	Passenger Nij vs. Time Primary	B-11
Plot 29	Passenger Left Femur Force vs. Time	B-12
Plot 30	Passenger Right Femur Force vs. Time	B-12





The following additional dummy and vehicle response data can be found in the R&D section of the NHTSA website at www.nhtsa.gov





Driver Head X Acceleration Redundant
 Driver Head Y Acceleration Redundant
 Driver Head Z Acceleration Redundant
 Driver Upper Neck Force Y
 Driver Upper Neck Moment X
 Driver Upper Neck Moment Z
 Driver Chest X Acceleration Redundant
 Driver Chest Y Acceleration Redundant
 Driver Chest Z Acceleration Redundant
 Driver Pelvis X
 Driver Pelvis Y
 Driver Pelvis Z
 Driver Left Femur Redundant
 Driver Right Femur Redundant
 Driver Left Upper Tibia Moment X
 Driver Left Upper Tibia Moment Y





Driver Left Upper Tibia Force Z
Driver Left Lower Tibia Moment X
Driver Left Lower Tibia Moment Y
Driver Left Lower Tibia Force Z
Driver Right Upper Tibia Moment X
Driver Right Upper Tibia Moment Y
Driver Right Upper Tibia Force Z
Driver Right Lower Tibia Moment X
Driver Right Lower Tibia Moment Y
Driver Right Lower Tibia Force Z
Driver Left Foot Fore Z
Driver Left Foot Aft X
Driver Left Foot Aft Z
Driver Right Foot Fore Z
Driver Right Foot Aft X
Driver Right Foot Aft Z
Driver Shoulder Belt Force
Driver Lap Belt Force
Driver Head Angular Velocity X
Driver Head Angular Velocity Y
Driver Head Angular Velocity Z
Passenger Head X Acceleration Redundant
Passenger Head Y Acceleration Redundant
Passenger Head Z Acceleration Redundant
Passenger Upper Neck Force X
Passenger Upper Neck Force Z
Passenger Upper Neck Moment Y
Passenger Chest X Acceleration Redundant
Passenger Chest Y Acceleration Redundant
Passenger Chest Z Acceleration Redundant
Passenger Pelvis X
Passenger Pelvis Y
Passenger Pelvis Z
Passenger Left Femur Redundant
Passenger Right Femur Redundant
Passenger Left Upper Tibia Moment X
Passenger Left Upper Tibia Moment Y
Passenger Left Upper Tibia Force Z
Passenger Left Lower Tibia Moment X
Passenger Left Lower Tibia Moment Y
Passenger Left Lower Tibia Force Z
Passenger Right Upper Tibia Moment X
Passenger Right Upper Tibia Moment Y
Passenger Right Upper Tibia Force Z
Passenger Right Lower Tibia Moment X
Passenger Right Lower Tibia Moment Y
Passenger Right Lower Tibia Force Z
Passenger Left Foot Fore Z
Passenger Left Foot Aft X
Passenger Left Foot Aft Z





Passenger Right Foot Fore Z
Passenger Right Foot Aft X
Passenger Right Foot Aft Z
Passenger Shoulder Belt Force
Passenger Lap Belt Force
Passenger Head Angular Velocity X
Passenger Head Angular Velocity Y
Passenger Head Angular Velocity Z
Left Rear Seat Crossmember X
Left Rear Seat Crossmember Z
Right Rear Seat Crossmember X
Right Rear Seat Crossmember Z
Left Rear Seat Crossmember X Redundant
Right Rear Seat Crossmember X Redundant
Vehicle Engine Top X
Vehicle Engine Bottom X
Load Cell Barrier Forces and Moments

























Passenger Left Femur Force vs. Time



Passenger Right Femur Force vs. Time



APPENDIX C

DUMMY CALIBRATION AND PERFORMANCE VERIFICATION DATA

CALIBRATION TEST RESULTS

PRE-TEST

HYBRID III 50TH PERCENTILE MALE - DRIVER ATD

SERIAL NO: 142



Date: 12/04/2019

C-3


ATD Manufacturer	Humanetics	Test Technician	E. Helenbrook
ATD Serial Number	142	Laboratory Supervisor	K. Brogan




Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	°C	21.4	Pass
Humidity	10	70	%	31.1	Pass
Resultant Acceleration	225	275	g's	249.7	Pass
Oscillation	0	10	%	2.8	Pass
Lateral Acceleration	-15	15	g's	-2.9	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
X Accelerometer	Endevco	P51681	8/13/2019	2/13/2020
Y Accelerometer	Endevco	P64151	8/13/2019	2/13/2020
Z Accelerometer	Endevco	P52114	8/13/2019	2/13/2020







ATD Manufacturer	Humanetics	Test Technician	K. Dutton
ATD Serial Number	142	Laboratory Supervisor	K. Brogan




Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	20.6	22.2	°C	21.6	Pass
Humidity	10	70	%	24.3	Pass
Velocity	6.89	7.13	m/s	6.903	Pass
Pendulum Deceleration at 10ms	22.5	27.5	g's	23.18	Pass
Pendulum Deceleration at 20ms	17.6	22.6	g's	19.80	Pass
Pendulum Deceleration at 30ms	12.5	18.5	g's	15.95	Pass
Max. Pendulum Deceleration After 30ms	0	29	g's	24.1	Pass
Pendulum Deceleration Time to 5 g's	34	42	ms	40.3	Pass
Maximum D Plane Rotation	64	78	deg	66.3	Pass
Time to Maximum Rotation	57	64	ms	62.4	Pass
Rotation Decay to Zero	113	127	ms	116.7	Pass
Moment About Occipital Condyle	88.1	108.4	Nm	97.35	Pass
Time to Maximum Moment	47	58	ms	53.0	Pass
Moment Decay to Zero	97	107	ms	104.8	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	ENDEVCO 7231CT	AC-AH5M9 Pend	1/29/2019	1/29/2020
Pendulum Potentiometer	ETI SP22G	DS-LABPOT1	9/13/2019	9/12/2020
Condyle Potentiometer	ETI SP22G	DS-LABPOT2	9/13/2019	9/12/2020
Upper Neck Load Cell	Denton 1716	17162019 FX	2/18/2019	2/18/2020







ATD Manufacturer	Humanetics	Test Technician	K. Dutton
ATD Serial Number	142	Laboratory Supervisor	K. Brogan




Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	20.6	22.2	°C	21.6	Pass
Humidity	10	70	%	23.4	Pass
Velocity	5.94	6.19	m/s	5.964	Pass
Pendulum Deceleration at 10ms	17.2	21.2	g's	20.68	Pass
Pendulum Deceleration at 20ms	14	19	g's	18.0	Pass
Pendulum Deceleration at 30ms	11	16	g's	15.1	Pass
Max. Pendulum Deceleration After 30ms	0	22	g's	20.8	Pass
Pendulum Deceleration Time to 5 g's	38	46	ms	41.5	Pass
Maximum D Plane Rotation	81	106	deg	95.7	Pass
Time to Maximum Rotation	72	82	ms	74.4	Pass
Rotation Decay to Zero	147	174	ms	155.4	Pass
Minimum Moment About OC	-80	-52.9	Nm	-71.26	Pass
Time to Minimum Moment	65	79	ms	70.2	Pass
Moment Decay to Zero	120	148	ms	137.6	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	ENDEVCO 7231CT	AC-AH5M9 Pend	1/29/2019	1/29/2020
Pendulum Potentiometer	ETI SP22G	DS-LABPOT1	9/13/2019	9/12/2020
Condyle Potentiometer	ETI SP22G	DS-LABPOT2	9/13/2019	9/12/2020
Upper Neck Load Cell	Denton 1716	17162019 FX	2/18/2019	2/18/2020






ATD Manufacturer	Humanetics	Test Technician	E. Helenbrook
ATD Serial Number	142	Laboratory Supervisor	K. Brogan



Results



Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	20.6	22.2	°C	21.6	Pass
Humidity	10	70	%	39.7	Pass
Velocity	6.59	6.83	m/s	6.670	Pass
Chest Displacement	-72.6	-63.5	mm	-70.13	Pass
Resistive Force	5160	5894	N	5707.5	Pass
Hysteresis	65	85	%	70.0	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	Measurement Specialties	A260568	7/29/2019	7/29/2020
Chest Potentiometer	SERVO	DS-142	9/12/2019	9/12/2020








ATD Manufacturer	Humanetics	Test Technician	K. Dutton
ATD Serial Number	142	Laboratory Supervisor	K. Brogan

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	°C	21.5	Pass
Humidity	10	70	%	23.0	Pass
Average Velocity	5	10	deg/s	7.0	Pass
Angle at 203Nm	40	50	deg	43.3	Pass
Moment at 30 degrees	0	94.9	Nm	88.9	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Potentiometer	ETI SP22	DS-0008	2019-09-18	2020-09-17
Load Cell	Key Trans 2301-02	LC-115 My	2019-09-12	2020-09-11




ATD Manufacturer	Humanetics	Test Technician	K. Dutton
ATD Serial Number	142	Laboratory Supervisor	K. Brogan

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	°C	21.3	Pass
Humidity	10	70	%	24.0	Pass
Average Velocity	5	10	deg/s	7.0	Pass
Angle at 203Nm	40	50	deg	46.2	Pass
Moment at 30 degrees	0	94.9	Nm	86.0	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Potentiometer	ETI SP22	DS-0008	2019-09-18	2020-09-17
Load Cell	Key Trans 2301-02	LC-115 My	2019-09-12	2020-09-11




ATD Manufacturer	Humanetics	Test Technician	E. Helenbrook
ATD Serial Number	142	Laboratory Supervisor	K. Brogan



Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	°C	20.8	Pass
Humidity	10	70	%	29.3	Pass
Velocity	2.07	2.13	m/s	2.130	Pass
Maximum Resistive Force	4720	5780	N	5114.8	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	Endevco	A260568	7/29/2019	7/29/2020






ATD Manufacturer	Humanetics	Test Technician	E. Helenbrook
ATD Serial Number	142	Laboratory Supervisor	K. Brogan



Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	°C	20.8	Pass
Humidity	10	70	%	29.3	Pass
Velocity	2.07	2.13	m/s	2.071	Pass
Maximum Resistive Force	4720	5780	N	5326.2	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	Endevco	A260568	7/29/2019	7/29/2020





CALIBRATION TEST RESULTS

PRE-TEST

HYBRID III 5TH PERCENTILE - PASSENGER ATD

SERIAL NO: 140





External Measurements - Hybrid 3 - 5th Female

Technician: K. Brogan

Date: 11/18/2019

Dummy Serial Number: 140



Symbol	Description	Specification (mm)		Result (mm)	Pass/Fail
A	Sitting Height	775	800	791	Pass
B	Shoulder Pivot Height	432	457	442	Pass
C	H-Point Height	81	86	83	Pass
D	H-Point from Backline	145	150	147	Pass
E	Shoulder Pivot from Backline	69	84	75	Pass
F	Thigh Clearance	119	135	126	Pass
G	Back of Elbow to Wrist Pivot	244	259	250	Pass
H	Head Back to Backline	43	48	45	Pass
I	Shoulder to Elbow Length	277	297	290	Pass
J	Elbow Rest Height	183	203	194	Pass
K	Buttock to Knee Length	521	546	535	Pass
L	Popliteal Height	356	376	366	Pass
M	Knee Pivot Height	394	419	409	Pass
N	Buttock Popliteal Length	414	439	428	Pass
O	Chest Depth without Jacket	175	191	182	Pass
P	Foot Length (right)	219	234	228	Pass
R	Buttock To Knee Pivot Length	457	483	467	Pass
S	Head Breadth	137	147	142	Pass
T	Head Depth	178	188	180	Pass
U	Hip Breadth	300	315	313	Pass
V	Shoulder Breadth	351	366	361	Pass
W	Foot Breadth	79	94	83	Pass
X	Head Circumference	528	549	540	Pass
Y	Chest Circumference with Jacket	851	881	874	Pass
Z	Waist Circumference	460	790	624	Pass
AA	Reference Location (Chest Circumference)	333	358	345	Pass
BB	Reference Location (Waist Circumference)	160	170	165	Pass


ATD Manufacturer	Humanetics	Test Technician	E. Helenbrook
ATD Serial Number	140	Laboratory Supervisor	K. Brogan




Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	°C	21.5	Pass
Humidity	10	70	%	30	Pass
Resultant Acceleration	250	300	g's	255.1	Pass
Oscillation	0	10	%	2.6	Pass
Lateral Acceleration	-15	15	g's	-7.9	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
X Accelerometer	Endevco	P58998	9/30/2019	3/30/2020
Y Accelerometer	Endevco	P51722	9/30/2019	3/30/2020
Z Accelerometer	Endevco	P58997	9/30/2019	3/30/2020






ATD Manufacturer	Humanetics	Test Technician	M. Dudek
ATD Serial Number	140	Laboratory Supervisor	K. Brogan



Results


Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	20.6	22.2	°C	21.0	Pass
Humidity	10	70	%	31.0	Pass
Velocity	6.89	7.13	m/s	7.013	Pass
Pendulum Impulse at 10ms	2.1	2.5	m/s	2.35	Pass
Pendulum Impulse at 20ms	4.0	5.0	m/s	4.56	Pass
Pendulum Impulse at 30ms	5.8	7.0	m/s	6.42	Pass
Max D Plane Rotation	77	91	deg	86.5	Pass
Max Moment During Rotation Interval	69	83	Nm	77.1	Pass
Moment Decay to 10.0 Nm	80	100	ms	90.4	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	ENDEVCO 7231CT	AC-AH5M9 Pend	1/29/2019	1/29/2020
Pendulum Potentiometer	ETI SP22G	DS-LABPOT1	9/13/2019	9/12/2020
Condyle Potentiometer	ETI SP22G	DS-LABPOT2	9/13/2019	9/12/2020
Upper Neck Load Cell	DENTON 1716A	LC-2206Fx	2/18/2019	2/18/2020








ATD Manufacturer	Humanetics	Test Technician	M. Dudek
ATD Serial Number	140	Laboratory Supervisor	K. Brogan



Results


Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	20.6	22.2	°C	21.6	Pass
Humidity	10	70	%	30.0	Pass
Velocity	5.95	6.19	m/s	6.005	Pass
Pendulum Impulse at 10ms	1.5	1.9	m/s	1.74	Pass
Pendulum Impulse at 20ms	3.1	3.9	m/s	3.48	Pass
Pendulum Impulse at 30ms	4.6	5.6	m/s	5.04	Pass
D Plane Rotation	99	114	deg	107.5	Pass
Moment During Rotation Interval	-65	-53	Nm	-58.2	Pass
Moment Decay to -10Nm	94	114	ms	106.2	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	ENDEVCO 7231CT	AC-AH5M9 Pend	1/29/2019	1/29/2020
Pendulum Potentiometer	ETI SP22G	DS-LABPOT1	9/13/2019	9/12/2020
Condyle Potentiometer	ETI SP22G	DS-LABPOT2	9/13/2019	9/12/2020
Upper Neck Load Cell	DENTON 1716A	LC-2206Fx	2/18/2019	2/18/2020








ATD Manufacturer	Humanetics	Test Technician	D.Reinhard
ATD Serial Number	140	Laboratory Supervisor	K. Brogan



Results



Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	20.6	22.2	°C	20.8	Pass
Humidity	10	70	%	38	Pass
Velocity	6.59	6.83	m/s	6.655	Pass
Chest Deflection	-58	-50	mm	-51.1	Pass
Maximum Resistive Force (50 to 58mm)	3900	4400	N	4369.7	Pass
Maximum Resistive Force (18 to 50mm)	0	4600	N	4399.2	Pass
Hysteresis	69	85	%	74.4	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	MSI 64C-2000	A260487	8/22/2019	2/20/2020
Chest Potentiometer	SERVO 14CBI-3615	DS-140GFE	6/21/2019	6/20/2020








ATD Manufacturer	Humanetics	Test Technician	K. Dutton
ATD Serial Number	140	Laboratory Supervisor	K. Brogan

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.6	25.6	°C	21.4	Pass
Humidity	10	70	%	34	Pass
Initial Angle	0	20	deg	16.7	Pass
Force at 45 Degrees	320	390	N	376.4	Pass
Return Angle Relative to Initial	0	8	deg	2.2	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Potentiometer	Rieker N4C-1	DS-13051548	2018-11-25	2019-11-25
Load Cell	Interface SML-200	LC-493319	2018-11-25	2019-11-25




ATD Manufacturer	Humanetics	Test Technician	M. Dudek
ATD Serial Number	140	Laboratory Supervisor	K. Brogan



Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	°C	21.2	Pass
Humidity	10	70	%	34.0	Pass
Velocity	2.07	2.13	m/s	2.093	Pass
Resistive Force	3450	4060	N	3766.9	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	MSI	A260568	07/29/2019	01/29/2020






ATD Manufacturer	Humanetics	Test Technician	M. Dudek
ATD Serial Number	140	Laboratory Supervisor	K. Brogan



Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	°C	21.0	Pass
Humidity	10	70	%	34.2	Pass
Velocity	2.07	2.13	m/s	2.093	Pass
Resistive Force	3450	4060	N	3598.9	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	MSI	A260568	07/29/2019	01/29/2020





CALIBRATION TEST RESULTS

POST-TEST

HYBRID III 50TH PERCENTILE MALE - DRIVER ATD

SERIAL NO: 142




External Measurements - Hybrid 3 - 50th Male

Technician: K. Dutton

Date: 01/10/2020

Dummy Serial Number: 142



Symbol	Description	Specification (in)		Result (in)	Pass/Fail
A	Sitting Height	34.6	35.0	34.8	Pass
B	Shoulder Pivot Height	19.9	20.5	20.2	Pass
C	H-Point Height	3.3	3.5	3.4	Pass
D	H-Point from Backline	5.3	5.5	5.4	Pass
E	Shoulder Pivot from Backline	3.3	3.7	3.5	Pass
F	Thigh Clearance	5.5	6.1	5.8	Pass
G	Back of Elbow to Wrist Pivot	11.4	12.0	11.8	Pass
H	Head Back to Backline	1.6	1.8	1.7	Pass
I	Shoulder to Elbow Length	13.0	13.6	13.5	Pass
J	Elbow Rest Height	7.5	8.3	8.2	Pass
K	Buttock to Knee Length	22.8	23.8	23.4	Pass
L	Popliteal Height	16.9	17.9	17.3	Pass
M	Knee Pivot Height	19.1	19.7	19.5	Pass
N	Buttock Popliteal Length	17.8	18.8	18.4	Pass
O	Chest Depth without Jacket	8.4	9.0	8.7	Pass
P	Foot Length (right)	9.9	10.5	10.3	Pass
V	Shoulder Breadth	16.3	17.2	16.9	Pass
W	Foot Breadth	3.6	4.2	3.8	Pass
Y	Chest Circumference with Jacket	38.2	39.4	38.8	Pass
Z	Waist Circumference	32.9	34.1	33.7	Pass
AA	Reference Location (Chest Circumference)	16.9	17.1	17.0	Pass
BB	Reference Location (Waist Circumference)	8.9	9.1	9.0	Pass


ATD Manufacturer	Humanetics	Test Technician	K. Dutton
ATD Serial Number	142	Laboratory Supervisor	K. Brogan




Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	°C	22.0	Pass
Humidity	10	70	%	22.2	Pass
Resultant Acceleration	225	275	g's	261.3	Pass
Oscillation	0	10	%	2.5	Pass
Lateral Acceleration	-15	15	g's	-9.4	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
X Accelerometer	ENDEVCO 7264	P51681	8/13/2019	2/11/2020
Y Accelerometer	ENDEVCO 7264	P64151	8/13/2019	2/11/2020
Z Accelerometer	ENDEVCO 7264	P52114	8/13/2019	2/11/2020







ATD Manufacturer	Humanetics	Test Technician	K. Dutton
ATD Serial Number	142	Laboratory Supervisor	K. Brogan




Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	20.6	22.2	°C	21.5	Pass
Humidity	10	70	%	24.1	Pass
Velocity	6.89	7.13	m/s	6.958	Pass
Pendulum Deceleration at 10ms	22.5	27.5	g's	26.51	Pass
Pendulum Deceleration at 20ms	17.6	22.6	g's	20.94	Pass
Pendulum Deceleration at 30ms	12.5	18.5	g's	16.73	Pass
Max. Pendulum Deceleration After 30ms	0	29	g's	26.5	Pass
Pendulum Deceleration Time to 5 g's	34	42	ms	40.5	Pass
Maximum D Plane Rotation	64	78	deg	70.5	Pass
Time to Maximum Rotation	57	64	ms	60.9	Pass
Rotation Decay to Zero	113	127	ms	118.0	Pass
Moment About Occipital Condyle	88.1	108.4	Nm	94.49	Pass
Time to Maximum Moment	47	58	ms	54.2	Pass
Moment Decay to Zero	97	107	ms	103.0	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	ENDEVCO 7231CT	AC-AH5M9 Pend	1/29/2019	1/29/2020
Pendulum Potentiometer	ETI SP22G	DS-LABPOT1	9/13/2019	9/12/2020
Condyle Potentiometer	ETI SP22G	DS-LABPOT2	9/13/2019	9/12/2020
Upper Neck Load Cell	Denton 1716	17162019 FX	2/18/2019	2/18/2020







ATD Manufacturer	Humanetics	Test Technician	K. Dutton
ATD Serial Number	142	Laboratory Supervisor	K. Brogan




Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	20.6	22.2	°C	21.8	Pass
Humidity	10	70	%	24.6	Pass
Velocity	5.94	6.19	m/s	6.005	Pass
Pendulum Deceleration at 10ms	17.2	21.2	g's	19.82	Pass
Pendulum Deceleration at 20ms	14	19	g's	18.2	Pass
Pendulum Deceleration at 30ms	11	16	g's	14.8	Pass
Max. Pendulum Deceleration After 30ms	0	22	g's	19.8	Pass
Pendulum Deceleration Time to 5 g's	38	46	ms	43.8	Pass
Maximum D Plane Rotation	81	106	deg	98.3	Pass
Time to Maximum Rotation	72	82	ms	78.7	Pass
Rotation Decay to Zero	147	174	ms	159.2	Pass
Minimum Moment About OC	-80	-52.9	Nm	-71.38	Pass
Time to Minimum Moment	65	79	ms	73.2	Pass
Moment Decay to Zero	120	148	ms	139.9	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	ENDEVCO 7231CT	AC-AH5M9 Pend	1/29/2019	1/29/2020
Pendulum Potentiometer	ETI SP22G	DS-LABPOT1	9/13/2019	9/12/2020
Condyle Potentiometer	ETI SP22G	DS-LABPOT2	9/13/2019	9/12/2020
Upper Neck Load Cell	Denton 1716	17162019 FX	2/18/2019	2/18/2020






ATD Manufacturer	Humanetics	Test Technician	M. Dudek
ATD Serial Number	142	Laboratory Supervisor	K. Brogan



Results



Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	20.6	22.2	°C	21.4	Pass
Humidity	10	70	%	33	Pass
Velocity	6.59	6.83	m/s	6.626	Pass
Chest Displacement	-72.6	-63.5	mm	-66.22	Pass
Resistive Force	5160	5894	N	5433.1	Pass
Hysteresis	65	85	%	68.6	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	MSI 64C-2000	A286228	9/27/2019	3/27/2020
Chest Potentiometer	JDK 6209-2038	DS-142	9/12/2019	9/11/2020








ATD Manufacturer	Humanetics	Test Technician	K. Dutton
ATD Serial Number	142	Laboratory Supervisor	K. Brogan

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	°C	22.0	Pass
Humidity	10	70	%	24.2	Pass
Average Velocity	5	10	deg/s	6.9	Pass
Angle at 203Nm	40	50	deg	42.2	Pass
Moment at 30 degrees	0	94.9	Nm	92.9	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Potentiometer	ETI SP22	DS-0008	9/18/2019	9/18/2020
Load Cell	Key Trans 2301-02	LC-115 My	9/12/2019	9/11/2020




ATD Manufacturer	Humanetics	Test Technician	K. Dutton
ATD Serial Number	142	Laboratory Supervisor	K. Brogan

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	°C	21.4	Pass
Humidity	10	70	%	25.4	Pass
Average Velocity	5	10	deg/s	7.0	Pass
Angle at 203Nm	40	50	deg	45.0	Pass
Moment at 30 degrees	0	94.9	Nm	88.9	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Potentiometer	ETI SP22	DS-0008	9/18/2019	9/18/2020
Load Cell	Key Trans 2301-02	LC-115 My	9/12/2019	9/11/2020




ATD Manufacturer	Humanetics	Test Technician	K. Dutton
ATD Serial Number	142	Laboratory Supervisor	K. Brogan



Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	°C	21.1	Pass
Humidity	10	70	%	25	Pass
Velocity	2.07	2.13	m/s	2.117	Pass
Maximum Resistive Force	4720	5780	N	5460.8	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	MSI 64C-2000	A260568	7/29/2019	1/27/2020






ATD Manufacturer	Humanetics	Test Technician	K. Dutton
ATD Serial Number	142	Laboratory Supervisor	K. Brogan



Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	°C	21.1	Pass
Humidity	10	70	%	24.1	Pass
Velocity	2.07	2.13	m/s	2.115	Pass
Maximum Resistive Force	4720	5780	N	5646.0	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	MSI 64C-2000	A260568	7/29/2019	1/27/2020





CALIBRATION TEST RESULTS

POST-TEST

HYBRID III 5TH PERCENTILE FEMALE - PASSENGER ATD

SERIAL NO: 140





External Measurements - Hybrid 3 - 5th Female

Technician: K. Brogan

Date: 1/09/2020

Dummy Serial Number: 140



Symbol	Description	Specification (mm)		Result (mm)	Pass/Fail
A	Sitting Height	775	800	791	Pass
B	Shoulder Pivot Height	432	457	442	Pass
C	H-Point Height	81	86	83	Pass
D	H-Point from Backline	145	150	146	Pass
E	Shoulder Pivot from Backline	69	84	75	Pass
F	Thigh Clearance	119	135	126	Pass
G	Back of Elbow to Wrist Pivot	244	259	250	Pass
H	Head Back to Backline	43	48	45	Pass
I	Shoulder to Elbow Length	277	297	290	Pass
J	Elbow Rest Height	183	203	194	Pass
K	Buttock to Knee Length	521	546	537	Pass
L	Popliteal Height	356	376	366	Pass
M	Knee Pivot Height	394	419	409	Pass
N	Buttock Popliteal Length	414	439	428	Pass
O	Chest Depth without Jacket	175	191	182	Pass
P	Foot Length (right)	219	234	229	Pass
R	Buttock To Knee Pivot Length	457	483	467	Pass
S	Head Breadth	137	147	142	Pass
T	Head Depth	178	188	180	Pass
U	Hip Breadth	300	315	313	Pass
V	Shoulder Breadth	351	366	361	Pass
W	Foot Breadth	79	94	83	Pass
X	Head Circumference	528	549	540	Pass
Y	Chest Circumference with Jacket	851	881	874	Pass
Z	Waist Circumference	460	790	624	Pass
AA	Reference Location (Chest Circumference)	333	358	345	Pass
BB	Reference Location (Waist Circumference)	160	170	165	Pass


ATD Manufacturer	Humanetics	Test Technician	E. Helenbrook
ATD Serial Number	140	Laboratory Supervisor	K. Brogan




Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	°C	21.5	Pass
Humidity	10	70	%	20.7	Pass
Resultant Acceleration	250	300	g's	267.3	Pass
Oscillation	0	10	%	2.2	Pass
Lateral Acceleration	-15	15	g's	5.6	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
X Accelerometer	Endevco	P58998	9/30/2019	3/30/2020
Y Accelerometer	Endevco	P51722	9/30/2019	3/30/2020
Z Accelerometer	Endevco	P58997	9/30/2019	3/30/2020






ATD Manufacturer	Humanetics	Test Technician	E. Helenbrook
ATD Serial Number	140	Laboratory Supervisor	K. Brogan



Results


Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	20.6	22.2	°C	21.3	Pass
Humidity	10	70	%	20.7	Pass
Velocity	6.89	7.13	m/s	7.013	Pass
Pendulum Impulse at 10ms	2.1	2.5	m/s	2.46	Pass
Pendulum Impulse at 20ms	4.0	5.0	m/s	4.82	Pass
Pendulum Impulse at 30ms	5.8	7.0	m/s	6.88	Pass
Max D Plane Rotation	77	91	deg	81.8	Pass
Max Moment During Rotation Interval	69	83	Nm	74.7	Pass
Moment Decay to 10.0 Nm	80	100	ms	89.6	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	ENDEVCO 7231CT	AC-AH5M9 Pend	1/29/2019	1/29/2020
Pendulum Potentiometer	ETI SP22G	DS-LABPOT1	9/13/2019	9/12/2020
Condyle Potentiometer	ETI SP22G	DS-LABPOT2	9/13/2019	9/12/2020
Upper Neck Load Cell	DENTON 1716A	LC-2206Fx	2/18/2019	2/18/2020








ATD Manufacturer	Humanetics	Test Technician	E. Helenbrook
ATD Serial Number	140	Laboratory Supervisor	K. Brogan



Results


Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	20.6	22.2	°C	21.3	Pass
Humidity	10	70	%	20.7	Pass
Velocity	5.95	6.19	m/s	6.046	Pass
Pendulum Impulse at 10ms	1.5	1.9	m/s	1.80	Pass
Pendulum Impulse at 20ms	3.1	3.9	m/s	3.72	Pass
Pendulum Impulse at 30ms	4.6	5.6	m/s	5.36	Pass
D Plane Rotation	99	114	deg	101.5	Pass
Moment During Rotation Interval	-65	-53	Nm	-61.1	Pass
Moment Decay to -10Nm	94	114	ms	103.8	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	ENDEVCO 7231CT	AC-AH5M9 Pend	1/29/2019	1/29/2020
Pendulum Potentiometer	ETI SP22G	DS-LABPOT1	9/13/2019	9/12/2020
Condyle Potentiometer	ETI SP22G	DS-LABPOT2	9/13/2019	9/12/2020
Upper Neck Load Cell	DENTON 1716A	LC-2206Fx	2/18/2019	2/18/2020








ATD Manufacturer	Humanetics	Test Technician	D.Reinhard
ATD Serial Number	140	Laboratory Supervisor	K. Brogan



Results



Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	20.6	22.2	°C	21.8	Pass
Humidity	10	70	%	32	Pass
Velocity	6.59	6.83	m/s	6.641	Pass
Chest Deflection	-58	-50	mm	-51.8	Pass
Maximum Resistive Force (50 to 58mm)	3900	4400	N	4173.6	Pass
Maximum Resistive Force (18 to 50mm)	0	4600	N	4182.3	Pass
Hysteresis	69	85	%	75.1	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	MSI 64C-2000	A286228	9/27/2019	3/27/2020
Chest Potentiometer	SERVO 14CBI-3615	DS-140GFE	6/21/2019	6/20/2020








ATD Manufacturer	Humanetics	Test Technician	D.Reinhard
ATD Serial Number	140	Laboratory Supervisor	K. Brogan

Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.6	25.6	°C	22	Pass
Humidity	10	70	%	29	Pass
Initial Angle	0	20	deg	17.2	Pass
Force at 45 Degrees	320	390	N	378.7	Pass
Return Angle Relative to Initial	0	8	deg	1.0	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Potentiometer	Rieker N4C-1	DS-13051548	12/9/2019	12/8/2020
Load Cell	Interface SML-200	LC-493319	1/10/2020	1/9/2021




ATD Manufacturer	Humanetics	Test Technician	E. Helenbrook
ATD Serial Number	140	Laboratory Supervisor	K. Brogan



Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	°C	21.3	Pass
Humidity	10	70	%	20.7	Pass
Velocity	2.07	2.13	m/s	2.076	Pass
Resistive Force	3450	4060	N	4024.9	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	Measurement Specialties	A260568	7/29/2019	7/29/2020






ATD Manufacturer	Humanetics	Test Technician	E. Helenbrook
ATD Serial Number	140	Laboratory Supervisor	K. Brogan



Results

Test Parameter	Minimum Specification	Maximum Specification	Unit	Result	Pass/Fail
Temperature	18.9	25.6	°C	21.3	Pass
Humidity	10	70	%	20.7	Pass
Velocity	2.07	2.13	m/s	2.078	Pass
Resistive Force	3450	4060	N	3552.0	Pass

Transducer Calibrations

Channel	Manufacturer	Serial Number	Calibration Date	Calibration Due Date
Pendulum Accelerometer	Measurement Specialties	A260568	7/29/2019	7/29/2020





APPENDIX D

DUMMY CALIBRATION AND PERFORMANCE VERIFICATION DATA

Table 1 – Driver Dummy Instrumentation

Instrumentation		Axis/Location	Hybrid III 50 th S/N: 142		
			Serial Number	Manufacturer	Calibration Date
Head Accelerometers	Primary	X	P51681	ENDEVCO	8/13/2019
		Y	P64151	ENDEVCO	8/13/2019
		Z	P52114	ENDEVCO	8/13/2019
	Redundant	X	P58833	ENDEVCO	8/13/2019
		Y	P58905	ENDEVCO	8/13/2019
		Z	P63996	ENDEVCO	8/13/2019
Head Angular Rate Sensors		X	ARS-5941 GFE	DTS ARS	7/8/2019
		Y	ARS-6014 GFE	DTS ARS	7/8/2019
		Z	ARS-5990	DTS ARS	7/8/2019
Upper Neck Load Cell		FX, Fy, Fz MX,MY, MZ	17162019 FX	Denton	2/18/2019
Chest Accelerometers	Primary	X	AC-P51994	ENDEVCO	10/21/2019
		Y	AC-P51991	ENDEVCO	10/21/2019
		Z	AC-P49185	ENDEVCO	10/21/2019
	Redundant	X	AC-P51713	ENDEVCO	10/21/2019
		Y	AC-P68059	ENDEVCO	10/21/2019
		Z	AC-P78824	ENDEVCO	10/21/2019
Chest Potentiometer		X	DS-142	JDK	9/12/2019
Pelvis Accelerometer		X	AC-P58800	ENDEVCO	12/9/2019
		Y	AC-P52157	ENDEVCO	12/9/2019
		Z	AC-P52156	ENDEVCO	12/9/2019
Femur Load Cells - Left	Primary	Z	LC-115-1 Fz	Denton	10/3/2019
	Redundant	Z	LC-115-2 Fz	Denton	10/3/2019
Femur Load Cells - Right	Primary	Z	LC- DI4210FZ1	Denton	10/3/2019
	Redundant	Z	LC- DI4210FZ2	Denton	10/3/2019
Tibia Load Cells - Left	Upper	MX, MY, FZ	LC-404Fx	Denton	9/25/2019
	Lower	MX, MY, FZ	LC-396Fz	Denton	9/25/2019
Tibia Load Cells – Right	Upper	MX, MY, FZ	LC-651 Fz	Denton	2/18/2019
	Lower	MX, MY, FZ	LC-364Fz	Denton	9/25/2019
Foot Accelerometers - Left	Rear	X	AC-P50084	ENDEVCO	9/30/2019
	Front	Z	AC-P58779	ENDEVCO	9/30/2019
Foot Accelerometers - Right	Rear	X	AC-P51872	ENDEVCO	10/1/2019
	Front	Z	AC-P58893	ENDEVCO	9/30/2019
Seat belt Load Cells	Lap		NA	NA	NA
	Shoulder		NA	NA	NA

Table 2 – Front Passenger Dummy Instrumentation

Instrumentation		Axis/Location	Hybrid III 5 th S/N: 140		
			Serial Number	Manufacturer	Calibration Date
Head Accelerometers	Primary	X	AC-P58998	ENDEVCO	9/30/2019
		Y	AC-P51722	ENDEVCO	10/1/2019
		Z	AC-P58997	ENDEVCO	9/30/2019
	Redundant	X	AC-P58780	ENDEVCO	9/30/2019
		Y	AC-P58749	ENDEVCO	9/30/2019
		Z	AC-P58909	ENDEVCO	9/30/2019
Head Angular Rate Sensors		X	ARS16992	ENDEVCO	5/28/2019
		Y	ARS-4712 GFE	DTS ARS	7/8/2019
		Z	ARS11293	DTS ARS	5/28/2019
Upper Neck Load Cell		FX, Fy, Fz MX,MY, MZ	ARS11293	DENTON	2/18/2019
Chest Accelerometers	Primary	X	AC-P59019	ENDEVCO	9/30/2019
		Y	AC-P51965	ENDEVCO	9/30/2019
		Z	AC-P58981	ENDEVCO	9/30/2019
	Redundant	X	AC-P64000	ENDEVCO	9/30/2019
		Y	AC-P51970	ENDEVCO	9/30/2019
		Z	AC-P51689	ENDEVCO	9/30/2019
Chest Potentiometer		X	DS-140GFE	SERVO	6/21/2019
Pelvis Accelerometer		X	AC-P58912	ENDEVCO	10/21/2019
		Y	AC-P51220	ENDEVCO	10/21/2019
		Z	AC-P51989	ENDEVCO	10/21/2019
Femur Load Cells - Left	Primary	Z	LC-DI4213-1	Denton	2/18/2019
	Redundant	Z	LC-DI4213-2	Denton	2/18/2019
Femur Load Cells - Right	Primary	Z	LC-DH3271Fz1	Denton	2/18/2019
	Redundant	Z	LC-DH3271Fz2	Denton	2/18/2019
Tibia Load Cells - Left	Upper	MX, MY, FZ	3643-93 Fz	Denton	10/3/2019
	Lower	MX, MY, FZ	LC-490Fz	Denton	10/3/2019
Tibia Load Cells – Right	Upper	MX, MY, FZ	LC-91Fz	Denton	10/3/2019
	Lower	MX, MY, FZ	LC-398Fz	Denton	10/3/2019
Foot Accelerometers - Left	Rear	X	AC-P64005	ENDEVCO	10/21/2019
	Front	Z	AC-P64006	ENDEVCO	10/21/2019
Foot Accelerometers - Right	Rear	X	AC-P52018	ENDEVCO	10/21/2019
	Front	Z	AC-P78669	ENDEVCO	10/21/2019
Seat belt Load Cells	Lap		NA	NA	NA
	Shoulder		NA	NA	NA

Table 3 – Vehicle Instrumentation

Instrumentation			Axis	Serial Number	Manufacturer	Calibration Date
Crossmember/Rear Seat Accelerometers	Left	Primary	X	A282709	MSI	9/17/2019
			Z	A283660	MSI	9/11/2019
		Redundant	X	A283599	MSI	9/17/2019
	Right	Primary	X	A281454	MSI	9/13/2019
			Z	A284323	MSI	10/25/2019
		Redundant	X	A283610	MSI	9/11/2019
Engine Accelerometers	Top		X	AC-A280364	MSI	11/5/2019
	Bottom		X	A284328	MSI	10/25/2019