



DEPARTMENT OF  
TRANSPORTATION

2021 JAN 28 A 10: 12

DOCKET OPERATIONS

MANUFACTURING QUALITY TIRES IN THE USA SINCE 1915

1600 Washington Street • Indiana, Pennsylvania 15701-2844 • Phone: 724-349-9010 • Fax: 724-349-8192

01/21/21

Docket Section  
National Highway Traffic Safety Administration  
1200 New Jersey Avenue, SE  
W. Bldg. Ground Floor, Room W12140  
Washington, DC 20590

SUBJECT: COMPLIANCE WITH 49 CFR 571.119, SECTION S5

We are hereby notifying the National Highway Traffic Safety Administration of the approved rims for the following tire size in our manufacturing plan:

SIZE	SPEED RATING	PLY/ TYPE	SKID DEPTH	TREAD WIDTH	DIA	SECTION WIDTH	MEASURING RIM	APPROVED RIM(S)	WEIGHT (LBS)
27x10.50-17LT	N/A	4/2 Nylon	.20	8.7	26.5	10.5	8½	7½J, 8J, 8½J, 9J, 9½J	26.18

MAX INFL (PSI)	MAX LOAD (LBS)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES				
		PSI	20	25	30	
30	1050	LOAD	830	945	1050	

Rim sizes for the above product is listed in retailer's catalog.

*Timothy M. Lockard*

Timothy M. Lockard  
Tire Design Engineer