

**NEW CAR ASSESSMENT PROGRAM
LANE DEPARTURE WARNING CONFIRMATION TEST
NCAP-DRI-LDW-21-02**

2021 Chevrolet Tahoe 2WD High Country

DYNAMIC RESEARCH, INC.

355 Van Ness Avenue, STE 200
Torrance, California 90501



15 March 2021

Final Report

Prepared Under Contract No. DTNH22-14-D-00333

**U.S. DEPARTMENT OF TRANSPORTATION
National Highway Traffic Safety Administration
New Car Assessment Program
1200 New Jersey Avenue, SE
West Building, 4th Floor (NRM-110)
Washington, DC 20590**

Prepared for the Department of Transportation, National Highway Traffic Safety Administration, under Contract No. DTNH22-14-D-00333.

This publication is distributed by the U.S. Department of Transportation, National Highway Traffic Safety Administration, in the interest of information exchange. The opinions, findings, and conclusions expressed in this publication are those of the author(s) and not necessarily those of the Department of Transportation or the National Highway Traffic Safety Administration. The United States Government assumes no liability for its contents or use thereof. If trade or manufacturer's names or products are mentioned, it is only because they are considered essential to the object of the publication and should not be construed as an endorsement. The United States Government does not endorse products of manufacturers.

Prepared By: J. Lenkeit and A. Ricci

Program Manager

Test Engineer

Date: 15 March 2021

1. Report No. NCAP-DRI-LDW-21-02	2. Government Accession No.	3. Recipient's Catalog No.	
4. Title and Subtitle Final Report of Lane Departure Warning Confirmation Test of a 2021 Chevrolet Tahoe 2WD High Country.		5. Report Date 15 March 2021	
		6. Performing Organization Code DRI	
7. Author(s) J. Lenkeit, Program Manager A. Ricci, Test Engineer		8. Performing Organization Report No. DRI-TM-20-176	
9. Performing Organization Name and Address Dynamic Research, Inc. 355 Van Ness Ave, STE 200 Torrance, CA 90501		10. Work Unit No.	
		11. Contract or Grant No. DTNH22-14-D-00333	
12. Sponsoring Agency Name and Address U.S. Department of Transportation National Highway Traffic Safety Administration New Car Assessment Program 1200 New Jersey Avenue, SE, West Building, 4th Floor (NRM-110) Washington, DC 20590		13. Type of Report and Period Covered Final Test Report February - March 2021	
		14. Sponsoring Agency Code NRM-110	
15. Supplementary Notes			
16. Abstract These tests were conducted on the subject 2021 Chevrolet Tahoe 2WD High Country in accordance with the specifications of the New Car Assessment Program's (NCAP) most current Test Procedure in docket NHTSA-2006-26555-0135 to confirm the performance of a Lane Departure Warning system. The vehicle passed the requirements of the test for all three lane marking types and for both directions.			
17. Key Words Lane Departure Warning, LDW, New Car Assessment Program, NCAP		18. Distribution Statement Copies of this report are available from the following: NHTSA Technical Reference Division National Highway Traffic Safety Administration 1200 New Jersey Avenue, SE Washington, DC 20590	
19. Security Classif. (of this report) Unclassified	20. Security Classif. (of this page) Unclassified	21. No. of Pages 140	22. Price

TABLE OF CONTENTS

<u>SECTION</u>	<u>PAGE</u>
I. INTRODUCTION	1
II. DATA SHEETS	2
Data Sheet 1: Test Results Summary	3
Data Sheet 2: Vehicle Data	4
Data Sheet 3: Test Conditions	5
Data Sheet 4: Lane Departure Warning System Operation	7
III. TEST PROCEDURES	9
A. Test Procedure Overview	9
B. Lane Delineation Markings	10
C. Test Validity	12
D. Pass/Fail Criteria	13
E. Instrumentation	13
APPENDIX A Photographs	A-1
APPENDIX B Excerpts from Owner's Manual	B-1
APPENDIX C Run Log	C-1
APPENDIX D Time Histories	D-1

Section I

INTRODUCTION

The purpose of the testing reported herein was to confirm the performance of a Lane Departure Warning (LDW) system installed on a 2021 Chevrolet Tahoe 2WD High Country. The LDW system for this vehicle provides a visual, auditory, and the option for haptic alerts. The haptic alerts occur after the test validity criteria and were not collected. The vehicle passed the requirements of the test for all three lane marking types and for both directions.

The test procedure is described in detail in the National Highway Traffic Safety Administration (NHTSA) document "LANE DEPARTURE WARNING SYSTEM CONFIRMATION TEST" dated February of 2013 (Docket No. NHTSA-2006-26555-0135). Its purpose is to confirm the performance of LDW systems installed on light vehicles with gross vehicle weight ratings (GVWR) of up to 10,000 lbs. Current LDW technology relies on sensors to recognize a lane delimiting edge line. As such, the test procedures described in the document rely on painted lines, taped lines, or Botts Dots being present on the test course to emulate those found on public roadways. Although it is impossible to predict what technologies could be used by future LDW systems (e.g., magnetic markers, RADAR reflective striping, ultra violet paint, infrared, etc.), it is believed that minor modifications to these procedures, when deemed appropriate, could be used to accommodate the evaluation of alternative or more advanced LDW systems.

Section II
DATA SHEETS

LANE DEPARTURE WARNING
DATA SHEET 1: TEST RESULTS SUMMARY

(Page 1 of 1)

2021 Chevrolet Tahoe 2WD High Country

VIN: 1GNSCTKL9MR11xxxx

Test Date: 2/12/2021

Lane Departure Warning setting: On

Test 1 – Continuous White Line Left: Pass Right: Pass

Test 2 – Dashed Yellow Line Left: Pass Right: Pass

Test 3 – Botts Dots Left: Pass Right: Pass

Overall: Pass

Notes:

LANE DEPARTURE WARNING
DATA SHEET 2: VEHICLE DATA

(Page 1 of 1)

2021 Chevrolet Tahoe 2WD High Country

TEST VEHICLE INFORMATION

VIN: 1GNSCTKL9MR11xxxx

Body Style: SUV

Color: Graywood Metallic

Date Received: 2/1/2021

Odometer Reading: 207 mi

DATA FROM VEHICLE'S CERTIFICATON LABEL

Vehicle manufactured by: General Motors LLC

Date of manufacture: 07/20

Vehicle Type: MPV

DATA FROM TIRE PLACARD

Tires size as stated on Tire Placard: Front: 275/50R22 H

Rear: 275/50R22 H

Recommended cold tire pressure: Front: 250 kPa (36 psi)

Rear: 250 kPa (36 psi)

TIRES

Tire manufacturer and model: Bridgestone Alenza A/S 02

Front tire size: 275/50R22 111H

Rear tire size: 275/50R22 111H

Front tire DOT prefix: 1W2RHAA21

Rear tire DOT prefix: 1W2RHAA21

LANE DEPARTURE WARNING
DATA SHEET 3: TEST CONDITIONS

(Page 1 of 2)

2021 Chevrolet Tahoe 2WD High Country

GENERAL INFORMATION

Test date: 2/12/2021

AMBIENT CONDITIONS

Air temperature: 12.8 C (55 F)

Wind speed: 1.5 m/s (3.5 mph)

- X Wind speed ≤ 10 m/s (22 mph)
- X Tests were not performed during periods of inclement weather. This includes, but is not limited to, rain, snow, hail, fog, smoke, or ash.
- X Tests were conducted during daylight hours with good atmospheric visibility (defined as an absence of fog and the ability to see clearly for more than 5000 meters). The tests were not conducted with the vehicle oriented into the sun during very low sun angle conditions, where the sun is oriented 15 degrees or less from horizontal, and camera "washout" or system inoperability results.

VEHICLE PREPARATION

Verify the following:

All non-consumable fluids at 100% capacity: X

Fuel tank is full: X

Tire pressures are set to manufacturer's
recommended cold tire pressure: X

Front: 250 kPa (36 psi)

Rear: 250 kPa (36 psi)

LANE DEPARTURE WARNING
DATA SHEET 3: TEST CONDITIONS

(Page 2 of 2)

2021 Chevrolet Tahoe 2WD High Country

WEIGHT

Weight of vehicle as tested including driver and instrumentation

Left Front: 684.0 kg (1508 lb)

Right Front: 660.9 kg (1457 lb)

Left Rear: 691.3 kg (1524 lb)

Right Rear: 679.5 kg (1498 lb)

Total: 2715.7 kg (5987 lb)

LANE DEPARTURE WARNING
DATA SHEET 4: LANE DEPARTURE WARNING SYSTEM OPERATION

(Page 1 of 2)

2021 Chevrolet Tahoe 2WD High Country

Name of the LDW option, option package, etc.:

Lane Keep Assist with Lane Departure Warning. It is included in the driver alert packages for LS, LT, RST, and Z71 trims. It is also included in Adaptive Cruise Control Package for high country and premier trims.

Type and location of sensor(s) used:

Mono camera located behind the windshield near the rear-view mirror.

Lane Departure Warning Setting used in test:

On

How is the Lane Departure Warning presented to the driver? Warning light
(Check all that apply) Buzzer or auditory alarm
 Vibration
 Other _____

Describe the method by which the driver is alerted. For example, if the warning is a light, where is it located, its color, size, words or symbol, does it flash on and off, etc. If it is a sound, describe if it is a constant beep or a repeated beep. If it is a vibration, describe where it is felt (e.g., pedals, steering wheel), the dominant frequency, (and possibly magnitude), the type of warning (light, auditory, vibration, or combination), etc.

The visual alert is presented in the heads-up display and shows the rear view of an automobile between dashed lane lines. See Appendix A, Figure A10. In addition, either a haptic or auditory alert can be selected as a secondary alert. The auditory alert is a repeated set of beeps that sounds from the front, and the seat bottom vibrates as the haptic alert. Note that it is not possible to select both haptic and auditory secondary alerts.

LANE DEPARTURE WARNING

DATA SHEET 4: LANE DEPARTURE WARNING SYSTEM OPERATION

(Page 2 of 2)

2021 Chevrolet Tahoe 2WD High Country

Is the vehicle equipped with a switch whose purpose is to render LDW inoperable? Yes
 No

If yes, please provide a full description including the switch location and method of operation, any associated instrument panel indicator, etc.

System menus are used to interact with the settings. The menu hierarchy is:

Settings

Vehicle

Collision/Detection Systems

Lane Change Alert

Select from: Off, On

See Appendix A, Figure A9.

Is the vehicle equipped with a control whose purpose is to adjust the range setting or otherwise influence the operation of LDW? Yes
 No

If yes, please provide a full description.

System menus can be used to switch the secondary alert between haptic and auditory. The menu hierarchy is:

Settings

Alert Type

Select from: Beeps and Safety Alert Seat

Are there other driving modes or conditions that render LDW inoperable or reduce its effectiveness? Yes
 No

If yes, please provide a full description.

System limitations are described on page 276 of the Owner's Manual, shown in Appendix B, page B-10.

Notes:

Section III

TEST PROCEDURES

A. Test Procedure Overview

Each LDW test involved one of three lane marking types: solid white lines, dashed yellow lines, or Botts Dots. Lane departures were done both to the left and to the right, and each test condition was repeated five times, as shown in Table 1.

Table 1. LDW Test Matrix

Lane Geometry	Line Type	Departure Direction	Number of Trials
Straight	Solid	L	5
		R	5
	Dashed	L	5
		R	5
	Botts Dots	L	5
		R	5

Prior to the start of a test series involving a given lane marking type and departure direction combination, the accuracy of the distance to lane marking measurement was verified. This was accomplished by driving the vehicle to the approximate location at which the lane departure would occur and placing the tire at the lane marking edge of interest (i.e., distance to lane marking = 0). The real-time display of distance to the lane marking was then observed to verify that the measured distance was within the tolerance (5 cm). If the measured distance was found to be greater than the tolerance, the instrumentation setup was checked and corrected, if necessary. If the measured distance was found to be within the tolerance, the instrumentation setup was considered appropriate and the test series was begun.

To begin the maneuver, the vehicle was accelerated from rest to a test speed of 72.4 km/h (45 mph), while being driven in a straight line parallel to the lane marking of interest, with the centerline of the vehicle approximately 1.83 m (6.0 ft) from the lane edge (i.e., such that the vehicle would pass through the center of the start gate). The test speed was achieved at least 60 m (200 ft) before the start gate was reached. Striking any start gate cones was not permitted, and any run in which a cone was struck was considered to be invalid. Also, during the initialization and test phases, the test driver avoided using turn signals and avoided applying any sudden acceleration, sudden steering, or sudden braking, and any use of the turn signals, sudden acceleration, sudden steering, or sudden braking invalidated the test trial.

Data collection began with the vehicle at least 60 m (200 ft) from the start gate, which was configured using a pair of non-reflective, low-contrast color traffic cones. A second set of cones, placed 6 m (20 ft) longitudinally before the start gate, was used to guide the driver into the start gate. The lateral width between the cone pairs was 20 cm (8 in) greater than the width of the vehicle, and the centerline of each pair was laterally offset from the lane marking by 1.8 m (6 ft).

Once the driver passed the gate, the driver manually input sufficient steering to achieve a lane departure with a target lateral velocity of 0.5 m/s with respect to the lane line. As shown in Figure 1, two additional non-reflective cones were used to guide the driver in making this steering maneuver. Throughout the maneuver, the driver modulated the throttle or used cruise control, as appropriate, such that vehicle speed remained at constant speed. The test was considered complete when the vehicle crossed at least 1 m (3.3 ft) over the lane edge boundary.




Figure 1. Position of Cones Used to Assist Driver

Data collected included vehicle speed, position, and yaw rate. In addition to cone strikes, vehicle speed and yaw rate data were used to identify invalid runs as described in Section C below. Data from trials where speed or yaw rate were outside of the performance specification were not considered valid.

B. Lane Delineation Markings

The New Car Assessment Program's Test Procedure for the confirmation of a Lane Departure Warning system contains a requirement that all lane markings meet United States Department of Transportation (USDOT) specifications as described in the Manual on Uniform Traffic Control Devices (MUTCD) and be considered in "very good condition".

1. Lane Marker Width

The width of the edge line marker was 10 to 15 cm (4 to 6 in). This is considered to be a normal width for longitudinal pavement markings under Section 3A.05 of the MUTCD.

2. Line Marking Color and Reflectivity

Lane marker color and reflectivity met all applicable standards. These standards include those from the International Commission of Illumination (CIE) for color and the American Society for Testing and Materials (ASTM) on lane marker reflectance.

3. Line Styles

The tests described in this document required the use of three lane line configurations: continuous solid white, discontinuous dashed yellow, and discontinuous with raised pavement markers.

- Continuous White Line

A continuous white line is defined as a white line that runs for the entire length of the test course.

- Dashed Yellow Line

As stated in the MUTCD, and as shown in Figure 2, a discontinuous dashed yellow line is defined as by a series of 3 m (10 ft) broken (dashed) yellow line segments, spaced 9.1 m (30 ft) apart.

- Raised Pavement Marker Line (Botts Dots)

California Standard Plans indicates raised pavement markers are commonly used in lieu of painted strips for marking roads in California. Other states, mainly in the southern part of the United States, rely on them as well. These markers may be white or yellow, depending on the specific application, following the same basic colors of their analogous white and yellow painted lines. Following the California 2006 Standard Plans, three types of raised pavement markings are used to form roadway lines. It is believed that these types of roadway markings are the hardest for an LDW sensor system to process. Type A and Type AY are non-reflective circular domes that are approximately 10 cm (4 in) in diameter and approximately 1.8 cm (0.7 in) high. Type C and D are square markings that are retro reflective in two directions measuring approximately 10 x 10 x 5 cm (4 x 4 x 0.5 in), and Type G and H that are the same as C and D only retro reflective in a single direction.

For the tests described in this document, raised pavement markers were set up following California Standard Plan A20A, Detail 4, as shown in Figure 3. Note that in this figure, the squares are Type D yellow reflectors and the circles are yellow Type AY discs.




Figure 2. MUTCD Discontinuous Dashed Line Specifications




Figure 3. California Standard Plan A20A, Detail 4

C. Test Validity

1. Speed

All LDW tests were conducted at 72.4 km/h (45 mph). Test speed was monitored and a test was considered valid if the test speed remained within ± 2 km/h (± 1.2 mph) of the 72.4 km/h (45 mph) target speed. It was required that the speed must remain within this window from the start of the test until any part of the vehicle crossed a lane line by 1 m (3.3 ft) or more.

2. Lateral Velocity

All tests were conducted with a lateral velocity of 0.1 to 0.6 m/s (0.3 to 2.0 ft/s), measured with respect to the lane line at the time of the alert. To assist the test driver in being able to efficiently establish the target lateral velocity, cones were positioned in the manner shown in Figure 1.

3. Yaw Rate

It was required that the magnitude of the vehicle's yaw rate could not exceed 1.0 deg/sec at any time during lane departure maneuver, from the time the vehicle passes through the start gate to the instant the vehicle has crossed a lane line by 1 m (3.3 ft).

D. Pass/Fail Criteria

The measured test data were used to determine the pass/fail outcome for each trial. The outcome was based on whether the LDW produced an appropriate alert during the maneuver. In the context of this test procedure, a lane departure is said to occur when any part of the two-dimensional polygon used to represent the test vehicle breaches the inboard lane line edge (i.e., the edge of the line close to the vehicle before the departure occurs). In the case of tests performed in this procedure, the front corner of the polygon, defined as the intersection of the center of the front wheels (longitudinally) with the outboard edge of the front tire (laterally), crossed the line edge first. So, for example, if the vehicle departed its lane to the left, the left front corner of the polygon would first breach the lane line edge.

For an individual trial to be considered a "pass":

- Test speed, lateral velocity, and yaw rate validity conditions must be satisfied.
- The LDW alert must not occur when the lateral position of the vehicle is greater than 0.75 m (2.5 ft) from the lane line edge (i.e., prior to the lane departure).
- The LDW alert must occur before the lane departure exceeds 0.3 m (1.0 ft).

For an overall, "Pass" the LDW system must satisfy the pass criteria for 3 of 5 individual trials for each combination of departure direction and lane line type (60%), and pass 20 of the 30 trials overall (66%).

E. Instrumentation

Table 2 lists the sensors, signal conditioning, and data acquisition equipment used for these tests.

Table 2. Test Instrumentation and Equipment

Type	Output	Range	Accuracy, Other Primary Specs	Mfr, Model	Serial Number	Calibration Dates Last Due
Tire Pressure Gauge	Vehicle Tire Pressure	0-100 psi 0-690 kPa	0.5 psi 3.45 kPa	Ashcroft, D1005PS	17042707002	By: DRI Date: 8/18/2020 Due: 8/18/2021
Platform Scales	Vehicle Total, Wheel, and Axle Load	8000 lb 35.6 kN	±1.0% of applied load	Intercomp, SWII	0410MN20001	By: DRI Date: 4/20/2020 Due: 4/20/2021
Differential Global Positioning System	Position, Velocity	Latitude: ±90 deg Longitude: ±180 deg Altitude: 0-18 km Velocity: 0-1000 knots	Horizontal Position: ±1 cm Vertical Position: ±2 cm Velocity: 0.05 km/h	Trimble GPS Receiver, 5700 (base station and in-vehicle)	00440100989	N/A
Multi-Axis Inertial Sensing System	Position: Longitudinal, Lateral, and Vertical Accels: Lateral, Longitudinal and Vertical Velocities: Roll, Pitch, Yaw Rates: Roll, Pitch, Yaw Angles	Latitude: ±90 deg Longitude: ±180 deg Altitude: 0-18 km Velocity: 0-1000 knots Accel: ±100 m/s ² Angular Rate: ±100 deg/s Angular Disp: ±180 deg	Position: ±2 cm Velocity: 0.05 km/h Accel: ≤ 0.01% of full range Angular Rate: ≤ 0.01% of full range Roll/Pitch Angle: ±0.03 deg Heading Angle: ±0.1 deg	Oxford Technical Solutions (OXTS), Inertial+	2258	By: Oxford Technical Solutions ¹ Date: 5/3/2019 Due: 5/3/2021
Real-Time Calculation of Position and Velocity Relative to Lane Markings	Distance and velocity to lane markings	Lateral Lane Dist: ±30 m Lateral Lane Velocity: ±20 m/sec	Lateral Distance to Lane Marking: ±2 cm Lateral Velocity to Lane Marking: ±0.02m/sec	Oxford Technical Solutions (OXTS), RT-Range	97	N/A

¹ Oxford Technical Solutions recommends calibration every two years.

Type	Output	Range	Accuracy, Other Primary Specs	Mfr, Model	Serial Number	Calibration Dates Last Due
Microphone	Sound (to measure time at alert)	Frequency Response: 80 Hz – 20 kHz	Signal-to-noise: 64 dB, 1 kHz at 1 Pa	Audio-Technica AT899	N/A	N/A
Light Sensor	Light intensity (to measure time at alert)	Spectral Bandwidth: 440-800 nm	Rise time < 10 msec	DRI designed and developed Light Sensor	N/A	N/A
Coordinate Measurement Machine	Inertial Sensing System Coordinates	0-8 ft 0-2.4 m	±.0020 in. ±.051 mm (Single point articulation accuracy)	Faro Arm, Fusion	UO8-05-08-06636	By: DRI Date: 1/6/2021 Due: 1/6/2022
Type	Description			Mfr, Model	Serial Number	
Data Acquisition System	Data acquisition is achieved using a dSPACE MicroAutoBox II Data from the Oxford IMU, including Longitudinal, Lateral, and Vertical Acceleration, Roll, Yaw, and Pitch Rate, Forward and Lateral Velocity, Roll and Pitch Angle are sent over Ethernet to the MicroAutoBox. The Oxford IMUs are calibrated per the manufacturer's recommended schedule (listed above).			D-Space Micro-Autobox II 1401/1513		
				Base Board	549068	
				I/O Board	588523	

For systems that implement auditory or haptic alerts, part of the pre-test instrumentation verification process is to determine the tonal frequency of the audible warning or the vibration frequency of the tactile warning through use of the PSD (Power Spectral Density) function in Matlab. This is accomplished in order to identify the center frequency around which a band-pass filter is applied to subsequent auditory or tactile warning data so that the beginning of such warnings can be programmatically determined. The band-pass filter used for these warning signal types is a phaseless, forward-reverse pass, elliptical (Cauer) digital filter, with filter parameters as listed in Table 3.

Table 3. Auditory and Tactile Warning Filter Parameters

Warning Type	Filter Order	Peak-to-Peak Ripple	Minimum Stop Band Attenuation	Passband Frequency Range
Auditory	5 th	3 dB	60 dB	Identified Center Frequency \pm 5%
Tactile	5 th	3 dB	60 dB	Identified Center Frequency \pm 20%

APPENDIX A

Photographs

LIST OF FIGURES

	Page
Figure A1. Front View of Subject Vehicle.....	A-3
Figure A2. Rear View of Subject Vehicle	A-4
Figure A3. Window Sticker (Monroney Label).....	A-5
Figure A4. Vehicle Certification Label	A-6
Figure A5. Tire Placard	A-7
Figure A6. DGPS, Inertial Measurement Unit, and MicroAutoBox Installed in Subject Vehicle.....	A-8
Figure A7. Sensors for Detecting Visual and Auditory Alerts	A-9
Figure A8. Computer Installed in Subject Vehicle	A-10
Figure A9. LDW Menus.....	A-11
Figure A10. Visual Alert	A-12



Figure A1. Front View of Subject Vehicle



Figure A2. Rear View of Subject Vehicle



CHEVROLET

2021 TAHOE 2WD HIGH COUNTRY

EXTERIOR: GRAYWOOD METALLIC
INTERIOR: JET BLACK / MOCHA

ENGINE, 6.2L ECOTEC3 V8
TRANSMISSION, 10-SPEED AUTO

Visit us at www.chevy.com

STANDARD EQUIPMENT

(ITEMS FEATURED BELOW ARE INCLUDED AT NO EXTRA CHARGE IN THE STANDARD VEHICLE PRICE SHOWN)

OWNER BENEFITS

- 3 YEAR/36,000 MILE* BUMPER-TO-BUMPER LIMITED WARRANTY
- 5 YEAR/60,000 MILE* POWERTRAIN LIMITED WARRANTY, ROADSIDE ASSISTANCE & COURTESY TRANSPORTATION
- FIRST MAINTENANCE VISIT
- *WHICHEVER COMES FIRST SEE CHEVROLET.COM OR DEALER FOR TERMS, DETAILS & LIMITS

PERFORMANCE & MECHANICAL

- SUSPENSION, MAGNETIC RIDE CONTROL
- MECHANICAL LIMITED SLIP DIFFERENTIAL
- AUTOMATIC STOP/START ENGINE
- 22" STERLING SILVER PAINTED

- WHEELS W/ CHROME INSERTS
- STABILITRAK
- ELECTRONIC PRECISION SHIFT
- TRAILERING EQUIPMENT

CONNECTIVITY & TECHNOLOGY

- 10 SPEAKER BOSE AUDIO SYSTEM
- HEAD-UP DISPLAY
- CHEVROLET INFOTAINMENT 3 PREMIUM WITH NAVIGATION
- 10.2" DIAG HD COLOR TOUCH-SCREEN, VOICE RECOGNITION, WIRELESS APPLE CARPLAY & WIRELESS ANDROID AUTO CAPABLE
- BLUETOOTH AUDIO STREAMING, IN-VEHICLE APPS AND PERSONALIZATION CAPABLE
- WIRELESS CHARGING FOR DEVICES
- KEYLESS OPEN, LOCK & START
- ONSTAR (R) SERVICES & 4G LTE WI-FI (R) AVAILABLE; SEE ONSTAR.COM FOR TERMS
- SIRIUSXM RADIO CAPABLE.

ALL ACCESS TRIAL W/ SUBSCRIPTION SOLD SEPARATELY

INTERIOR

- TRI-ZONE AUTOMATIC HVAC
- REAR CAMERA MIRROR
- HEATED AND VENTILATED FRONT POWER BUCKET SEATS W/ LEATHER SEATING SURFACES
- MEMORY SETTINGS, DRIVER SEAT, OUTSIDE MIRRORS, STEERING COLUMN
- SECOND ROW HEATED BUCKET SEATS, POWER RELEASE
- THIRD ROW 60/40 SPLIT BENCH, POWER FOLD

EXTERIOR

- LED HEADLAMPS & TAILLAMPS
- LED DAYTIME RUNNING LAMPS
- HANDS FREE POWER LIFTGATE
- POWER FOLD MIRRORS
- DUAL EXHAUST W/ DUAL TIPS

SAFETY & SECURITY

- AUTOMATIC EMERGENCY BRAKING
- FORWARD COLLISION ALERT
- LANE KEEP ASSIST W/ LANE DEPARTURE WARNING
- LANE CHANGE ALERT WITH SIDE BLIND ZONE ALERT
- HD SURROUND VISION
- FRONT AND REAR PARK ASSIST
- REAR CROSS TRAFFIC ALERT
- FRONT PEDESTRIAN BRAKING
- REAR PEDESTRIAN ALERT
- FOLLOWING DISTANCE INDICATOR
- SAFETY ALERT SEAT
- THEFT DETERENT SYSTEM

MANUFACTURER'S SUGGESTED RETAIL PRICE

STANDARD VEHICLE PRICE **\$69,600.00**

OPTIONS & PRICING

OPTIONS INSTALLED BY THE MANUFACTURER (MAY REPLACE STANDARD EQUIPMENT SHOWN)

PREMIUM PACKAGE: 4,605.00

- SUNROOF, POWER PANORAMIC, TILT-SLIDING WITH POWER SUNSHADE
- ASSIST STEPS, POWER RETRACTABLE W/ PERIMETER LIGHTING
- ADAPTIVE CRUISE CONTROL
- ENHANCED AUTOMATIC EMERGENCY BRAKING (REPLACES STANDARD AUTOMATIC EMERGENCY BRAKING)
- TRAILER BRAKE CONTROLLER
- ADVANCED TRAILERING SYSTEM
- HITCH GUIDANCE W/ HITCH VIEW
- TRAILER SIDE BLIND ZONE ALERT
- ENHANCED COOLING RADIATOR

TOTAL OPTIONS \$4,605.00
 TOTAL VEHICLE & OPTIONS \$74,205.00
 DESTINATION CHARGE 1,295.00

TOTAL VEHICLE PRICE* **\$75,500.00**

EPA DOT Fuel Economy and Environment

Gasoline Vehicle


Fuel Economy
17 MPG
 combined city/hwy
 15 city
 20 highway
 5.9 gallons per 100 miles

Standard SUVs range from 13 to 101 MPG. The best vehicle rates 141 MPG.


You spend
\$6,750
 more in fuel costs over 5 years compared to the average new vehicle.

Annual fuel cost
\$2,850

Fuel Economy & Greenhouse Gas Rating (tailpipe only)



Smog Rating (tailpipe only)



Actual results will vary for many reasons, including driving conditions and how you drive and maintain your vehicle. The average new vehicle gets 27 MPG and costs \$7,500 to fuel over 5 years. Cost estimates are based on 15,000 miles per year at \$3.25 per gallon. MPG is miles per gasoline gallon equivalent. Vehicle emissions are a significant cause of climate change and smog.

fuelconomy.gov
 Calculate personalized estimates and compare vehicles



GOVERNMENT 5-STAR SAFETY RATINGS

This vehicle has not been rated by the government for overall vehicle score, frontal crash, side crash or rollover risk.

Source: National Highway Traffic Safety Administration (NHTSA)
www.safercar.gov or 1-888-327-4236

OnStar logo
 Equipped with the safety and security of OnStar.
 Visit onstar.com for details.
 onstar.com/privacy

WARNING
 Cancer and Reproductive Harm
www.P65Warnings.ca.gov/
 passenger-vehicle
 SEE OWNER'S MANUAL

PARTS CONTENT INFORMATION

FOR VEHICLES IN THIS CARLINE:
 U.S./CANADIAN PARTS CONTENT: 46%
 MAJOR SOURCES OF FOREIGN PARTS CONTENT: MEXICO 38%

NOTE: PARTS CONTENT DOES NOT INCLUDE FINAL ASSEMBLY, DISTRIBUTION, OR OTHER NON-PARTS COSTS.

FOR THIS VEHICLE:
 FINAL ASSEMBLY POINT:
 ARLINGTON, TX U.S.A.
 COUNTRY OF ORIGIN:
 ENGINE: UNITED STATES
 TRANSMISSION: UNITED STATES

This label has been prepared pursuant to Federal law. It may contain price information for the United States only. It does not include dealer-installed options and accessories not listed above, local taxes or license fees.

© 2020 General Motors LLC
 GMAL, PRCO, 2020-16740274

ORDER NO. 190707M SALES CODE 4
 SALES MODEL CODE 0210707
 DEALER NO.
 FINAL ASSEMBLY:
 ARLINGTON, TX U.S.A.
 VIN 1GNSCTKL5MRT1
 DEALER TO WHOM DELIVERED



MU
 1AZ0017688

Figure A3. Window Sticker (Monroney Label)



MFD BY GENERAL MOTORS LLC

07/20

GVWR
3357 KG
7400 LB

GAWR FRT
1588 KG
3500 LB

GAWR RR
1950 KG
4300 LB



634D

THIS VEHICLE CONFORMS TO ALL
APPLICABLE U.S. FEDERAL MOTOR
VEHICLE SAFETY STANDARDS IN EFFECT
ON THE DATE OF MANUFACTURE
SHOWN ABOVE.

1GNSCTKL9MR11
TYPE: M.P.V.

	TIRE SIZE	
FRT	275/50R22	H
RR	275/50R22	H
SPA	265/70R17	S

RIM
22X9J
22X9J
17X7J

MODEL: 91CC10706

Figure A4. Vehicle Certification Label



TIRE AND LOADING INFORMATION



1GNSCTKL9MR11

SEATING CAPACITY : TOTAL 7 : FRONT 2 : REAR 5

The combined weight of occupants and cargo should never exceed **722** kg or **1590** lbs.

TIRE	ORIGINAL SIZE	COLD TIRE PRESSURE	SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION
FRONT	275/50R22 H	250 kPa, 36 PSI	
REAR	275/50R22 H	250 kPa, 36 PSI	
SPARE	265/70R17 S	240 kPa, 35 PSI	

Figure A5. Tire Placard



Figure A6. DGPS, Inertial Measurement Unit, and MicroAutoBox Installed in Subject Vehicle



Figure A7. Sensors for Detecting Visual and Auditory Alerts



Figure A8. Computer Installed in Subject Vehicle



Figure A9. LDW Menus




Figure A10. Visual Alert


APPENDIX B


Excerpts from Owner's Manual


Vehicle Symbol Chart


Here are some additional symbols that may be found on the vehicle and what they mean. See the features in this manual for information.


 : Air Conditioning System


 : Air Conditioning Refrigerant Oil

 : Airbag Readiness Light

 : Antilock Brake System (ABS)

 : Brake System Warning Light

 : Dispose of Used Components Properly

 : Do Not Apply High Pressure Water

 : Engine Coolant Temperature


 : Flame/Fire Prohibited


 : Flammable

 : Forward Collision Alert

 : Fuse Block Cover Lock Location

 : Fuses

 : ISOFIX/LATCH System Child Restraints


 : Keep Fuse Block Covers Properly Installed

 : Lane Change Alert

 : Lane Departure Warning


 : Lane Keep Assist

 : Malfunction Indicator Lamp

 : Oil Pressure


 : Park Assist


 : Pedestrian Ahead Indicator

 : Power

 : Rear Cross Traffic Alert

 : Registered Technician

 : Remote Vehicle Start


 : Risk of Electrical Fire

 : Seat Belt Reminders

 : Side Blind Zone Alert

 : Stop/Start

 : Tire Pressure Monitor


 : Traction Control/StabiliTrak/Electronic Stability Control (ESC)

 : Under Pressure


 : Vehicle Ahead Indicator

4 Introduction

Instrument Panel Overview




Instrument Cluster



Base Level Cluster English Shown, Metric Similar

- | | |
|--|--|
| 1. Tachometer ⇨ 105 | 5. Voltmeter Gauge ⇨ 107 |
| 2. Engine Oil Pressure Gauge ⇨ 106 | 6. Speedometer ⇨ 105 |
| 3. Engine Coolant Temperature Gauge
⇨ 107 | 7. Driver Information Center (DIC) ⇨ 119 |
| 4. Fuel Gauge ⇨ 105 | |




Uplevel Cluster English Shown, Metric Similar

- | | |
|--|---|
| <ul style="list-style-type: none"> 1. Tachometer ⇨ 105 2. Engine Oil Pressure Gauge ⇨ 106 3. Engine Coolant Temperature Gauge ⇨ 107 | <ul style="list-style-type: none"> 4. Fuel Gauge ⇨ 105 5. Voltmeter Gauge ⇨ 107 6. Speedometer ⇨ 105 7. Driver Information Center (DIC) ⇨ 119 |
|--|---|

Cluster Menu

There is an interactive display area in the center of the instrument cluster.



Use the right steering wheel control to open and scroll through the different items and displays.

Press < or > to access the cluster applications. Use the thumbwheel to scroll through the list of available features. Press the thumbwheel to select. Not all applications will be available on all vehicles.

- Home

If the ABS warning light stays on, or comes on again while driving, the vehicle needs service. A chime may also sound when the light stays on.

If the ABS warning light is the only light on, the vehicle has regular brakes, but ABS is not functioning.

If both the ABS warning light and the brake system warning light are on, ABS is not functioning and there is a problem with the regular brakes. See your dealer for service.

See *Brake System Warning Light* ⇨ 111.

Four-Wheel-Drive Light



Auto Mode Shown, Other Modes Similar

If equipped, the four-wheel-drive light displays what mode the vehicle is in. The light will show each mode: 2WD, 4HI, AUTO (all transfer cases); 4LOW and N (two-speed transfer case only).

The light will flash when a shift is in progress. Once the shift is complete the light will be steady.

If the light turns amber, there may be a malfunction with the four-wheel-drive system. See your dealer.

See *Four-Wheel Drive* ⇨ 236.

Hill Descent Control Light



If equipped, the Hill Descent Control light comes on when the system is ready for use. When the light flashes, the system is active.

See *Hill Descent Control (HDC)* ⇨ 244.

Lane Keep Assist (LKA) Light



After the vehicle is started, this light turns off and stays off if LKA has not been turned on or is unavailable.

If equipped, this light is white if LKA is turned on, but not ready to assist.

This light is green if LKA is turned on and is ready to assist.

LKA may assist by gently turning the steering wheel if the vehicle approaches a detected lane marking. The LKA light is amber when assisting.




This light flashes amber as a Lane Departure Warning (LDW) alert, to indicate that the lane marking has been crossed.

LKA will not assist or alert if the turn signal is active in the direction of lane departure, or if LKA detects that you are accelerating, braking or actively steering.

See *Lane Keep Assist (LKA)* ⇨ 275.

Vehicle Ahead Indicator



4. Touch  or  to turn a feature off or on.
5. Touch  to go to the top level of the Settings menu.

The menu may contain the following:

Rear Seat Reminder

This allows for a chime and a message when the rear door has been opened before or during operation of the vehicle.

Touch Off or On.

Climate and Air Quality

Touch and the following may display:

- Auto Fan Speed
- Auto Cooled Seats
- Auto Heated Seats
- Auto Defog
- Auto Rear Defog

Auto Fan Speed

This setting specifies the amount of airflow when the climate control fan setting is Auto Fan.

Touch Low, Medium, or High.

Auto Cooled Seats

This setting automatically turns on and regulates the ventilated seats when the cabin temperature is warm. See *Heated and Ventilated Front Seats* ⇨ 43.

Touch Off or On.

Auto Heated Seats

This setting automatically turns on and regulates the heated seats when the cabin temperature is cool. The auto heated seats can be turned off by using the heated seat buttons on the center stack. See *Heated and Ventilated Front Seats* ⇨ 43.

If equipped with the auto heated steering wheel, this feature will turn on when the auto heated seats turn on.

Touch Off or On.

Auto Defog

This setting automatically directs air to the windshield to assist in defogging, based on temperature and humidity conditions.

Touch Off or On.

Auto Rear Defog

This setting automatically turns the rear defogger on based on temperature and humidity conditions.

Touch Off or On.

Collision/Detection Systems

Touch and the following may display:

- Alert Type
- Forward Collision System
- Front Pedestrian Detection
- Adaptive Cruise Go Notifier
- Lane Change Alert
- Park Assist
- Rear Camera Park Assist Symbols
- Rear Cross Traffic Alert
- Rear Pedestrian Detection

Alert Type

This feature sets the type of alert from the driver assistance systems to help avoid crashes.

Touch Beeps or Safety Alert Seat.

Forward Collision System

This setting can alert of a potential crash with a detected vehicle ahead and can apply brakes to help reduce a collision's severity.

Touch Off, Alert, or Alert and Brake.

Front Pedestrian Detection

This feature may help avoid or reduce the harm caused by front-end crashes with nearby pedestrians. See *Front Pedestrian Braking (FPB) System* ⇨ 270.

Touch Off, Alert, or Alert and Brake.

Adaptive Cruise Go Notifier

This setting determines if an alert will appear when Adaptive Cruise Control brings the vehicle to a complete stop and the vehicle ahead of you starts moving again. See *Adaptive Cruise Control (Advanced)* ⇨ 253.

Touch Off or On.

Lane Change Alert

This allows the feature to be turned on or off. See *Lane Change Alert (LCA)* ⇨ 272.

Touch Off or On.

Park Assist

This allows the feature to be turned on or off. See *Assistance Systems for Parking or Backing* ⇨ 262.

Select Off or On.

Rear Camera Park Assist Symbols

This setting enables the Rear Camera Park Assist Symbols. See *Assistance Systems for Parking or Backing* ⇨ 262.

Touch Off or On.

Rear Cross Traffic Alert

This allows the Rear Cross Traffic Alert feature to be turned on or off. See *Assistance Systems for Parking or Backing* ⇨ 262.

Touch Off or On.

Rear Pedestrian Detection

This setting specifies if alerts will display when the vehicle detects pedestrians behind when in R (Reverse). See *Rear Pedestrian Alert* ⇨ 266.

Touch Off, Alert, or Alert and Brake.

Comfort and Convenience

Touch and the following may display:

- Automatic Entry/Egress Assist
- Chime Volume
- Hands Free Liftgate/Trunk Control
- Reverse Tilt Mirror
- Remote Mirror Folding
- Rain Sense Wipers

- Auto Wipe in Reverse Gear

Automatic Entry/Egress Assist

This feature specifies if the vehicle will automatically lower to make it easier to enter or exit the vehicle.

Touch Off or On.

Chime Volume

This determines the chime volume level.

Touch the controls on the infotainment display to adjust the volume.

Hands Free Liftgate/Trunk Control

The liftgate may be operated with a kicking motion under the left corner of the rear bumper. See *Liftgate* ⇨ 18.

Touch Off, On-Open and Close, or On-Open Only.

Reverse Tilt Mirror

When on, the driver, passenger, or both driver and passenger outside mirrors will tilt downward when the vehicle is shifted into R (Reverse) to improve visibility of the ground near the rear wheels. They may move from their tilted position when the vehicle is shifted out of R (Reverse) or turned off. See *Reverse Tilt Mirrors* ⇨ 29.

Driving with a Trailer

Although this system is intended to help drivers avoid lane change crashes, it does not replace driver vision and therefore should be considered a lane change aid. Even with the ESBZA system, the driver must check carefully for objects outside of the reporting zone (e.g., a fast approaching vehicle) or vehicle along the side of the trailer before changing lanes.

Use caution while changing lanes when towing a trailer.

Lane Keep Assist (LKA)

If equipped, LKA may help avoid crashes due to unintentional lane departures. This system uses a camera to detect lane markings between 60 km/h (37 mph) and 180 km/h (112 mph). It may assist by gently turning the steering wheel if the vehicle approaches a detected lane marking. It may also provide a Lane Departure Warning (LDW) alert if the vehicle crosses a detected lane marking. LKA can be overridden by turning the steering wheel. This system is not intended to keep the vehicle centered in the lane. LKA will not assist and alert if the

turn signal is active in the direction of lane departure, or if it detects that you are accelerating, braking or actively steering.

⚠ Warning

The LKA system does not continuously steer the vehicle. It may not keep the vehicle in the lane or give a Lane Departure Warning (LDW) alert, even if a lane marking is detected.

The LKA and LDW systems may not:

- Provide an alert or enough steering assist to avoid a lane departure or crash.
- Detect lane markings under poor weather or visibility conditions. This can occur if the windshield or headlamps are blocked by dirt, snow, or ice; if they are not in proper condition; or if the sun shines directly into the camera.
- Detect road edges.
- Detect lanes on winding or hilly roads.

If LKA only detects lane markings on one side of the road, it will only assist or provide an LDW alert when approaching
(Continued)

Warning (Continued)

the lane on the side where it has detected a lane marking. Even with LKA and LDW, you must steer the vehicle. Always keep your attention on the road and maintain proper vehicle position within the lane, or vehicle damage, injury, or death could occur. Always keep the windshield, headlamps, and camera sensors clean and in good repair. Do not use LKA in bad weather conditions or on roads with unclear lane markings, such as construction zones.


⚠ Warning





Using LKA while towing a trailer or on slippery roads could cause loss of control of the vehicle and a crash. Turn the system off.

How the System Works

LKA uses a camera sensor installed on the windshield ahead of the rearview mirror to detect lane markings. It may provide brief steering assist if it detects an unintended lane departure. It may further provide an

audible alert or the driver seat may pulse indicating that a lane marking has been crossed.

To turn LKA on and off, press  to the left of the steering wheel. If equipped, the indicator light on the button comes on when LKA is on and turns off when LKA is disabled.

When on,  is white, if equipped, indicating that the system is not ready to assist.  is green if LKA is ready to assist. LKA may assist by gently turning the steering wheel if the vehicle approaches a detected lane marking.  is amber when assisting. It may also provide a Lane Departure Warning (LDW) alert by flashing  amber if the vehicle crosses a detected lane marking. Additionally, there may be three beeps, or the driver seat may pulse three times, on the right or left, depending on the lane departure direction.

Take Steering

The LKA system does not continuously steer the vehicle. If LKA does not detect active driver steering, an alert and chime may be provided. Steer the vehicle to dismiss. LKA may become temporarily unavailable after repeated take steering alerts.

When the System Does Not Seem to Work Properly

The system performance may be affected by:

- Close vehicles ahead.
- Sudden lighting changes, such as when driving through tunnels.
- Banked roads.
- Roads with poor lane markings, such as two-lane roads.

If the LKA system is not functioning properly when lane markings are clearly visible, cleaning the windshield may help.

A camera blocked message may display if the camera is blocked. Some driver assistance systems may have reduced performance or not work at all. An LKA or LDW unavailable message may display if the systems are temporarily unavailable. This message could be due to a blocked camera. The LKA system does not need service. Clean the outside of the windshield behind the rearview mirror.

LKA assistance and/or LDW alerts may occur due to tar marks, shadows, cracks in the road, temporary or construction lane markings, or other road imperfections. This

is normal system operation; the vehicle does not need service. Turn LKA off if these conditions continue.

Fuel

Top Tier Fuel

GM recommends the use of TOP TIER Detergent Gasoline to keep the engine clean, reduce engine deposits, and maintain optimal vehicle performance. Look for the TOP TIER Logo or see www.toptiergas.com for a list of TOP TIER Detergent Gasoline marketers and applicable countries.



APPENDIX C

Run Log

Subject Vehicle: 2021 Chevrolet Tahoe 2WD High Country

Test Date: 2/12/2021

Driver: A. Ricci

Note: For Distance at Warning, positive values indicate inside the lane

Run	Lane Marking Type	Departure Direction	Valid Run?	Distance at Auditory Alert (ft)	Distance at Visual Alert (ft)	Pass/Fail	Notes
1	Dashed	Left	Y	-1.17	0.32	Pass	
2			Y	-1.20	0.49	Pass	
3			Y	-1.25	0.19	Pass	
4			Y	NW ²	0.51	Pass	
5			Y	-0.99	0.38	Pass	
6			Y	-1.20	0.46	Pass	
7			Y	-1.30	0.48	Pass	
8	Dashed	Right	Y	NW	2.01	Pass	No audible warning for right departure
9			N				SV speed
10			Y	NW	NW	Fail	No warning (no lane recognition at all)
11			Y	NW	1.87	Pass	
12			Y	NW	1.86	Pass	
13			Y	NW	1.74	Pass	
14			Y	NW	1.92	Pass	
15			Y	NW	NW	Fail	No warning (no lane recognition at all)

² No Warning

Run	Lane Marking Type	Departure Direction	Valid Run?	Distance at Audible Alert (ft)	Distance at Visual Alert (ft)	Pass/Fail	Notes
16	Solid	Right	Y	NW	1.55	Pass	No audible warning for right departure
17			Y	NW	1.75	Pass	
18			Y	NW	1.45	Pass	
19			Y	NW	1.61	Pass	
20			Y	NW	1.49	Pass	
21			Y	NW	1.71	Pass	
22			Y	NW	1.69	Pass	
23	Solid	Left	Y	-0.98	0.55	Pass	
24			N				SV speed
25			Y	-1.05	0.74	Pass	
26			Y	-1.09	0.48	Pass	
27			Y	-1.13	0.62	Pass	
28			Y	-0.96	0.42	Pass	
29			Y	-1.15	0.56	Pass	
30			Y	-1.10	0.48	Pass	
31	Botts	Left	Y	-1.56	0.34	Pass	
32			Y	-1.33	0.20	Pass	
33			Y	-1.46	0.24	Pass	
34			Y	-1.53	0.20	Pass	
35			Y	-1.60	0.38	Pass	
36			Y	-1.37	0.15	Pass	
37			Y	-1.34	0.20	Pass	

Run	Lane Marking Type	Departure Direction	Valid Run?	Distance at Audible Alert (ft)	Distance at Visual Alert (ft)	Pass/Fail	Notes
38	Botts	Right	Y	NW	1.64	Pass	No audible warning for right departure
39			Y	NW	1.85	Pass	
40			Y	NW	1.91	Pass	
41			Y	NW	1.63	Pass	
42			Y	NW	1.82	Pass	
43			Y	NW	1.61	Pass	
44			Y	NW	1.74	Pass	

APPENDIX D

Time History Plots

LIST OF FIGURES

	Page
Figure D1. Example Time History for Lane Departure Warning Test, Passing.....	D-8
Figure D2. Example Time History for Lane Departure Warning Test, Failing, No Warning Issued.....	D-9
Figure D3. Example Time History for Lane Departure Warning Test, Invalid Run Due to Subject Vehicle Yaw Rate	D-10
Figure D4. Time History for Run 01, Dashed Line, Left Departure, Auditory Warning.....	D-11
Figure D5. Time History for Run 01, Dashed Line, Left Departure, Visual Warning.....	D-12
Figure D6. Time History for Run 02, Dashed Line, Left Departure, Auditory Warning.....	D-13
Figure D7. Time History for Run 02, Dashed Line, Left Departure, Visual Warning.....	D-14
Figure D8. Time History for Run 03, Dashed Line, Left Departure, Auditory Warning.....	D-15
Figure D9. Time History for Run 03, Dashed Line, Left Departure, Visual Warning.....	D-16
Figure D10. Time History for Run 04, Dashed Line, Left Departure, Auditory Warning.....	D-17
Figure D11. Time History for Run 04, Dashed Line, Left Departure, Visual Warning.....	D-18
Figure D12. Time History for Run 05, Dashed Line, Left Departure, Auditory Warning.....	D-19
Figure D13. Time History for Run 05, Dashed Line, Left Departure, Visual Warning.....	D-20
Figure D14. Time History for Run 06, Dashed Line, Left Departure, Auditory Warning.....	D-21
Figure D15. Time History for Run 06, Dashed Line, Left Departure, Visual Warning.....	D-22
Figure D16. Time History for Run 07, Dashed Line, Left Departure, Auditory Warning.....	D-23
Figure D17. Time History for Run 07, Dashed Line, Left Departure, Visual Warning.....	D-24
Figure D18. Time History for Run 08, Dashed Line, Right Departure, Auditory Warning	D-25
Figure D19. Time History for Run 08, Dashed Line, Right Departure, Visual Warning.....	D-26
Figure D20. Time History for Run 10, Dashed Line, Right Departure, Auditory Warning	D-27
Figure D21. Time History for Run 10, Dashed Line, Right Departure, Visual Warning.....	D-28
Figure D22. Time History for Run 11, Dashed Line, Right Departure, Auditory Warning	D-29
Figure D23. Time History for Run 11, Dashed Line, Right Departure, Visual Warning.....	D-30
Figure D24. Time History for Run 12, Dashed Line, Right Departure, Auditory Warning	D-31
Figure D25. Time History for Run 12, Dashed Line, Right Departure, Visual Warning.....	D-32
Figure D26. Time History for Run 13, Dashed Line, Right Departure, Auditory Warning	D-33
Figure D27. Time History for Run 13, Dashed Line, Right Departure, Visual Warning.....	D-34
Figure D28. Time History for Run 14, Dashed Line, Right Departure, Auditory Warning	D-35
Figure D29. Time History for Run 14, Dashed Line, Right Departure, Visual Warning.....	D-36
Figure D30. Time History for Run 15, Dashed Line, Right Departure, Auditory Warning	D-37
Figure D31. Time History for Run 15, Dashed Line, Right Departure, Visual Warning.....	D-38
Figure D32. Time History for Run 16, Solid Line, Right Departure, Auditory Warning.....	D-39
Figure D33. Time History for Run 16, Solid Line, Right Departure, Visual Warning.....	D-40
Figure D34. Time History for Run 17, Solid Line, Right Departure, Auditory Warning.....	D-41
Figure D35. Time History for Run 17, Solid Line, Right Departure, Visual Warning.....	D-42
Figure D36. Time History for Run 18, Solid Line, Right Departure, Auditory Warning.....	D-43
Figure D37. Time History for Run 18, Solid Line, Right Departure, Visual Warning.....	D-44
Figure D38. Time History for Run 19, Solid Line, Right Departure, Auditory Warning.....	D-45

Figure D39.	Time History for Run 19, Solid Line, Right Departure, Visual Warning	D-46
Figure D40.	Time History for Run 20, Solid Line, Right Departure, Auditory Warning.....	D-47
Figure D41.	Time History for Run 20, Solid Line, Right Departure, Visual Warning	D-48
Figure D42.	Time History for Run 21, Solid Line, Right Departure, Auditory Warning.....	D-49
Figure D43.	Time History for Run 21, Solid Line, Right Departure, Visual Warning	D-50
Figure D44.	Time History for Run 22, Solid Line, Right Departure, Auditory Warning.....	D-51
Figure D45.	Time History for Run 22, Solid Line, Right Departure, Visual Warning	D-52
Figure D46.	Time History for Run 23, Solid Line, Left Departure, Auditory Warning	D-53
Figure D47.	Time History for Run 23, Solid Line, Left Departure, Visual Warning	D-54
Figure D48.	Time History for Run 25, Solid Line, Left Departure, Auditory Warning	D-55
Figure D49.	Time History for Run 25, Solid Line, Left Departure, Visual Warning	D-56
Figure D50.	Time History for Run 26, Solid Line, Left Departure, Auditory Warning	D-57
Figure D51.	Time History for Run 26, Solid Line, Left Departure, Visual Warning	D-58
Figure D52.	Time History for Run 27, Solid Line, Left Departure, Auditory Warning	D-59
Figure D53.	Time History for Run 27, Solid Line, Left Departure, Visual Warning	D-60
Figure D54.	Time History for Run 28, Solid Line, Left Departure, Auditory Warning	D-61
Figure D55.	Time History for Run 28, Solid Line, Left Departure, Visual Warning	D-62
Figure D56.	Time History for Run 29, Solid Line, Left Departure, Auditory Warning	D-63
Figure D57.	Time History for Run 29, Solid Line, Left Departure, Visual Warning	D-64
Figure D58.	Time History for Run 30, Solid Line, Left Departure, Auditory Warning	D-65
Figure D59.	Time History for Run 30, Solid Line, Left Departure, Visual Warning	D-66
Figure D60.	Time History for Run 31, Botts Dots, Left Departure, Auditory Warning	D-67
Figure D61.	Time History for Run 31, Botts Dots, Left Departure, Visual Warning	D-68
Figure D62.	Time History for Run 32, Botts Dots, Left Departure, Auditory Warning	D-69
Figure D63.	Time History for Run 32, Botts Dots, Left Departure, Visual Warning	D-70
Figure D64.	Time History for Run 33, Botts Dots, Left Departure, Auditory Warning	D-71
Figure D65.	Time History for Run 33, Botts Dots, Left Departure, Visual Warning	D-72
Figure D66.	Time History for Run 34, Botts Dots, Left Departure, Auditory Warning	D-73
Figure D67.	Time History for Run 34, Botts Dots, Left Departure, Visual Warning	D-74
Figure D68.	Time History for Run 35, Botts Dots, Left Departure, Auditory Warning	D-75
Figure D69.	Time History for Run 35, Botts Dots, Left Departure, Visual Warning	D-76
Figure D70.	Time History for Run 36, Botts Dots, Left Departure, Auditory Warning	D-77
Figure D71.	Time History for Run 36, Botts Dots, Left Departure, Visual Warning	D-78
Figure D72.	Time History for Run 37, Botts Dots, Left Departure, Auditory Warning	D-79
Figure D73.	Time History for Run 37, Botts Dots, Left Departure, Visual Warning	D-80
Figure D74.	Time History for Run 38, Botts Dots, Right Departure, Auditory Warning.....	D-81
Figure D75.	Time History for Run 38, Botts Dots, Right Departure, Visual Warning	D-82
Figure D76.	Time History for Run 39, Botts Dots, Right Departure, Auditory Warning.....	D-83
Figure D77.	Time History for Run 39, Botts Dots, Right Departure, Visual Warning	D-84
Figure D78.	Time History for Run 40, Botts Dots, Right Departure, Auditory Warning.....	D-85
Figure D79.	Time History for Run 40, Botts Dots, Right Departure, Visual Warning	D-86
Figure D80.	Time History for Run 41, Botts Dots, Right Departure, Auditory Warning.....	D-87
Figure D81.	Time History for Run 41, Botts Dots, Right Departure, Visual Warning	D-88

Figure D82. Time History for Run 42, Botts Dots, Right Departure, Auditory Warning	D-89
Figure D83. Time History for Run 42, Botts Dots, Right Departure, Visual Warning	D-90
Figure D84. Time History for Run 43, Botts Dots, Right Departure, Auditory Warning	D-91
Figure D85. Time History for Run 43, Botts Dots, Right Departure, Visual Warning	D-92
Figure D86. Time History for Run 44, Botts Dots, Right Departure, Auditory Warning	D-93
Figure D87. Time History for Run 44, Botts Dots, Right Departure, Visual Warning	D-94

Description of Time History Plots

A set of time history plots is provided for each valid run in the test series. Each set of plots comprises time varying data from the Subject Vehicle, as well as pass/fail envelopes and thresholds. The following is a description of data types shown in the time history plots, as well as a description of the color code for data envelopes.

Time History Plot Description

Time history figures include the following sub-plots:

- Warning – Indicates timing of warning issued by LDW system. Depending on the type of LDW alert or instrumentation used to measure the alert, this can be any of the following:
 - Filtered and rectified sound signal
 - Filtered and rectified acceleration (e.g., steering wheel vibration)
 - Light sensor signal
 - Discrete on/off value
- Speed (mph) – Speed of the Subject Vehicle
- Yaw Rate (deg/sec) – Yaw rate of the Subject Vehicle
- Distance to Lane Edge (ft) – Lateral distance (in lane coordinates) from the outer front tire bulge to the inside edge of the lane marking of interest for a given test (a positive value indicates the vehicle is completely within the lane while a negative value indicates that the outer front tire bulge has crossed over the inner lane marking edge). The distance to the lane edge at the moment the LDW alert is issued, is displayed to the right of subplot.
- Lateral Lane Velocity (ft/sec) – Lateral velocity (in lane coordinates) of the outer front tire bulge
- Bird's Eye View – Indicates the position of the Subject Vehicle with respect to the lane marking of interest for a given test. Green rectangles represent the Subject Vehicle's position at approximately 2 second intervals, while the yellow rectangle indicates the position of the Subject Vehicle at the time of LDW warning issuance.

Envelopes and Thresholds

Each of the time history plot figures can contain either green or yellow envelopes and/or black threshold lines. These envelopes and thresholds are used to programmatically and visually determine the validity of a given test run. Envelope and threshold exceedances are indicated with either red shading or red asterisks, and red text is placed to the right side of the plot indicating the type of exceedance.

Green envelopes indicate that the time-varying data should not exceed the envelope boundaries at any time within the envelope. Exceedances of a green envelope are indicated by red shading in the area between the measured time-varying data and the envelope boundaries.

Yellow envelopes indicate that the time-varying data should not exceed the envelope only at the right end. Exceedances at the right extent of a yellow envelope are indicated by red asterisks. Data within the boundaries at the right extent of a yellow envelope are indicated by green circles.

For the warning plot, a dashed black threshold line indicates the threshold used to determine the onset of the LDW alert. The alert is considered on the first time the alert signal crosses this threshold line.

Color Codes

Color codes have been adopted to easily identify the types of data, envelopes, and thresholds used in the plots.

Color codes can be broken into three categories:

1. Validation envelopes and thresholds
 1. Validation envelopes and thresholds
 2. Instantaneous samplings
 3. Text
1. Validation envelope and threshold color codes:
 - Green envelope = time varying data must be within the envelope at all times in order to be valid
 - Yellow envelope = time varying data must be within limits at right end
 - Black threshold (Solid) = time varying data must not exceed this threshold in order to be valid
 - Black threshold (Dashed) = for reference only – this can include warning level thresholds which are used to determine the timing of the alert
2. Instantaneous sampling color codes:
 - Green circle = passing or valid value at a given moment in time
 - Red asterisk = failing or invalid value at a given moment in time

3. Text color codes:


- Green = passing or valid value
- Red = failing or invalid value

Other Notations

- NG – Indicates that the value for that variable was outside of bounds and therefore “No Good”.
- No Wng – No warning was detected.


The minimum (worst) GPS fix type is displayed in the lower right corner of each page. The only valid fix type is RTK fixed (displayed in green). If the fix type during any portion of the test was anything other than RTK fixed, then “RTK Fixed OR LESS!!” is displayed in red.

Examples of time history plots (including passing, failing and invalid runs) are shown in Figure D1 through Figure D3. Actual time history data plots for the vehicle under consideration are provided subsequently.




GPS Fix Type: RTK Fixed

Figure D1. Example Time History for Lane Departure Warning Test, Passing




GPS Fix Type: RTK Fixed

Figure D2. Example Time History for Lane Departure Warning Test, Failing, No Warning Issued




GPS Fix Type: RTK Fixed

Figure D3. Example Time History for Lane Departure Warning Test, Invalid Run Due to Subject Vehicle Yaw Rate




GPS Fix Type: RTK Fixed

Figure D4. Time History for Run 01, Dashed Line, Left Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D5. Time History for Run 01, Dashed Line, Left Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D6. Time History for Run 02, Dashed Line, Left Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D7. Time History for Run 02, Dashed Line, Left Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D8. Time History for Run 03, Dashed Line, Left Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D9. Time History for Run 03, Dashed Line, Left Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D10. Time History for Run 04, Dashed Line, Left Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D11. Time History for Run 04, Dashed Line, Left Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D12. Time History for Run 05, Dashed Line, Left Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D13. Time History for Run 05, Dashed Line, Left Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D14. Time History for Run 06, Dashed Line, Left Departure, Auditory Warning



GPS Fix Type: RTK Fixed

Figure D15. Time History for Run 06, Dashed Line, Left Departure, Visual Warning



GPS Fix Type: RTK Fixed

Figure D16. Time History for Run 07, Dashed Line, Left Departure, Auditory Warning






Figure D17. Time History for Run 07, Dashed Line, Left Departure, Visual Warning



GPS Fix Type: RTK Fixed

Figure D18. Time History for Run 08, Dashed Line, Right Departure, Auditory Warning



GPS Fix Type: RTK Fixed

Figure D19. Time History for Run 08, Dashed Line, Right Departure, Visual Warning






Figure D20. Time History for Run 10, Dashed Line, Right Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D21. Time History for Run 10, Dashed Line, Right Departure, Visual Warning



GPS Fix Type: RTK Fixed


Figure D22. Time History for Run 11, Dashed Line, Right Departure, Auditory Warning



1.87 ft


GPS Fix Type: RTK Fixed

Figure D23. Time History for Run 11, Dashed Line, Right Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D24. Time History for Run 12, Dashed Line, Right Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D25. Time History for Run 12, Dashed Line, Right Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D26. Time History for Run 13, Dashed Line, Right Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D27. Time History for Run 13, Dashed Line, Right Departure, Visual Warning



GPS Fix Type: RTK Fixed

Figure D28. Time History for Run 14, Dashed Line, Right Departure, Auditory Warning



GPS Fix Type: RTK Fixed

Figure D29. Time History for Run 14, Dashed Line, Right Departure, Visual Warning






Figure D30. Time History for Run 15, Dashed Line, Right Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D31. Time History for Run 15, Dashed Line, Right Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D32. Time History for Run 16, Solid Line, Right Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D33. Time History for Run 16, Solid Line, Right Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D34. Time History for Run 17, Solid Line, Right Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D35. Time History for Run 17, Solid Line, Right Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D36. Time History for Run 18, Solid Line, Right Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D37. Time History for Run 18, Solid Line, Right Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D38. Time History for Run 19, Solid Line, Right Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D39. Time History for Run 19, Solid Line, Right Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D40. Time History for Run 20, Solid Line, Right Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D41. Time History for Run 20, Solid Line, Right Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D42. Time History for Run 21, Solid Line, Right Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D43. Time History for Run 21, Solid Line, Right Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D44. Time History for Run 22, Solid Line, Right Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D45. Time History for Run 22, Solid Line, Right Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D46. Time History for Run 23, Solid Line, Left Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D47. Time History for Run 23, Solid Line, Left Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D48. Time History for Run 25, Solid Line, Left Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D49. Time History for Run 25, Solid Line, Left Departure, Visual Warning



GPS Fix Type: RTK Fixed

Figure D50. Time History for Run 26, Solid Line, Left Departure, Auditory Warning



GPS Fix Type: RTK Fixed

Figure D51. Time History for Run 26, Solid Line, Left Departure, Visual Warning






Figure D52. Time History for Run 27, Solid Line, Left Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D53. Time History for Run 27, Solid Line, Left Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D54. Time History for Run 28, Solid Line, Left Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D55. Time History for Run 28, Solid Line, Left Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D56. Time History for Run 29, Solid Line, Left Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D57. Time History for Run 29, Solid Line, Left Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D58. Time History for Run 30, Solid Line, Left Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D59. Time History for Run 30, Solid Line, Left Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D60. Time History for Run 31, Botts Dots, Left Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D61. Time History for Run 31, Botts Dots, Left Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D62. Time History for Run 32, Botts Dots, Left Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D63. Time History for Run 32, Botts Dots, Left Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D64. Time History for Run 33, Botts Dots, Left Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D65. Time History for Run 33, Botts Dots, Left Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D66. Time History for Run 34, Botts Dots, Left Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D67. Time History for Run 34, Botts Dots, Left Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D68. Time History for Run 35, Botts Dots, Left Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D69. Time History for Run 35, Botts Dots, Left Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D70. Time History for Run 36, Botts Dots, Left Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D71. Time History for Run 36, Botts Dots, Left Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D72. Time History for Run 37, Botts Dots, Left Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D73. Time History for Run 37, Botts Dots, Left Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D74. Time History for Run 38, Botts Dots, Right Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D75. Time History for Run 38, Botts Dots, Right Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D76. Time History for Run 39, Botts Dots, Right Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D77. Time History for Run 39, Botts Dots, Right Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D78. Time History for Run 40, Botts Dots, Right Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D79. Time History for Run 40, Botts Dots, Right Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D80. Time History for Run 41, Botts Dots, Right Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D81. Time History for Run 41, Botts Dots, Right Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D82. Time History for Run 42, Botts Dots, Right Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D83. Time History for Run 42, Botts Dots, Right Departure, Visual Warning




GPS Fix Type: RTK Fixed

Figure D84. Time History for Run 43, Botts Dots, Right Departure, Auditory Warning




GPS Fix Type: RTK Fixed

Figure D85. Time History for Run 43, Botts Dots, Right Departure, Visual Warning



GPS Fix Type: RTK Fixed

Figure D86. Time History for Run 44, Botts Dots, Right Departure, Auditory Warning



GPS Fix Type: RTK Fixed

Figure D87. Time History for Run 44, Botts Dots, Right Departure, Visual Warning